

Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

### 1 Identification

· Product identifier

· Trade name: Phorate Standard (1X1 mL)

· Part number: PST-800K100A01

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd.

Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: acetone
- · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

(Contd. on page 2)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

(Contd. of page 1)

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

67-64-1 acetone

99.987%

### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \ Indication \ of \ any \ immediate \ medical \ attention \ and \ special \ treatment \ needed$

No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### **6 Accidental release measures**

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| · PAC-1:               |                         |
|------------------------|-------------------------|
| 67-64-1 acetone        | 200 ppm                 |
| 298-02-2 phorate (ISO) | $0.0036 \text{ mg/m}^3$ |
| · PAC-2:               |                         |
| 67-64-1 acetone        | 3200* ppm               |
| 298-02-2 phorate (ISO) | $0.040 \text{ mg/m}^3$  |
| · PAC-3:               |                         |
| 67-64-1 acetone        | 5700* ppm               |
| 298-02-2 phorate (ISO) | $0.12 \text{ mg/m}^3$   |

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

Protect against electrostatic charges.

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

#### · Components with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

| PEL | Long-term value: 2400 mg/m³, 1000 ppm  |
|-----|--|
| REL | Long-term value: 590 mg/m³, 250 ppm  |
| TLV | Short-term value: 1187 mg/m³, 500 ppm<br>Long-term value: 594 mg/m³, 250 ppm |
|     | Long-term value: 594 mg/m³, 250 ppm  |
|     | REI STATE  |

#### · Ingredients with biological limit values:

#### 67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

### · Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

(Contd. on page 5)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

(Contd. of page 4)

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

• **Penetration time of glove material** For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles

| Information on basic physical and c | chemical properties  |  |
|-------------------------------------|--|--|
| General Information                 |  |  |
| Appearance: Form:                   | Fluid  |  |
| Color:                              | Colorless  |  |
| Odor:                               | Characteristic   |  |
| Odor threshold:                     | Not determined.  |  |
| pH-value:                           | Not determined.  |  |
| Change in condition                 |  |  |
| Melting point/Melting range:        | -94.7 °C (-138.5 °F)   |  |
| <b>Boiling point/Boiling range:</b> | 55 °C (131 °F)   |  |
| Flash point:                        | -17 °C (1.4 °F)  |  |
| Flammability (solid, gaseous):      | Not applicable.  |  |
| Ignition temperature:               | 465 °C (869 °F)  |  |
| Decomposition temperature:          | Not determined.  |  |
| Auto igniting:                      | Product is not selfigniting.   |  |
| Danger of explosion:                | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |  |
| Explosion limits:                   |  |  |
| Lower:                              | 2.6 Vol %  |  |
| Upper:                              | 13 Vol %   |  |
| Vapor pressure at 20 °C (68 °F):    | 245.3 hPa (184 mm Hg)  |  |
| Density at 20 °C (68 °F):           | 0.80004 g/cm³ (6.67633 lbs/gal)  |  |
| Relative density                    | Not determined.  |  |
| Vapor density                       | Not determined.  |  |
| Evaporation rate                    | Not determined.  |  |
| Solubility in / Miscibility with    |  |  |
| Water:                              | Not miscible or difficult to mix.  |  |

(Contd. on page 6)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

(Contd. of page 5)

Viscosity:
 Dynamic:
 Kinematic:
 Not determined.
 Not determined.

· Solvent content:

Organic solvents: 100.0 % VOC content: 0.01 %

0.1 g/l / 0.00 lb/gal

• Other information No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC | 50 valu         | es that are relevant for classification: |  |
|---------|-----------------|--|--|
| 67-64-1 | 67-64-1 acetone |  |  |
| Oral    | LD50            | 5,800 mg/kg (rat)                        |  |
| Dermal  | LD50            | 20,000 mg/kg (rabbit)                    |  |
| 298-02- | 2 phor          | ate (ISO)                                |  |
| Oral    | LD50            | 1.6 mg/kg (rat)                          |  |
| Dermal  | LD50            | 2.5 mg/kg (rat)                          |  |

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

### · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

### · NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

| · Not Regulated, De minimus Quantities | -  |
|--|--|
| · UN-Number<br>· DOT, IMDG, IATA       | UN1993   |
| · UN proper shipping name              |  |
| · DOT                                  | Flammable liquids, n.o.s. (Acetone)                |
| · IMDG                                 | FLAMMABLE LIQUID, N.O.S. (ACETONE, phorate (ISO)), |
|  | MARINE POLLUTANT                                   |
| · IATA                                 | FLAMMABLE LIQUID, N.O.S. (ACETONE)                 |
|  |  |

- · Transport hazard class(es)
- · DOT, IATA



Class 3 Flammable liquids

(Contd. on page 8)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

|                                      | (Contd. of pag  |
|--------------------------------------|---|
| Label                                | 3   |
| IMDG                                 |   |
|                                      |   |
| · Class                              | 3 Flammable liquids   |
| Label                                | 3   |
| Packing group<br>DOT, IMDG, IATA     | II  |
| Environmental hazards:               | Product contains environmentally hazardous substances: phorate (ISO)                                |
| Marine pollutant:                    | Symbol (fish and tree)  |
| Special precautions for user         | Warning: Flammable liquids  |
| Danger code (Kemler):                | 33  |
| EMS Number:                          | F-E, <u>S-E</u>   |
| Stowage Category                     | В   |
| Transport in bulk according to Annex |   |
| MARPOL73/78 and the IBC Code         | Not applicable.   |
| Transport/Additional information:    |   |
| · DOT                                |   |
| Quantity limitations                 | On passenger aircraft/rail: 5 L   |
|                                      | On cargo aircraft only: 60 L  |
| · IMDG                               |   |
| Limited quantities (LQ)              | 1L  |
| Excepted quantities (EQ)             | Code: E2  |
|                                      | Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
|                                      |   |
| UN "Model Regulation":               | UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), 3, II, ENVIRONMENTALLY HAZARDOUS                        |

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara

| · Section 355 | (extremely | hazardous | s substances | ): |
|---------------|------------|-----------|--------------|----|
|---------------|------------|-----------|--------------|----|

298-02-2 phorate (ISO)

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

67-64-1 acetone

(Contd. on page 9)



Printing date 03/30/2019 Version Number 2 Reviewed on 03/30/2019

Trade name: Phorate Standard (1X1 mL)

|   | (Contd. of page |
|---|-----------------|
| · Proposition 65  |                 |
| Chemicals known to cause cancer:  |                 |
| None of the ingredients is listed.  |                 |
| Chemicals known to cause reproductive toxicity for females:                       |                 |
| None of the ingredients is listed.  |                 |
| Chemicals known to cause reproductive toxicity for males:                         |                 |
| None of the ingredients is listed.  |                 |
| Chemicals known to cause developmental toxicity:                                  |                 |
| None of the ingredients is listed.  |                 |
| Carcinogenic categories   |                 |
| EPA (Environmental Protection Agency)   |                 |
| 67-64-1 acetone   |                 |
| TLV (Threshold Limit Value established by ACGIH)                                  |                 |
| 67-64-1 acetone   | A               |
| 298-02-2 phorate (ISO)  | A               |
| NIOSH-Ca (National Institute for Occupational Safety and Health)                  |                 |
| None of the ingredients is listed.  |                 |
| Chemical safety assessment: A Chemical Safety Assessment has not been carried out | t.              |

## 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- $\cdot \textbf{Contact:} \ regulatory @ultrasci.com$
- · Date of preparation / last revision 03/30/2019 / 1
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

(Contd. on page 10)



Printing date 03/30/2019 Reviewed on 03/30/2019 Version Number 2

Trade name: Phorate Standard (1X1 mL)

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 ·\* Data compared to the previous version altered.