

SAFETY DATA SHEET



Polaris Si and NH2 LC Columns with less than 10 ml solvent

Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier

- Product name** : Polaris Si and NH2 LC Columns with less than 10 ml solvent
- Part no.** : A2003020X020, A2003030X020, A2003050G100, A2003050X030, A2003050X046, A2003100X020, A2003100X030, A2003100X046, A2003125X040, A2003125X046, A2003150X020, A2003150X021, A2003150X030, A2003150X040, A2003150X046, A2003150X100, A2003250X020, A2003250X021, A2003250X030, A2003250X040, A2003250X046, A2003MG, A2003MG2, A2004150X039, A2004250X046, A2004MG, A2004MG2, A2005020X020, A2005030X020, A2005030X021, A2005050X020, A2005050X021, A2005050X030, A2005050X046, A2005100X020, A2005100X030, A2005100X046, A2005150X020, A2005150X030, A2005150X046, A2005250X020, A2005250X030, A2005250X046, A2005MG, A2005MG2, A2013020X020, A2013030X020, A2013050G100, A2013050X020, A2013050X046, A2013100X020, A2013100X030, A2013100X046, A2013125X040, A2013150X020, A2013150X030, A2013150X039, A2013150X040, A2013150X046, A2013250X020, A2013250X021, A2013250X030, A2013250X046, A2013MG, A2013MG2, A2014020X020, A2014030X020, A2014030X021, A2014050X020, A2014050X021, A2014050X030, A2014050X046, A2014100X020, A2014100X021, A2014100X030, A2014100X046, A2014150X020, A2014150X030, A2014150X046, A2014250X020, A2014250X030, A2014250X046, A2014MG, A2014MG2, 79925CN-564, 79925CN-584, 79925DI-564, 79925DI-584, 79925MO-58K, 79925OD-58K, 79925SI-584

Validation date : 5/20/2025

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Identified uses** : Analytical chemistry.
 HPLC column
 Solvent volume:<10 ml
- | | |
|--------------|--|
| A2003020X020 | Polaris 5 Si 20 x 2.0mm, 0.1 ml tube, 0.04 ml solvent |
| A2003030X020 | Polaris 5 Si 30 x 2.0mm, 0.1 ml tube, 0.06 ml solvent |
| A2003050G100 | Polaris 5 Si-A 50 X 10.0mm Guard, 3.9 ml tube, 2.36 ml solvent |
| A2003050X030 | Polaris 5 Si 50 x 3.0mm, 0.4 ml tube, 0.21 ml solvent |
| A2003050X046 | Polaris 5 Si 50 x 4.6mm, 0.8 ml tube, 0.05 ml solvent |
| A2003100X020 | Polaris 5 Si 100 x 2.0mm, 0.3 ml tube, 0.19 ml solvent |
| A2003100X030 | Polaris 5 Si 100 x 3.0mm, 0.7 ml tube, 0.42 ml solvent |
| A2003100X046 | Polaris 5 Si 100 x 4.6mm, 1.7 ml tube, 1.00 ml solvent |
| A2003125X040 | Polaris 5 Si 125 x 4.0mm, 1.6 ml tube, 0.94 ml solvent |
| A2003125X046 | Polaris 5 Si 125 x 4.6mm, 2.1 ml tube, 1.25 ml solvent |
| A2003150X020 | Polaris 5 Si 150 x 2.0mm, 0.5 ml tube, 0.28 ml solvent |
| A2003150X021 | Polaris 5 Si 150 x 2.1mm, 0.5 ml tube, 0.31 ml solvent |
| A2003150X030 | Polaris 5 Si 150 x 3.0mm, 1.1 ml tube, 0.64 ml solvent |
| A2003150X040 | Polaris 5 Si 150 x 4.0mm, 1.9 ml tube, 1.13 ml solvent |
| A2003150X046 | Polaris 5 Si 150 x 4.6mm, 2.5 ml tube, 1.50 ml solvent |
| A2003150X100 | Polaris 5 Si 150 x 10.0mm, 12 ml tube, 7.07 ml solvent |
| A2003250X020 | Polaris 5 Si 250 x 2.0mm, 0.8 ml tube, 0.047 ml solvent |
| A2003250X021 | Polaris 5 Si 250 x 2.1mm, 0.9 ml tube, 0.52 ml solvent |
| A2003250X030 | Polaris 5 Si 250 x 3.0mm, 1.8 ml tube, 1.06 ml solvent |
| A2003250X040 | Polaris 5 Si 250 x 4.0mm, 3.1 ml tube, 1.88 ml solvent |
| A2003250X046 | Polaris 5 Si 250 x 4.6mm, 4.2 ml tube, 2.49 ml solvent |
| A2003MG | MetaGuard 4.6mm Polaris Si-A 5u, 0.2 ml tube, 0.10 ml solvent |
| A2003MG2 | MetaGuard 2.0mm Polaris Si-A 5u, 0.03 ml tube, 0.02 ml solvent |
| A2004150X039 | Polaris 10 Si 150 x 3.9mm, 1.8 ml tube, 1.08 ml solvent |
| A2004250X046 | Polaris 10 Si 250 x 4.6mm, 4.2 ml tube, 2.49 ml solvent |

Section 1. Identification

A2004MG	MetaGuard 4.6mm Polaris Si-A 10u, 0.2 ml tube, 0.10 ml solvent
A2004MG2	MetaGuard 2.0mm Polaris Si-A 10u, 0.03 ml tube, 0.02 ml solvent
A2005020X020	Polaris 3 Si 20 x 2.0mm, 0.1 ml tube, 0.04 ml solvent
A2005030X020	Polaris 3 Si 30 x 2.0mm, 0.1 ml tube, 0.06 ml solvent
A2005030X021	Polaris 3 Si 30 x 2.1mm, 0.1 ml tube, 0.06 ml solvent
A2005050X020	Polaris 3 Si 50 x 2.0mm, 0.2 ml tube, 0.09 ml solvent
A2005050X021	Polaris 3 Si 50 x 2.1mm, 0.2 ml tube, 0.10 ml solvent
A2005050X030	Polaris 3 Si 50 x 3.0mm, 0.4 ml tube, 0.21 ml solvent
A2005050X046	Polaris 3 Si 50 x 4.6mm, 0.8 ml tube, 0.50 ml solvent
A2005100X020	Polaris 3 Si 100 x 2.0mm, 0.3 ml tube, 0.19 ml solvent
A2005100X030	Polaris 3 Si 100 x 3.0mm, 0.7 ml tube, 0.42 ml solvent
A2005100X046	Polaris 3 Si 100 x 4.6mm, 1.7 ml tube, 1.00 ml solvent
A2005150X020	Polaris 3 Si 150 x 2.0mm, 0.5 ml tube, 0.28 ml solvent
A2005150X030	Polaris 3 Si 150 x 3.0mm, 1.1 ml tube, 0.64 ml solvent
A2005150X046	Polaris 3 Si 150 x 4.6mm, 2.5 ml tube, 1.50 ml solvent
A2005250X020	Polaris 3 Si 250 x 2.0mm, 0.8 ml tube, 0.47 ml solvent
A2005250X030	Polaris 3 Si 250 x 3.0mm, 1.8 ml tube, 1.06 ml solvent
A2005250X046	Polaris 3 Si 250 x 4.6mm, 4.2 ml tube, 2.49 ml solvent
A2005MG	MetaGuard 4.6mm Polaris Si-A 3u, 0.2 ml tube, 0.10 ml solvent
A2005MG2	MetaGuard 2.0mm Polaris Si-A 3u, 0.03 ml tube, 0.02 ml solvent
A2013020X020	Polaris 5 NH2 20 x 2.0mm, 0.1 ml tube, 0.04 ml solvent
A2013030X020	Polaris 5 NH2 30 x 2.0mm, 0.1 ml tube, 0.06 ml solvent
A2013050G100	Polaris NH2 5u 50 x 10.0mm Guard, 3.9 ml tube, 2.36 ml solvent
A2013050X020	Polaris 5 NH2 50 x 2.0mm, 0.2 ml tube, 0.09 ml solvent
A2013050X046	Polaris 5 NH2 50 x 4.6mm, 0.8 ml tube, 0.50 ml solvent
A2013100X020	Polaris 5 NH2 100 x 2.0mm, 0.3 ml tube, 0.19 ml solvent
A2013100X030	Polaris 5 NH2 100 x 3.0mm, 0.7 ml tube, 0.42 ml solvent
A2013100X046	Polaris 5 NH2 100 x 4.6mm, 1.7 ml tube, 1.00 ml solvent
A2013125X040	Polaris 5 NH2 125 x 4.0mm, 1.6 ml tube, 0.94 ml solvent
A2013150X020	Polaris 5 NH2 150 x 2.0mm, 0.5 ml tube, 0.28 ml solvent
A2013150X030	Polaris 5 NH2 150 x 3.0mm, 1.1 ml tube, 0.64 ml solvent
A2013150X039	Polaris 5 NH2 150 x 3.9mm, 1.8 ml tube, 1.06 ml solvent
A2013150X040	Polaris 5 NH2 150 x 4.0mm, 1.9 ml tube, 1.13 ml solvent
A2013150X046	Polaris 5 NH2 150 x 4.6mm, 2.5 ml tube, 1.50 ml solvent
A2013250X020	Polaris 5 NH2 250 x 2.0mm, 0.8 ml tube, 0.47 ml solvent
A2013250X021	Polaris 5 NH2 250 x 2.1mm, 0.9 ml tube, 0.52 ml solvent
A2013250X030	Polaris 5 NH2 250 x 3.0mm, 1.8 ml tube, 1.08 ml solvent
A2013250X046	Polaris 5 NH2 250 x 4.6mm, 4.2 ml tube, 2.49 ml solvent
A2013MG	MetaGuard 4.6mm Polaris NH2 5u, 0.2 ml tube, 0.10 ml solvent
A2013MG2	MetaGuard 2.0mm Polaris NH2 5u, 0.03 ml tube, 0.02 ml solvent
A2014020X020	Polaris 3 NH2 20 x 2.0mm, 0.1 ml tube, 0.04 ml solvent
A2014030X020	Polaris 3 NH2 30 x 2.0mm, 0.1 ml tube, 0.06 ml solvent
A2014030X021	Polaris 3 NH2 30 x 2.1mm, 0.1 ml tube, 0.06 ml solvent
A2014050X020	Polaris 3 NH2 50 x 2.0mm, 0.2 ml tube, 0.09 ml solvent
A2014050X021	Polaris 3 NH2 50 x 2.1mm, 0.2 ml tube, 0.10 ml solvent
A2014050X030	Polaris 3 NH2 50 x 3.0mm, 0.4 ml tube, 0.21 ml solvent
A2014050X046	Polaris 3 NH2 50 x 4.6mm, 0.8 ml tube, 0.50 ml solvent
A2014100X020	Polaris 3 NH2 100 x 2.0mm, 0.3 ml tube, 0.19 ml solvent
A2014100X021	Polaris 3 NH2 100 x 2.1mm, 0.3 ml tube, 0.21 ml solvent
A2014100X030	Polaris 3 NH2 100 x 3.0mm, 0.7 ml tube, 0.42 ml solvent
A2014100X046	Polaris 3 NH2 100 x 4.6mm, 1.7 ml tube, 1.00 ml solvent
A2014150X020	Polaris 3 NH2 150 x 2.0mm, 0.5 ml tube, 0.28 ml solvent
A2014150X030	Polaris 3 NH2 150 x 3.0mm, 1.1 ml tube, 0.64 ml solvent
A2014150X046	Polaris 3 NH2 150 x 4.6mm, 2.5 ml tube, 1.50 ml solvent
A2014250X020	Polaris 3 NH2 250 x 2.0mm, 0.8 ml tube, 0.47 ml solvent
A2014250X030	Polaris 3 NH2 250 x 3.0mm, 1.8 ml tube, 1.06 ml solvent
A2014250X046	Polaris 3 NH2 250 x 4.6mm, 4.2 ml tube, 2.49 ml solvent
A2014MG	MetaGuard 4.6mm Polaris NH2 3u, 0.2 ml tube, 0.10 ml solvent

Section 1. Identification

A2014MG2 solvent	MetaGuard 2.0mm Polaris NH2 3u, 0.03 ml tube, 0.02 ml
79925CN-564	LiChrospher 100 CN 5um 125 x 4 mm Crtgd Col
79925CN-584	LiChrospher 100 CN 5um 250 x 4 mm Crtgd Col
79925DI-564	LiChrospher 100 Diol 5um 125 x 4 mm Crtgd Col
79925DI-584	LiChrospher 100 Diol 5um 250 x 4 mm Crtgd Col
79925MO-58K	LiChrospher C-8 5um 250 x 4 mm 3/PK
79925OD-58K	LiChrospher C18 5um 250 x 4 mm 3/PK
79925SI-584	LiChrospher 60Si 5um 250 x 4 mm Crtgd Col

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer : Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051, USA
800-227-9770

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

H225	FLAMMABLE LIQUIDS - Category 2
H315	SKIN IRRITATION - Category 2
H319	EYE IRRITATION - Category 2A
H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H304	ASPIRATION HAZARD - Category 1
H400	AQUATIC HAZARD (ACUTE) - Category 1
H410	AQUATIC HAZARD (LONG-TERM) - Category 1

2.2 GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H225 - Highly flammable liquid and vapor.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Section 2. Hazards identification

- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 - Use explosion-proof electrical, ventilating or lighting equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P273 - Avoid release to the environment.
P261 - Avoid breathing vapor.
P264 - Wash thoroughly after handling.
- Response** : P391 - Collect spillage.
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Keep cool.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

- Substance/mixture** : Mixture (encapsulated in article)

Ingredient name	%	Identifiers
Heptane	≥25 - ≤50	CAS: 142-82-5
Propan-2-ol	≤3	CAS: 67-63-0

Contains: Organosilane bonded silica gel.

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Section 4. First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Section 6. Accidental release measures

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Industrial applications, Professional applications.
- Industrial sector specific solutions** : Not available.

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Heptane	<p>NIOSH REL (United States, 10/2020) TWA 10 hours: 85 ppm. TWA 10 hours: 350 mg/m³. CEIL 15 minutes: 440 ppm. CEIL 15 minutes: 1800 mg/m³.</p> <p>CAL OSHA PEL (United States, 5/2018) STEL 15 minutes: 2000 mg/m³. STEL 15 minutes: 500 ppm. TWA 8 hours: 1600 mg/m³.</p>

Section 8. Exposure controls/personal protection

Propan-2-ol	<p>TWA 8 hours: 400 ppm. OSHA PEL (United States, 5/2018) TWA 8 hours: 500 ppm. TWA 8 hours: 2000 mg/m³. OSHA PEL 1989 (United States, 3/1989) TWA 8 hours: 400 ppm. TWA 8 hours: 1600 mg/m³. STEL 15 minutes: 500 ppm. STEL 15 minutes: 2000 mg/m³. ACGIH TLV (United States, 1/2024) [Heptane] TWA 8 hours: 400 ppm. TWA 8 hours: 1640 mg/m³. STEL 15 minutes: 500 ppm. STEL 15 minutes: 2050 mg/m³. NIOSH REL (United States, 10/2020) TWA 10 hours: 400 ppm. TWA 10 hours: 980 mg/m³. STEL 15 minutes: 500 ppm. STEL 15 minutes: 1225 mg/m³. CAL OSHA PEL (United States, 5/2018) STEL 15 minutes: 1225 mg/m³. STEL 15 minutes: 500 ppm. TWA 8 hours: 980 mg/m³. TWA 8 hours: 400 ppm. OSHA PEL (United States, 5/2018) TWA 8 hours: 400 ppm. TWA 8 hours: 980 mg/m³. OSHA PEL 1989 (United States, 3/1989) TWA 8 hours: 400 ppm. TWA 8 hours: 980 mg/m³. STEL 15 minutes: 500 ppm. STEL 15 minutes: 1225 mg/m³. ACGIH TLV (United States, 1/2024) A4. TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm.</p>
-------------	--

[Biological exposure indices](#)

Ingredient name	Exposure indices
Propan-2-ol	ACGIH BEI (United States, 1/2024) BEI: 40 mg/l, acetone [in urine]. Sampling time: end of shift at end of workweek.

[8.2 Exposure controls](#)

Appropriate engineering controls

- Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

[Individual protection measures](#)


Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Solid. (containing flammable liquid)
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : Not available.
- Flash point** : losed cup: -18 to 23°C (-0.4 to 73.4°F) [Based on solvent.]
- Evaporation rate** : Not available.
- Flammability** : Contains: Flammable liquid.
- Lower and upper explosion limit/flammability limit** : Not available.
- Vapor pressure** :

Section 9. Physical and chemical properties and safety characteristics

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Heptane	34.5028	4.6	-	-	-	-
Propan-2-ol	33.00268	4.4	-	177	23.6	-

Relative vapor density : Not available.

Relative density : Not available.

Solubility(ies) :

Media	Result
Mobile phase	Insoluble
Stationary phase	Insoluble

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
Heptane	285	545	-
Propan-2-ol	456	852.8	-

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials
Incompatible with hydrogen fluoride.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
Heptane	Rat - Inhalation - LC50 Vapor 103 g/m ³ [4 hours]
	Rat - Inhalation - LC50 Vapor 48000 ppm [4 hours]
Propan-2-ol	Rabbit - Dermal - LD50 12800 mg/kg
	Rat - Oral - LD50 5000 mg/kg

Section 11. Toxicological information

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Product/ingredient name **Result**
 Propan-2-ol Rabbit - Skin - Mild irritant -

Conclusion/Summary [Product] : Repeated exposure may cause skin dryness or cracking.

Ingredient name **Conclusion/Summary**
 Propan-2-ol Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product/ingredient name **Result** **Duration of treatment/ exposure: 24 hours**
 Propan-2-ol Rabbit - Eyes - Moderate irritant -
 Rabbit - Eyes - Moderate irritant -

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Product/ingredient name
Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Skin
Conclusion/Summary [Product] : Not available.

Respiratory
Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity
Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.
Conclusion/Summary [Product] : Not available.
Classification

Product/ingredient name	OSHA	IARC	NTP
Propan-2-ol	-	3	-

Reproductive toxicity

Conclusion/Summary [Product] : Not available.

Section 11. Toxicological information

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
Heptane	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Propan-2-ol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Polaris Si and NH2 LC Columns with less than 10 ml solvent	ASPIRATION HAZARD - Category 1
Heptane	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: Adverse symptoms may include the following: nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Section 11. Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Polaris Si and NH2 LC Columns with less than 10 ml solvent	500000	N/A	N/A	N/A	N/A
Heptane	N/A	N/A	N/A	103	N/A
Propan-2-ol	5000	12800	N/A	72.2	N/A

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name

Result

Heptane	Acute - LC50 - Fresh water	375 mg/l [96 hours]
Propan-2-ol	Acute - LC50 - Marine water	1400 mg/l [48 hours]
	Acute - LC50 - Fresh water	4200 mg/l [96 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Heptane	-	-	Readily
Propan-2-ol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Heptane	4.66	552	High
Propan-2-ol	0.05	-	Low

Section 12. Ecological information

12.4 Mobility in soil

Soil/Water partition coefficient : Not available.

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / IATA : Not regulated.

Remarks: Special provisions

DOT: 47

TDG: 56

MX: 216

IATA: A46

IMDG: 216

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations

TSCA 12(b) - Chemical export notification

Not applicable.

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 2
 SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
 ASPIRATION HAZARD - Category 1

Composition/information on ingredients

Name	%	Classification
Organosilane bonded silica gel	≥50 - ≤75	COMBUSTIBLE DUSTS
Heptane	≥25 - ≤50	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1
Propan-2-ol	≤3	HNOC - Static-accumulating flammable liquid FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 HNOC - Defatting irritant

State regulations

Massachusetts : The following components are listed: HEPTANE; ISOPROPYL ALCOHOL

New York : None of the components are listed.

New Jersey : The following components are listed: n-HEPTANE; ISOPROPYL ALCOHOL

Pennsylvania : The following components are listed: HEPTANE; 2-PROPANOL

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

Section 15. Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Japan	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: All components are listed or exempted.
United States	: All components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1	On basis of test data Calculation method Calculation method Calculation method Calculation method Expert judgment Calculation method Calculation method

History

Date of issue/Date of revision	: 05/20/2025
Date of previous issue	: 10/18/2023
Version	: 7

Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
DOT = Department of Transportation
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
IMO = International Maritime Organization
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
TDG = Transportation of Dangerous Goods
UN = United Nations

📌 Indicates information that has changed from previously issued version.

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.