

SAFETY DATA SHEET

Polaris LC Columns with less than 10ml solvent

Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier

- Product name** : Polaris LC Columns with less than 10ml solvent
- Part no.** : A2000020X020, A2000030X020, A2000030X030, A2000030X046, A2000050G100, A2000050P046, A2000050X020, A2000050X021, A2000050X030, A2000050X046, A2000075X021, A2000100C030, A2000100C046, A2000100R030, A2000100R046, A2000100T030, A2000100T046, A2000100X020, A2000100X021, A2000100X030, A2000100X040, A2000100X046, A2000100X100, A2000120X046, A2000125X040, A2000125X046, A2000150C030, A2000150C046, A2000150R030, A2000150R046, A2000150T030, A2000150T046, A2000150X020, A2000150X021, A2000150X030, A2000150X039, A2000150X040, A2000150X046, A2000200X046, A2000250C030, A2000250C046, A2000250R030, A2000250R046, A2000250T030, A2000250T046, A2000250X020, A2000250X021, A2000250X030, A2000250X040, A2000250X046, A2000300X046, A2000CG2, A2000CG3, A2000MG, A2000MG2, A2001020X020, A2001030X020, A2001030X030, A2001030X046, A2001050C046, A2001050P046, A2001050R046, A2001050T046, A2001050X010, A2001050X020, A2001050X030, A2001050X046, A2001075X046, A2001100C030, A2001100C046, A2001100T030, A2001100T046, A2001100X010, A2001100X020, A2001100X030, A2001100X046, A2001150C030, A2001150C046, A2001150R030, A2001150R046, A2001150T030, A2001150T046, A2001150X010, A2001150X020, A2001150X030, A2001150X046, A2001250C046, A2001250R046, A2001250X020, A2001250X030, A2001250X046, A2001MG, A2001MG1, A2001MG2, A2002030G046, A2002050G100, A2002250X046, A2002300X039, A2002MG, A2002MG2, A2006020X020, A2006030X020, A2006050G100, A2006050X020, A2006050X046, A2006100X020, A2006100X030, A2006125X040, A2006150X020, A2006150X030, A2006150X040, A2006150X046, A2006200X046, A2006250C046S, A2006250X020, A2006250X030, A2006250X040, A2006250X046, A2006MG, A2006MG2, A2007020X020, A2007030X030, A2007050X020, A2007050X021, A2007050X030, A2007050X032, A2007050X046, A2007050X100, A2007100X020, A2007100X021, A2007100X030, A2007100X046, A2007150X020, A2007150X021, A2007150X030, A2007150X032, A2007150X046, A2007250X020, A2007250X030, A2007250X046, A2007MG, A2007MG2, A2008050G100, A2008250X046, A2008300X039, A2008MG2, A2010020X020, A2010030X020, A2010050G100, A2010050X020, A2010050X046, A2010100X020, A2010100X030, A2010100X046, A2010125X040, A2010125X046, A2010150X020, A2010150X021, A2010150X030, A2010150X040, A2010150X046, A2010250X020, A2010250X030, A2010250X040, A2010250X046, A2010MG, A2010MG2, A2011020X020, A2011030X030, A2011050X020, A2011050X021, A2011050X046, A2011075X046, A2011100X020, A2011100X030, A2011100X046, A2011150X020, A2011150X021, A2011150X030, A2011150X046, A2011250X020, A2011250X030, A2011MG, A2011MG2, A2020020X020, A2020030X020, A2020050G100, A2020050X020, A2020050X046, A2020100X020, A2020100X030, A2020100X046, A2020125X040, A2020150X020, A2020150X030, A2020150X039, A2020150X040, A2020150X046, A2020250X020, A2020250X030, A2020250X040, A2020250X046, A2020MG, A2020MG2, A2021020X020, A2021020X040, A2021030X020, A2021030X030, A2021050P021, A2021050P046, A2021050X020, A2021050X021, A2021050X030, A2021050X032, A2021050X046, A2021050X100, A2021075X020, A2021100X020, A2021100X030, A2021100X040, A2021100X046, A2021150X010, A2021150X020, A2021150X030, A2021150X046, A2021250X010, A2021250X020, A2021250X021, A2021250X030, A2021250X046, A2021MG, A2021MG2, A2030020X020, A2030030X020, A2030050G100, A2030050X020, A2030050X046, A2030100X020, A2030100X030, A2030100X046, A2030125X040, A2030150X020, A2030150X030, A2030150X039, A2030150X040, A2030150X046, A2030250X020,

Section 1. Identification

A2030250X030, A2030250X040, A2030MG, A2031020X020, A2031030X020,
 A2031030X030, A2031050X020, A2031050X021, A2031050X030, A2031050X046,
 A2031075X046, A2031100X020, A2031100X046, A2031150X020, A2031150X021,
 A2031150X046, A2031250X020, A2031250X030, A2031250X046, A2031MG2,
 A2040100X020, A2040MG, A2040MG2, CP914682

Validation date : 7/24/2018

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Reagents and Standards for Analytical Chemistry Laboratory Use
 HPLC Column

A2000020X020	Polaris 5 C18-A 20 x 2.0mm	0.06ml
A2000030X020	Polaris 5 C18-A 30 x 2.0mm	0.1ml
A2000030X030	Polaris 5 C18-A 30 x 3.0mm	0.2ml
A2000030X046	Polaris 5 C18-A 30 x 4.6mm	0.5ml
A2000050G100	Polaris 5 C18-A 50 X 10.0mm Guard	3.9ml
A2000050P046	Polaris 5 C18-A 50 x 4.6mm	0.8ml
A2000050X020	Polaris 5 C18-A 50 x 2.0mm	0.2ml
A2000050X021	Polaris 5 C18-A 50 x 2.1mm	0.2ml
A2000050X030	Polaris 5 C18-A 50 x 3.0mm	0.4ml
A2000050X046	Polaris 5 C18-A 50 x 4.6mm	0.8ml
A2000075X021	Polaris 5 C18-A 75 x 2.1mm	0.3ml
A2000100C030	Polaris 5 C18-A, S100X3.0 Col	0.7ml
A2000100C046	Polaris 5 C18-A, S100x4.6 Col	1.7ml
A2000100R030	Polaris 5 C18-A, S100x3.0 Repl	0.7ml
A2000100R046	Polaris 5 C18-A, S100x4.6 Repl	1.7ml
A2000100T030	Polaris 5 C18-A, S100x3.0 Repl.3	0.7ml
A2000100T046	Polaris 5 C18-A, S100x4.6 Repl.3	1.7ml
A2000100X020	Polaris 5 C18-A 100 x 2.0mm	0.3ml
A2000100X021	Polaris 5 C18-A 100 x 2.1mm	0.3ml
A2000100X030	Polaris 5 C18-A 100 x 3.0mm	0.7ml
A2000100X040	Polaris 5 C18-A 100 x 4.0mm	1.3ml
A2000100X046	Polaris 5 C18-A 100 x 4.6mm	1.7ml
A2000100X100	Polaris 5 C18-A 100 X 10.0mm	7.9ml
A2000120X046	Polaris 5 C18-A 120 x 4.6mm	2.0ml
A2000125X040	Polaris 5 C18-A 125 x 4.0mm	1.6ml
A2000125X046	Polaris 5 C18-A 125 x 4.6mm	2.1ml
A2000150C030	Polaris 5 C18-A, S150x3.0 Col	1.1ml
A2000150C046	Polaris 5 C18-A, S150x4.6 Col	2.5ml
A2000150R030	Polaris 5 C18-A, S150x3.0 Repl	1.1ml
A2000150R046	Polaris 5 C18-A, S150x4.6 Repl	2.5ml
A2000150T030	Polaris 5 C18-A, S150x3.0 Repl.3	1.1ml
A2000150T046	Polaris 5 C18-A, S150x4.6 Repl.3	2.5ml
A2000150X020	Polaris 5 C18-A 150 x 2.0mm	0.5ml
A2000150X021	Polaris 5 C18-A 150 x 2.1mm	0.5ml
A2000150X030	Polaris 5 C18-A 150 x 3.0mm	1.1ml
A2000150X039	Polaris 5 C18-A 150 x 3.9mm	1.8ml
A2000150X040	Polaris 5 C18-A 150 x 4.0mm	1.9ml
A2000150X046	Polaris 5 C18-A 150 x 4.6mm	2.5ml
A2000200X046	Polaris 5 C18-A 200 x 4.6mm	3.3ml
A2000250C030	Polaris 5 C18-A, S250x3.0 Col	1.8ml
A2000250C046	Polaris 5 C18-A, S250x4.6 Col	4.2ml
A2000250R030	Polaris 5 C18-A, S250x3.0 Repl	1.8ml
A2000250R046	Polaris 5 C18-A S250 x 4.6mm Repl	4.2ml
A2000250T030	Polaris 5 C18-A, S250x3.0 Repl.3	1.8ml
A2000250T046	Polaris 5 C18-A, S250x4.6 Repl.3	4.2ml
A2000250X020	Polaris 5 C18-A 250 x 2.0mm	0.8ml
A2000250X021	Polaris 5 C18-A 250 x 2.1mm	0.9ml
A2000250X030	Polaris 5 C18-A 250 x 3.0mm	1.8ml
A2000250X040	Polaris 5 C18-A 250 x 4.0mm	3.1ml
A2000250X046	Polaris 5 C18-A 250 x 4.6mm	4.2ml
A2000300X046	Polaris 5 C18-A 300 x 4.6mm	5.0ml
A2000CG2	ChromSep guard, Pol 5 C18-A 10x2 Repl 3	0.03ml

Section 1. Identification

A2000CG	ChromSep guard, Pol 5 C18-A 10x3 Repl 3	0.07ml
A2000MG	MetaGuard 4.6mm Polaris 5 C18-A	0.2ml
A2000MG2	MetaGuard 2.0mm Polaris 5 C18-A	0.03ml
A2001020X020	Polaris 3 C18-A 20 x 2.0mm	0.06ml
A2001030X020	Polaris 3 C18-A 30 x 2.0mm	0.1ml
A2001030X030	Polaris 3 C18-A 30 x 3.0mm	0.2ml
A2001030X046	Polaris 3 C18-A 30 x 4.6mm	0.5ml
A2001050C046	Polaris 3 C18-A, S50x4.6 Col	0.8ml
A2001050P046	Polaris 3 C18-A 50 x 4.6mm	0.8ml
A2001050R046	Polaris 3 C18-A, S50x4.6 Repl	0.8ml
A2001050T046	Polaris 3 C18-A, S50x4.6 Repl.3	0.8ml
A2001050X010	Polaris 3 C18-A 50 x 1.0mm	0.04ml
A2001050X020	Polaris 3 C18-A 50 x 2.0mm	0.2ml
A2001050X030	Polaris 3 C18-A 50 x 3.0mm	0.4ml
A2001050X046	Polaris 3 C18-A 50 x 4.6mm	0.8ml
A2001075X046	Polaris 3 C18-A 75 x 4.6mm	1.2ml
A2001100C030	Polaris 3 C18-A, S100x3.0 Col	0.7ml
A2001100C046	Polaris 3 C18-A, S100x4.6 Col	1.7ml
A2001100T030	Polaris 3 C18-A, S100x3.0 Repl.3	0.7ml
A2001100T046	Polaris 3 C18-A, S100x4.6 Repl.3	1.7ml
A2001100X010	Polaris 3 C18-A 100 x 1.0mm	0.08ml
A2001100X020	Polaris 3 C18-A 100 x 2.0mm	0.3ml
A2001100X030	Polaris 3 C18-A 100 x 3.0mm	0.7ml
A2001100X046	Polaris 3 C18-A 100 x 4.6mm	1.7ml
A2001150C030	Polaris 3 C18-A, S150x3.0 Col	1.1ml
A2001150C046	Polaris 3 C18-A, S150x4.6 Col	2.5ml
A2001150R030	Polaris 3 C18-A, S150x3.0 Repl	1.1ml
A2001150R046	Polaris 3 C18-A, S150x4.6 Repl	2.5ml
A2001150T030	Polaris 3 C18-A, S150x3.0 Repl.3	1.1ml
A2001150T046	Polaris 3 C18-A, S150x4.6 Repl.3	2.5ml
A2001150X010	Polaris 3 C18-A 150 x 1.0mm	0.1ml
A2001150X020	Polaris 3 C18-A 150 x 2.0mm	0.5ml
A2001150X030	Polaris 3 C18-A 150 x 3.0mm	1.1ml
A2001150X046	Polaris 3 C18-A 150 x 4.6mm	2.5ml
A2001250C046	Polaris 3 C18-A, S250x4.6 Col	4.2ml
A2001250R046	Polaris 3 C18-A, S250x4.6 Repl	4.2ml
A2001250X020	Polaris 3 C18-A 250 x 2.0mm	0.8ml
A2001250X030	Polaris 3 C18-A 250 x 3.0mm	1.8ml
A2001250X046	Polaris 3 C18-A 250 x 4.6mm	4.2ml
A2001MG	MetaGuard 4.6mm Polaris 3 C18-A	0.2ml
A2001MG1	MetaGuard 1.0mm Polaris 3 C18-A	0.01ml
A2001MG2	MetaGuard 2.0mm Polaris 3 C18-A	0.03ml
A2002030G046	Polaris 10u C18-A 30 x 4.6mm GUARD	0.5ml
A2002050G100	Polaris 10u C18-A 50 x 10.0mm Guard	3.9ml
A2002250X046	Polaris 10 C18-A 250 x 4.6mm	4.2ml
A2002300X039	Polaris 10 C18-A 300 x 3.9mm	3.6ml
A2002MG	MetaGuard 4.6mm Polaris 10u C18-A	0.2ml
A2002MG2	MetaGuard 2.1mm Polaris 10U C18-A	0.03ml
A2006020X020	Polaris 5 Amide-C18 20 x 2.0mm	0.06ml
A2006030X020	Polaris 5 Amide-C18 30 x 2.0mm	0.1ml
A2006050G100	Polaris 5 Amide-C18 50 X 10.0mm Guard	3.9ml
A2006050X020	Polaris 5 Amide-C18 50 x 2.0mm	0.2ml
A2006050X046	Polaris 5 Amide-C18 50 x 4.6mm	0.8ml
A2006100X020	Polaris 5 Amide-C18 100 x 2.0mm	0.3ml
A2006100X030	Polaris 5 Amide-C18 100 x 3.0mm	0.7ml
A2006125X040	Polaris 5 Amide-C18 125 x 4.0mm	1.6ml
A2006150X020	Polaris 5 Amide-C18 150 x 2.0mm	0.5ml
A2006150X030	Polaris 5 Amide-C18 150 x 3.0mm	1.1ml
A2006150X040	Polaris 5 Amide-C18 150 x 4.0mm	1.9ml
A2006150X046	Polaris 5 Amide-C18 150 x 4.6mm	2.5ml
A2006200X046	Polaris 5 Amide-C18 200 x 4.6mm	3.3ml
A2006250C046S	Polaris 5 Amide-C18 250 x 4.6mm Col	4.2ml

Section 1. Identification

A2006250X020	Polaris 5 Amide-C18 250 x 2.0mm	0.8ml
A2006250X030	Polaris 5 Amide-C18 250 x 3.0mm	1.8ml
A2006250X040	Polaris 5 Amide-C18 250 x 4.0mm	3.1ml
A2006250X046	Polaris 5 Amide-C18 250 x 4.6mm	4.2ml
A2006MG	Polaris 5 Amide-C18 4.6mm MetaGuard	0.2ml
A2006MG2	Polaris 5 Amide-C18 2.0mm MetaGuard	0.03ml
A2007020X020	Polaris 3 Amide-C18 20 x 2.0mm	0.06ml
A2007030X030	Polaris 3 Amide-C18 30 x 3.0mm	0.2ml
A2007050X020	Polaris 3 Amide-C18 50 x 2.0mm	0.2ml
A2007050X021	Polaris 3 Amide-C18 50 x 2.1mm	0.2ml
A2007050X030	Polaris 3 Amide-C18 50 x 3.0mm	0.4ml
A2007050X032	Polaris 3 Amide-C18 50 x 3.2mm	0.4ml
A2007050X046	Polaris 3 Amide-C18 50 x 4.6mm	0.8ml
A2007050X100	Polaris 3 Amide-C18 50 X 10.0mm	3.9ml
A2007100X020	Polaris 3 Amide-C18 100 x 2.0mm	0.3ml
A2007100X021	Polaris 3 Amide-C18 100 x 2.1mm	0.3ml
A2007100X030	Polaris 3 Amide-C18 100 x 3.0mm	0.7ml
A2007100X046	Polaris 3 Amide-C18 100 x 4.6mm	1.7ml
A2007150X020	Polaris 3 Amide-C18 150 x 2.0mm	0.5ml
A2007150X021	Polaris 3 Amide-C18 150 x 2.1mm	0.5ml
A2007150X030	Polaris 3 Amide-C18 150 x 3.0mm	1.1ml
A2007150X032	Polaris 3 Amide-C18 150 x 3.2mm	1.2ml
A2007150X046	Polaris 3 Amide-C18 150 x 4.6mm	2.5ml
A2007250X020	Polaris 3 Amide-C18 250 x 2.0mm	0.8ml
A2007250X030	Polaris 3 Amide-C18 250 x 3.0mm	1.8ml
A2007250X046	Polaris 3 Amide-C18 250 x 4.6mm	4.2ml
A2007MG	Polaris 3 Amide-C18 4.6mm MetaGuard	0.2ml
A2007MG2	Polaris 3 Amide-C18 2.0mm MetaGuard	0.03ml
A2008050G100	Polaris 10 Amide-C18 50 X 10.0mm Guard	3.9ml
A2008250X046	Polaris 10 Amide-C18 250 x 4.6mm	4.2ml
A2008300X039	Polaris 10 Amide-C18 300 x 3.9mm	3.6ml
A2008MG2	Polaris 10 Amide-C18 2.0mm MetaGuard	0.03ml
A2010020X020	Polaris 5 C8-A 20 x 2.0mm	0.06ml
A2010030X020	Polaris 5 C8-A 30 x 2.0mm	0.1ml
A2010050G100	Polaris 5 C8-A 50 X 10.0mm Guard	3.9ml
A2010050X020	Polaris 5 C8-A 50 x 2.0mm	0.2ml
A2010050X046	Polaris 5 C8-A 50 x 4.6mm	0.8ml
A2010100X020	Polaris 5 C8-A 100 x 2.0mm	0.3ml
A2010100X030	Polaris 5 C8-A 100 x 3.0mm	0.7ml
A2010100X046	Polaris 5 C8-A 100 x 4.6mm	1.7ml
A2010125X040	Polaris 5 C8-A 125 x 4.0mm	1.6ml
A2010125X046	Polaris 5 C8-A 125 x 4.6mm	2.1ml
A2010150X020	Polaris 5 C8-A 150 x 2.0mm	0.5ml
A2010150X021	Polaris 5 C8-A 150 x 2.1mm	0.5ml
A2010150X030	Polaris 5 C8-A 150 x 3.0mm	1.1ml
A2010150X040	Polaris 5 C8-A 150 x 4.0mm	1.9ml
A2010150X046	Polaris 5 C8-A 150 x 4.6mm	2.5ml
A2010250X020	Polaris 5 C8-A 250 x 2.0mm	0.8ml
A2010250X030	Polaris 5 C8-A 250 x 3.0mm	1.8ml
A2010250X040	Polaris 5 C8-A 250 x 4.0mm	3.1ml
A2010250X046	Polaris 5 C8-A 250 x 4.6mm	4.2ml
A2010MG	MetaGuard 4.6mm Polaris C8-A 5u	0.2ml
A2010MG2	MetaGuard 2.0mm Polaris C8-A 5u	0.03ml
A2011020X020	Polaris 3 C8-A 20 x 2.0mm	0.06ml
A2011030X030	Polaris 3 C8-A 30 x 3.0mm	0.2ml
A2011050X020	Polaris 3 C8-A 50 x 2.0mm	0.2ml
A2011050X021	Polaris 3 C8-A 50 x 2.1mm	0.2ml
A2011050X046	Polaris 3 C8-A 50 x 4.6mm	0.8ml
A2011075X046	Polaris 3 C8-A 75 x 4.6mm	1.2ml
A2011100X020	Polaris 3 C8-A 100 x 2.0mm	0.3ml
A2011100X030	Polaris 3 C8-A 100 x 3.0mm	0.7ml
A2011100X046	Polaris 3 C8-A 100 x 4.6mm	1.7ml

Section 1. Identification

A2011150X020	Polaris 3 C8-A 150 x 2.0mm 0.5ml
A2011150X021	Polaris 3 C8-A 150 x 2.1mm 0.5ml
A2011150X030	Polaris 3 C8-A 150 x 3.0mm 1.1ml
A2011150X046	Polaris 3 C8-A 150 x 4.6mm 2.5ml
A2011250X020	Polaris 3 C8-A 250 x 2.0mm 0.8ml
A2011250X030	Polaris 3 C8-A 250 x 3.0mm 1.8ml
A2011MG	MetaGuard 4.6mm Polaris C8-A 3u 0.2ml
A2011MG2	MetaGuard 2.0mm Polaris C8-A 3u 0.03ml
A2020020X020	Polaris 5 C18-Ether 20 x 2.0mm 0.06ml
A2020030X020	Polaris 5 3 C18-Ether0 x 2.0mm 0.1ml
A2020050G100	Polaris C18-Ether 5u 50 x 10.0mm Guard 3.9ml
A2020050X020	Polaris 5 C18-Ether 50 x 2.0mm 0.2ml
A2020050X046	Polaris 5 C18-Ether 50 x 4.6mm 0.8ml
A2020100X020	Polaris 5 C18-Ether 100 x 2.0mm 0.3ml
A2020100X030	Polaris 5 C18-Ether 100 x 3.0mm 0.7ml
A2020100X046	Polaris 5 C18-Ether 100 x 4.6mm 1.7ml
A2020125X040	Polaris 5 C18-Ether 125 x 4.0mm
A2020150X020	Polaris 5 C18-Ether 150 x 2.0mm 0.5ml
A2020150X030	Polaris 5 C18-Ether 150 x 3.0mm 1.1ml
A2020150X039	Polaris 5 C18-Ether 150 x 3.9mm
A2020150X040	Polaris 5 C18-Ether 150 x 4.0mm
A2020150X046	Polaris 5 C18-Ether 150 x 4.6mm
A2020250X020	Polaris 5 C18-Ether 250 x 2.0mm
A2020250X030	Polaris 5 C18-Ether 250 x 3.0mm 1.8ml
A2020250X040	Polaris 5 C18-Ether 250 x 4.0mm
A2020250X046	Polaris 5 C18-Ether 250 x 4.6mm
A2020MG	MetaGuard 4.6mm Polaris C18-Ether 5u 0.2ml
A2020MG2	MetaGuard 2.0mm Polaris C18-Ether 5u 0.03ml
A2021020X020	Polaris 3 C18-Ether 20 x 2.0mm 0.06ml
A2021020X040	Polaris 3 C18-Ether 20 x 4.0mm 0.3ml
A2021030X020	Polaris 3 3 C18-Ether0 x 2.0mm 0.1ml
A2021030X030	Polaris 3 C18-Ether 30 x 3.0mm 0.2ml
A2021050P021	Polaris 3 C18-Ether 50 x 2.1mm 0.2ml
A2021050P046	Polaris 3 C18-Ether 50 x 4.6mm 0.8ml
A2021050X020	Polaris 3 C18-Ether 50 x 2.0mm 0.2ml
A2021050X021	Polaris 3 C18-Ether 50 x 2.1mm 0.2ml
A2021050X030	Polaris 3 C18-Ether 50 x 3.0mm 0.4ml
A2021050X032	Polaris 3 C18-Ether 50 x 3.2mm 0.4ml
A2021050X046	Polaris 3 C18-Ether 50 x 4.6mm 0.8ml
A2021050X100	Polaris C18-Ether 3u 50 x 10.0mm 3.9ml
A2021075X020	Polaris 3 C18-Ether 75 x 2.0mm 0.2ml
A2021100X020	Polaris 3 C18-Ether 100 x 2.0mm 0.3ml
A2021100X030	Polaris 3 C18-Ether 100 x 3.0mm 0.7ml
A2021100X040	Polaris 3 C18-Ether 100 x 4.0mm 1.3ml
A2021100X046	Polaris 3 C18-Ether 100 x 4.6mm 1.7ml
A2021150X010	Polaris 3 C18-Ether 150 x 1.0mm 0.1ml
A2021150X020	Polaris 3 C18-Ether 150 x 2.0mm 0.5ml
A2021150X030	Polaris 3 C18-Ether 150 x 3.0mm 1.1ml
A2021150X046	Polaris 3 C18-Ether 150 x 4.6mm 2.5ml
A2021250X010	Polaris 3 C18-Ether 250 x 1.0mm 0.2ml
A2021250X020	Polaris 3 C18-Ether 250 x 2.0mm 0.8ml
A2021250X021	Polaris 3 C18-Ether 250 x 2.1mm 0.9ml
A2021250X030	Polaris 3 C18-Ether 250 x 3.0mm 1.8ml
A2021250X046	Polaris 3 C18-Ether 250 x 4.6mm 4.2ml
A2021MG	MetaGuard 4.6mm Polaris C18-Ether 3u 0.2ml
A2021MG2	MetaGuard 2.0mm Polaris C18-Ether 3u 0.03ml
A2030020X020	Polaris 5 C8-Ether 20 x 2.0mm 0.06ml
A2030030X020	Polaris 5 C8-Ether 30 x 2.0mm 0.1ml
A2030050G100	Polaris C8-Ether 5u 50 x 10.0mm Guard 3.9ml
A2030050X020	Polaris 5 C8-Ether 50 x 2.0mm 0.2ml
A2030050X046	Polaris 5 C8-Ether 50 x 4.6mm 0.8ml
A2030100X020	Polaris 5 C8-Ether 100 x 2.0mm 0.3ml

Section 1. Identification

A2030100X030	Polaris 5 C8-Ether 100 x 3.0mm	0.7ml
A2030100X046	Polaris 5 C8-Ether 100 x 4.6mm	1.7ml
A2030125X040	Polaris 5 C8-Ether 125 x 4.0mm	1.6ml
A2030150X020	Polaris 5 C8-Ether 150 x 2.0mm	0.5ml
A2030150X030	Polaris 5 C8-Ether 150 x 3.0mm	1.1ml
A2030150X039	Polaris 5 C8-Ether 150 x 3.9mm	1.8ml
A2030150X040	Polaris 5 C8-Ether 150 x 4.0mm	1.9ml
A2030150X046	Polaris 5 C8-Ether 150 x 4.6mm	2.5ml
A2030250X020	Polaris 5 C8-Ether 250 x 2.0mm	0.8ml
A2030250X030	Polaris 5 C8-Ether 250 x 3.0mm	1.8ml
A2030250X040	Polaris 5 C8-Ether 250 x 4.0mm	3.1ml
A2030MG	MetaGuard 4.6mm Polaris C8-Ether 5u	0.2ml
A2031020X020	Polaris 3 C8-Ether 20 x 2.0mm	0.06ml
A2031030X020	Polaris 3 C8-Ether 30 x 2.0mm	0.1ml
A2031030X030	Polaris 3 C8-Ether 30 x 3.0mm	0.2ml
A2031050X020	Polaris 3 C8-Ether 50 x 2.0mm	0.2ml
A2031050X021	Polaris 3 C8-Ether 50 x 2.1mm	0.2ml
A2031050X030	Polaris 3 C8-Ether 50 x 3.0mm	0.4ml
A2031050X046	Polaris 3 C8-Ether 50 x 4.6mm	0.8ml
A2031075X046	Polaris 3 C8-Ether 75 x 4.6mm	1.2ml
A2031100X020	Polaris 3 C8-Ether 100 x 2.0mm	0.3ml
A2031100X046	Polaris 3 C8-Ether 100 x 4.6mm	1.7ml
A2031150X020	Polaris 3 C8-Ether 150 x 2.0mm	0.5ml
A2031150X021	Polaris 3 C8-Ether 150 x 2.1mm	0.5ml
A2031150X046	Polaris 3 C8-Ether 150 x 4.6mm	2.5ml
A2031250X020	Polaris 3 C8-Ether 250 x 2.0mm	0.8ml
A2031250X030	Polaris 3 C8-Ether 250 x 3.0mm	1.8ml
A2031250X046	Polaris 3 C8-Ether 250 x 4.6mm	4.2ml
A2031MG2	MetaGuard 2.0mm Polaris C8-Ether 3u	0.03ml
A2040100X020	Polaris 5 C18-B 100 x 2.0mm	0.3ml
A2040MG	MetaGuard 4.6mm Polaris 5 C18-B	0.2ml
A2040MG2	MetaGuard 2.0mm Polaris 5 C18-B	0.03ml
CP914682	Polaris 3 C18-Ether 250 x 2.0mm	0.8ml

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer : Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051, USA
800-227-9770

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

H225 FLAMMABLE LIQUIDS - Category 2
H319 EYE IRRITATION - Category 2A
H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2

Section 2. Hazards identification

2.2 GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H225 - Highly flammable liquid and vapor.
 H319 - Causes serious eye irritation.
 H373 - May cause damage to organs through prolonged or repeated exposure. (blood system, central nervous system (CNS), kidneys, liver)

Precautionary statements

Prevention

: P280 - Wear protective gloves. Wear eye or face protection.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P233 - Keep container tightly closed.
 P260 - Do not breathe vapor.
 P264 - Wash hands thoroughly after handling.

Response

: P314 - Get medical attention if you feel unwell.
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 - If eye irritation persists: Get medical attention.

Storage

: P403 - Store in a well-ventilated place.
 P235 - Keep cool.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

Substance/mixture : Mixture (encapsulated in article)

Ingredient name	%	CAS number
Acetonitrile	≥10 - <25	75-05-8

Contains: Organosilane bonded silica gel

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the chemical : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides
cyanides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Industrial applications, Professional applications.

Industrial sector specific solutions : Not applicable.

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Acetonitrile	<p>ACGIH TLV (United States, 3/2017). Absorbed through skin. TWA: 20 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 40 ppm 8 hours. TWA: 70 mg/m³ 8 hours. STEL: 60 ppm 15 minutes. STEL: 105 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2016). TWA: 20 ppm 10 hours. TWA: 34 mg/m³ 10 hours.</p> <p>OSHA PEL (United States, 6/2016). TWA: 40 ppm 8 hours. TWA: 70 mg/m³ 8 hours.</p>

8.2 Exposure controls

Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Solid. (containing flammable liquid)
- Color** : White.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Neutral.
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Closed cup: -18 to 23°C (-0.4 to 73.4°F)

Section 9. Physical and chemical properties

Evaporation rate	: Not available.
Flammability (solid, gas)	: Contains: Flammable liquid
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Mobile phase: Soluble Stationary phase: Insoluble
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.

Section 10. Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials Incompatible with hydrogen fluoride.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetonitrile	LC50 Inhalation Vapor	Rat	17100 ppm	4 hours
	LD50 Oral	Rat	2460 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetonitrile	Eyes - Moderate irritant	Rabbit	-	24 hours 100 microliters	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-

Sensitization

Not available.

Section 11. Toxicological information

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Acetonitrile	Category 2	Not determined	blood system, central nervous system (CNS), kidneys and liver

Aspiration hazard

Not available.

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Section 11. Toxicological information

General	: May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	2083.3 mg/kg
Dermal	4583.3 mg/kg
Inhalation (vapors)	45.83 mg/l

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Acetonitrile	Acute IC50 3685000 µg/l Fresh water Acute LC50 3600000 µg/l Fresh water Acute LC50 1000000 µg/l Fresh water Chronic NOEC 1000000 µg/l Fresh water Chronic NOEC 160000 µg/l Fresh water	Aquatic plants - Lemna minor Daphnia - Daphnia magna Fish - Pimephales promelas Aquatic plants - Lemna minor Daphnia - Daphnia magna	96 hours 48 hours 96 hours 96 hours 21 days

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetonitrile	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Acetonitrile	-0.34	3	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc})	: Not available.
--	------------------

12.5 Other adverse effects	: No known significant effects or critical hazards.
-----------------------------------	---

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Acetonitrile (I,T)	75-05-8	Listed	U003

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / IATA : Not regulated.

Additional information

Remarks: Special provisions

DOT: 47

TDG: 56

MX: 216

IATA: A46

IMDG: 216

DOT Classification : **Reportable quantity** 20833.3 lbs / 9458.3 kg. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 14. Transport information

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : TSCA 8(a) PAIR: Acetonitrile
 TSCA 8(a) CDR Exempt/Partial exemption: Not determined
 Clean Water Act (CWA) 307: Acetonitrile

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 2
 EYE IRRITATION - Category 2A
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2

Composition/information on ingredients

Name	%	Classification
<input checked="" type="checkbox"/> Organosilane bonded silica gel Acetonitrile	≥50 - ≤75 ≥10 - <25	COMBUSTIBLE DUSTS FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Acetonitrile	75-05-8	≥10 - <25
Supplier notification	Acetonitrile	75-05-8	≥10 - <25

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Section 15. Regulatory information

- Massachusetts** : The following components are listed: ACETONITRILE
New York : The following components are listed: Acetonitrile; Ethanenitrile
New Jersey : The following components are listed: ACETONITRILE; CYANOMETHANE
Pennsylvania : The following components are listed: ACETONITRILE

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

- Australia** : All components are listed or exempted.
Canada : Not determined.
China : All components are listed or exempted.
Europe : All components are listed or exempted.
Japan : **Japan inventory (ENCS)**: All components are listed or exempted.
Japan inventory (ISHL): All components are listed or exempted.
Malaysia : All components are listed or exempted.
New Zealand : All components are listed or exempted.
Philippines : Not determined.
Republic of Korea : Not determined.
Taiwan : All components are listed or exempted.
Thailand : Not determined.
Turkey : All components are listed or exempted.
United States : All components are listed or exempted.
Viet Nam : Not determined.

Section 16. Other information

History

- Date of issue** : 07/24/2018
Date of previous issue : 08/01/2016
Version : 3

Procedure used to derive the classification

Classification	Justification
<input checked="" type="checkbox"/> FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system, central nervous system (CNS), kidneys, liver) - Category 2	On basis of test data Calculation method Calculation method

Indicates information that has changed from previously issued version.

Section 16. Other information

[Notice to reader](#)

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.