

SAFETY DATA SHEET

Pursuit C18 LC Columns with less than 10ml solvent

Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier

Product name : Pursuit C18 LC Columns with less than 10ml solvent

Part no. : A3000MG2, A3001MG2, A3002MG2, A3001050X010, A3000020X020, A3001020X020, A3002020X020, A3000CG3, A3001030X020, A3000050X020, A3001050X020, A3000MG, A3001MG, A3002MG, A3000050X021, A3000075X020, A3000100X020, A3001100X020, A3000100X021, A3001050X030, A3000150X020, A3001150X020, A3001030X046, A3000150X021, A3000100C030, A3000100R030, A3000100T030, A3000100X030, A3001100C030, A3001100R030, A3001100X030, A3000250X020, A3001250X020, A3000050X046, A3001050C046, A3001050X046, A3000250X021, A3000150C030, A3000150R030, A3000150X030, A3001150C030, A3001150R030, A3001150X030, A3001075X046, A3000100X040, A3000125X040, A3000100C046, A3000100X046, A3001100R046, A3001100X046, A3000250C030, A3000250R030, A3000250X030, A3000150X039, A3000150X040, A3000125X046, A3000150C046, A3000150R046, A3000150X046, A3001150C046, A3001150R046, A3001150T046, A3001150X046, A3002150X046, A3000250X040, A3002300X039, A3000050G100, A3000050X100, A3000250C046, A3000250R046, A3000250X046, A3001250X046, A3002250X046, A3000300X046, A3000100X100, A3000030G212, A3000150X100

Validation date : 11/20/2023

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Analytical chemistry.
HPLC column
Solvent volume: <10 ml

A3000MG2	MetaGuard 2.0mm Pursuit 5u C18, 0.02ml
A3001MG2	MetaGuard 2.0mm Pursuit 3u C18, 0.02ml
A3002MG2	MetaGuard 2.0mm Pursuit 10u C18, 0.02ml
A3001050X010	Pursuit 3 C18 50 x 1.0mm, 0.02ml
A3000020X020	Pursuit 5 C18 20 x 2.0mm, 0.04ml
A3001020X020	Pursuit 3 C18 20 x 2.0mm, 0.04ml
A3002020X020	Pursuit 10 C18 20 x 2.0mm, 0.04ml
A3000CG3	ChromSep guard, Pur 5 C18 10 x 3 Repl.3, 0.04ml
A3001030X020	Pursuit 3 C18 30 x 2.0mm, 0.06ml
A3000050X020	Pursuit 5 C18 50 x 2.0mm, 0.09ml
A3001050X020	Pursuit 3 C18 50 x 2.0mm, 0.09ml
A3000MG	MetaGuard 4.6mm Pursuit 5u C18, 0.10ml
A3001MG	Metaguard 4.6mm Pursuit 3u C18, 0.10ml
A3002MG	MetaGuard 4.6mm Pursuit 10u C18, 0.10ml
A3000050X021	Pursuit 5 C18 50 x 2.1mm, 0.10ml
A3000075X020	Pursuit 5 C18 75 x 2.0mm, 0.14ml
A3000100X020	Pursuit 5 C18 100 x 2.0mm, 0.19ml
A3001100X020	Pursuit 3 C18 100 x 2.0mm, 0.19ml
A3000100X021	Pursuit 5 C18 100 x 2.1mm, 0.21ml
A3001050X030	Pursuit 3 C18 50 x 3.0mm, 0.21ml
A3000150X020	Pursuit 5 C18 150 x 2.0mm, 0.28ml
A3001150X020	Pursuit 3 C18 150 x 2.0mm, 0.28ml
A3001030X046	Pursuit 3 C18 30 x 4.6mm, 0.30ml
A3000150X021	Pursuit 5 C18 150 x 2.1mm, 0.31ml
A3000100C030	Pursuit 5 C18, S100 x 3.0 Col, 0.42ml
A3000100R030	Pursuit 5 C18, S100 x 3.0 Repl, 0.42ml
A3000100T030	Pursuit 5 C18, S100 x 3.0 Repl.3, 0.42ml
A3000100X030	Pursuit 5 C18 100 x 3.0mm, 0.42ml
A3001100C030	Pursuit 3 C18, S100 x 3.0 Col, 0.42ml

Section 1. Identification

A3001100R030	Pursuit 3 C18, S100 x 3.0 Repl, 0.42ml
A3001100X030	Pursuit 3 C18 100 x 3.0mm, 0.42ml
A3000250X020	Pursuit 5 C18 250 x 2.0mm, 0.47ml
A3001250X020	Pursuit 3 C18 250 x 2.0mm, 0.47ml
A3000050X046	Pursuit 5 C18 50 x 4.6mm, 0.50ml
A3001050C046	Pursuit 3 C18, S50 x 4.6 Col, 0.50ml
A3001050X046	Pursuit 3 C18 50 x 4.6mm, 0.50ml
A3000250X021	Pursuit 5 C18 250 x 2.1mm, 0.52ml
A3000150C030	Pursuit 5 C18, S150 x 3.0 Col, 0.64ml
A3000150R030	Pursuit 5 C18, S150 x 3.0 Repl, 0.64ml
A3000150X030	Pursuit 5 C18 150 x 3.0mm, 0.64ml
A3001150C030	Pursuit 3 C18, S150x3.0 Col, 0.64ml
A3001150R030	Pursuit 3 C18, S150x3.0 Repl, 0.64ml
A3001150X030	Pursuit 3 C18 150 x 3.0mm, 0.64ml
A3001075X046	Pursuit 3 C18 75 x 4.6mm, 0.75ml
A3000100X040	Pursuit 5 C18 100 x 4.0mm, 0.75ml
A3000125X040	Pursuit 5 C18 125 x 4.0mm, 0.94ml
A3000100C046	Pursuit 5 C18, S100 x 4.6 Col, 1.00ml
A3000100X046	Pursuit 5 C18 100 x 4.6mm, 1.00ml
A3001100R046	Pursuit 3 C18, S100 x 4.6 Repl, 1.00ml
A3001100X046	Pursuit 3 C18 100 x 4.6mm, 1.00ml
A3000250C030	Pursuit 5 C18, S250 x 3.0 Col, 1.06ml
A3000250R030	Pursuit 5 C18, S250 x 3.0 Repl, 1.06ml
A3000250X030	Pursuit 5 C18 250 x 3.0mm, 1.06ml
A3000150X039	Pursuit 5 C18 150 x 3.9mm, 1.08ml
A3000150X040	Pursuit 5 C18 150 x 4.0mm, 1.13ml
A3000125X046	Pursuit 5 C18 125 x 4.6mm, 1.25ml
A3000150C046	Pursuit 5 C18, S150 x 4.6 Col, 1.50ml
A3000150R046	Pursuit 5 C18, S150 x 4.6 Repl, 1.50ml
A3000150X046	Pursuit 5 C18 150 x 4.6mm, 1.50ml
A3001150C046	Pursuit 3 C18, S150 x 4.6 Col, 1.50ml
A3001150R046	Pursuit 3 C18, S150 x 4.6 Repl, 1.50ml
A3001150T046	Pursuit 3 C18, S150 x 4.6 Repl.3, 1.50ml
A3001150X046	Pursuit 3 C18 150 x 4.6mm, 1.50ml
A3002150X046	Pursuit 10 C18 150 x 4.6mm, 1.50ml
A3000250X040	Pursuit 5 C18 250 x 4.0mm, 1.88ml
A3002300X039	Pursuit 10 C18 300 x 3.9mm, 2.15ml
A3000050G100	Pursuit 5u C18 50 x 10.0mm Guard, 2.36ml
A3000050X100	Pursuit 5u C18 50 x 10.0mm, 2.36ml
A3000250C046	Pursuit 5 C18, S250 x 4.6 Col, 2.49ml
A3000250R046	Pursuit 5 C18, S250 x 4.6 Repl, 2.49ml
A3000250X046	Pursuit 5 C18 250 x 4.6mm, 2.49ml
A3001250X046	Pursuit 3 C18 250 x 4.6mm, 2.49ml
A3002250X046	Pursuit 10 C18 250 x 4.6mm, 2.49ml
A3000300X046	Pursuit 5 C18 300 x 4.6mm, 2.99ml
A3000100X100	Pursuit 5u C18 100 x 10.0mm, 4.71ml
A3000030G212	Pursuit 5u C18 30 x 21.2mm GUARD, 6.35ml
A3000150X100	Pursuit 5u C18 150 x 10.0mm, 7.07ml

[1.3 Details of the supplier of the safety data sheet](#)

Supplier/Manufacturer : Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051, USA
800-227-9770

[1.4 Emergency telephone number](#)

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

H225 FLAMMABLE LIQUIDS - Category 2
 H319 EYE IRRITATION - Category 2A
 H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

2.2 GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H225 - Highly flammable liquid and vapor.
 H319 - Causes serious eye irritation.
 H373 - May cause damage to organs through prolonged or repeated exposure. (blood system, central nervous system (CNS), kidneys, liver)

Precautionary statements

Prevention

: P280 - Wear eye or face protection.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 - Use explosion-proof electrical, ventilating or lighting equipment.
 P242 - Use non-sparking tools.
 P243 - Take action to prevent static discharges.
 P233 - Keep container tightly closed.
 P260 - Do not breathe vapor.

Response

: P314 - Get medical advice or attention if you feel unwell.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage

: P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

Substance/mixture : Mixture (encapsulated in article)

Ingredient name	%	CAS number
Acetonitrile	≥10 - <25	75-05-8

Section 3. Composition/information on ingredients

Contains: Organosilane bonded silica gel

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Section 4. First aid measures

4.3 Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides
cyanides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Industrial applications, Professional applications.
- Industrial sector specific solutions** : Not available.

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Acetonitrile	<p>ACGIH TLV (United States, 1/2022). Absorbed through skin. TWA: 20 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 40 ppm 8 hours. TWA: 70 mg/m³ 8 hours. STEL: 60 ppm 15 minutes. STEL: 105 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2020). TWA: 20 ppm 10 hours. TWA: 34 mg/m³ 10 hours.</p>

Section 8. Exposure controls/personal protection

OSHA PEL (United States, 5/2018).

TWA: 40 ppm 8 hours.

TWA: 70 mg/m³ 8 hours.

CAL OSHA PEL (United States, 5/2018).

Absorbed through skin.

STEL: 105 mg/m³ 15 minutes.

STEL: 60 ppm 15 minutes.

TWA: 70 mg/m³ 8 hours.

TWA: 40 ppm 8 hours.

Biological exposure indices

No exposure indices known.

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

- : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Solid. (containing flammable liquid)																											
Color	: White.																											
Odor	: Not available.																											
Odor threshold	: Not available.																											
pH	: Not available.																											
Melting point/freezing point	: Not available.																											
Boiling point, initial boiling point, and boiling range	: Not available.																											
Flash point	: <input checked="" type="checkbox"/> Closed cup: -18 to 23°C (-0.4 to 73.4°F) [Based on solvent.]																											
Evaporation rate	: Not available.																											
Flammability	: Contains: Flammable liquid																											
Lower and upper explosion limit/flammability limit	: Not available.																											
Vapor pressure	: <table border="1"> <thead> <tr> <th rowspan="2">Ingredient name</th> <th colspan="3">Vapor Pressure at 20°C</th> <th colspan="3">Vapor pressure at 50°C</th> </tr> <tr> <th>mm Hg</th> <th>kPa</th> <th>Method</th> <th>mm Hg</th> <th>kPa</th> <th>Method</th> </tr> </thead> <tbody> <tr> <td><input checked="" type="checkbox"/> Acetonitrile</td> <td>70.89</td> <td>9.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>water</td> <td>17.5</td> <td>2.3</td> <td>-</td> <td>92.258</td> <td>12.3</td> <td>-</td> </tr> </tbody> </table>	Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	<input checked="" type="checkbox"/> Acetonitrile	70.89	9.5	-	-	-	-	water	17.5	2.3	-	92.258	12.3	-
Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C																								
	mm Hg	kPa	Method	mm Hg	kPa	Method																						
<input checked="" type="checkbox"/> Acetonitrile	70.89	9.5	-	-	-	-																						
water	17.5	2.3	-	92.258	12.3	-																						

Relative vapor density : Not available.

Relative density : Not available.

Solubility(ies)	: <table border="1"> <thead> <tr> <th>Media</th> <th>Result</th> </tr> </thead> <tbody> <tr> <td><input checked="" type="checkbox"/> Mobile phase</td> <td>Soluble</td> </tr> <tr> <td>Stationary phase</td> <td>Insoluble</td> </tr> </tbody> </table>	Media	Result	<input checked="" type="checkbox"/> Mobile phase	Soluble	Stationary phase	Insoluble
Media	Result						
<input checked="" type="checkbox"/> Mobile phase	Soluble						
Stationary phase	Insoluble						

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature	: <table border="1"> <thead> <tr> <th>Ingredient name</th> <th>°C</th> <th>°F</th> <th>Method</th> </tr> </thead> <tbody> <tr> <td><input checked="" type="checkbox"/> Acetonitrile</td> <td>524</td> <td>975.2</td> <td>-</td> </tr> </tbody> </table>	Ingredient name	°C	°F	Method	<input checked="" type="checkbox"/> Acetonitrile	524	975.2	-
Ingredient name	°C	°F	Method						
<input checked="" type="checkbox"/> Acetonitrile	524	975.2	-						

Decomposition temperature : Not available.

Viscosity : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Section 10. Stability and reactivity

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials
Incompatible with hydrogen fluoride.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetonitrile	LC50 Inhalation Vapor LD50 Oral	Rat Rat	17100 ppm 2460 mg/kg	4 hours -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetonitrile	Eyes - Moderate irritant	Rabbit	-	24 hours 100 uL	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Acetonitrile	Category 2	-	blood system, central nervous system (CNS), kidneys, liver

Aspiration hazard

Not available.

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Section 11. Toxicological information

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Pursuit C18 LC Columns with less than 10ml solvent Acetonitrile	2083.3 500	4583.3 1100	N/A N/A	45.8 11	N/A N/A

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Acetonitrile	Acute IC50 3685000 µg/l Fresh water Acute LC50 3600000 µg/l Fresh water Acute LC50 1000000 µg/l Fresh water Chronic NOEC 1000000 µg/l Fresh water Chronic NOEC 160000 µg/l Fresh water	Aquatic plants - <i>Lemna minor</i> Daphnia - <i>Daphnia magna</i> Fish - <i>Pimephales promelas</i> Aquatic plants - <i>Lemna minor</i> Daphnia - <i>Daphnia magna</i>	96 hours 48 hours 96 hours 96 hours 21 days

12.2 Persistence and degradability

Section 12. Ecological information

Product/ingredient name	Test	Result	Dose	Inoculum
Acetonitrile	OECD 310 Ready Biodegradability - CO ₂ in Sealed Vessels (Headspace Test)	70 % - Readily - 21 days	-	Activated sludge

Conclusion/Summary : Based on chemical experience, will degrade over very long period of time.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetonitrile	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Acetonitrile	-0.34	3	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Acetonitrile (I,T)	75-05-8	Listed	U003

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 13. Disposal considerations

for additional handling information and protection of employees.

Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / : Not regulated.

IATA

Additional information

Remarks :Special provisions

DOT: 47

TDG: 56

MX: 216

IATA: A46

IMDG: 216

Special precautions for user : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : TSCA 8(a) PAIR: Acetonitrile
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
Clean Water Act (CWA) 307: Acetonitrile

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 2
EYE IRRITATION - Category 2A
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Composition/information on ingredients

Section 15. Regulatory information

Name	%	Classification
Organosilane bonded silica gel Acetonitrile	≥50 - ≤75 ≥10 - <25	COMBUSTIBLE DUSTS FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Acetonitrile	75-05-8	≥10 - <25
Supplier notification	Acetonitrile	75-05-8	≥10 - <25

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

- Massachusetts** : The following components are listed: ACETONITRILE
- New York** : The following components are listed: Acetonitrile
- New Jersey** : The following components are listed: ACETONITRILE
- Pennsylvania** : The following components are listed: ACETONITRILE

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- China** : All components are listed or exempted.
- Japan** : **Japan inventory (CSCL)**: All components are listed or exempted.
Japan inventory (ISHL): All components are listed or exempted.
- New Zealand** : All components are listed or exempted.
- Philippines** : Not determined.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.
- Thailand** : Not determined.
- Turkey** : All components are listed or exempted.
- United States** : All components are active or exempted.

Section 15. Regulatory information

Viet Nam : Not determined.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Expert judgment Calculation method Calculation method

History

Date of issue/Date of revision : 11/20/2023

Date of previous issue : 11/17/2020

Version : 5

Key to abbreviations

: ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 UN = United Nations

📌 Indicates information that has changed from previously issued version.

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.