

SAFETY DATA SHEET



Pursuit LC Columns with less than 10 ml ACN type solvent

Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier

- Product name** : Pursuit LC Columns with less than 10 ml ACN type solvent
- Part no.** : A3030MG2, A3031MG2, A3040MG2, A3041MG2, A3050MG2, A3051MG2, A6000MG2, A6001MG2, A6010MG2, A6011MG2, A6020MG2, A6021MG2, A3041050X010, A3051050X010, A3040050X010, A6021050X010, A3031020X020, A304201G, A3030050X020, A3040050X020, A3050050X020, A600201G, A3051020X020, A7000MG3, A7001MG3, A3041100X010, A3041030X020, A3051030X020, A3040030X020, A6021030X020, A6000030X020, A7501030X020, A7511030X020, A7521030X020, A3040030X021, A3031050X020, A3041050X020, A3051050X020, A6011050X020, A6021050X020, A6000050X020, A6020050X020, A7501050X020, A7511050X020, A7521050X020, A3030MG, A3031MG, A3040MG, A3041MG, A3050MG, A3051MG, A6000MG, A6001MG, A6002MG, A6010MG, A6011MG, A6020MG, A6021MG, A3030050X021, A3040050X021, A3051030X030, A6021030X030, A3031100X020, A3041100X020, A7001100X020, A3051100X020, A3040100X020, A3050100X020, A6011100X020, A6021100X020, A6000100X020, A7501100X020, A7511100X020, A7521100X020, A3040100X021, A3041050X030, A6000050X030, A3031150X020, A3041150X020, A3051150X020, A3030150X020, A3040150X020, A3050150X020, A6011150X020, A6021150X020, A6000150X020, A6010150X020, A6020150X020, A7501150X020, A7521150X020, A3041030X046, A3030030X046, A3040030X046, A6021030X046, A3040150X021, A3050150X021, A3041200X020, A3031100X030, A3041100X030, A7001100X030, A7001100R030, A3051100X030, A7000100R030, A6000100T030, A6011100X030, A6021100X030, A6000100X030, A6011100C030S, A7000100T030, A7001100C030, A6000100R030, A7501100X030, A3041250X020, A3051250X020, A3040250X020, A3050250X020, A6021250X020, A6000250X020, A6020250X020, A3031050X046, A3041050X046, A3051050X046, A3030050X046, A3040050X046, A6002050X046S, A6001050C046, A6011050X046, A6021050X046, A6000050X046, A6020050X046, A3031150X030, A3041150X030, A7001150X030S, A3051150X030, A3050150X030, A6000150C030, A6021150X030, A6011150C030, A6000150X030, A6010150X030, A6000150R030, A7501150X030, A7511150X030, A6021075X046, A7001100R040S, A3030125X040, A6000125X040, A6010125X040, A3031100X046, A3041100X046, A7001100X046, A3041100C046, A7001100R046, A3051100X046, A3030100X046, A3050100X046, A6000100C046, A6001100C046, A6011100X046, A6021100X046, A6000100X046, A6010100X046, A6020100X046, A7001100C046, A7001100T046, A7001100T046ANL, A3040250X030, A3050250X030, A6000250X030, A7000250C030S, A6020250X030, A3030150X039, A6000150X040, A6010150X040, A6020150X040, A6000120X046, A6000125X046, A6010125X046, A3032150X046, A3031150C046, A3031150X046, A3041150X046, A3040150C046, A7001150X046S, A7001150R046, A3051150X046, A3030150X046, A3040150X046, A7000150X046, A7000150R046, A3050150X046, A6000150C046, A6001150C046, A6011150X046, A6021150X046, A6010150C046, A6000150X046, A6010150X046, A7000150C046, A7000150T046, A6020150X046, A7001150C046, A6000150R046, A3030250X040, A6000250X040, A6010250X040, A3050200X046, A6000200X046, A3032050G100, A6002050G100, A6000050X100, A6000050G100, A3030250C046, A3032250X046, A3041250X046, A3030250X046, A3030250R046, A3040250X046, A7000250X046, A7000250R046, A3050250X046, A6000250C046, A6002250X046, A6011250X046, A6021250X046, A6000250X046, A6010250X046, A7000250C046, A7000250T046, A6020250X046, A6000250R046, A3040150X080, A6020100X100, A3041150X100, A3050150X100, A6002150X100, A6010150X100, A6000150X100

Validation date : 3/19/2024

1.2 Relevant identified uses of the substance or mixture and uses advised against

Section 1. Identification

Identified uses

: Analytical chemistry.
 HPLC column
 Solvent volume: <10 ml
 A3030MG2 MetaGuard 2.0 mm Pursuit 5u C8 0.02mL Solvent
 A3031MG2 MetaGuard 2.0 mm Pursuit 3u C8 0.02mL Solvent
 A3040MG2 MetaGuard 2.0 mm Pursuit 5u DP 0.02mL Solvent
 A3041MG2 MetaGuard 2.0 mm Pursuit 3u DP 0.02mL Solvent
 A3050MG2 MetaGuard 2.0 mm Pursuit 5u PFP 0.02mL Solvent
 A3051MG2 MetaGuard 2.0 mm Pursuit 3u PFP 0.02mL Solvent
 A6000MG2 MetaGuard 2.0 mm Pursuit XRs 5U C18, 3/Pk 0.02mL Solvent
 A6001MG2 MetaGuard 2.0 mm Pursuit XRs 3U C18, 3/Pk 0.02mL Solvent
 A6010MG2 MetaGuard 2.0 mm Pursuit XRs 5U C8, 3/Pk 0.02mL Solvent
 A6011MG2 MetaGuard 2.0 mm Pursuit XRs 3U C8, 3/Pk 0.02mL Solvent
 A6020MG2 MetaGuard 2.0 mm Pursuit XRs 5U Dp, 3/Pk 0.02mL Solvent
 A6021MG2 MetaGuard 2.0 mm Pursuit XRs 3U Dp, 3/Pk 0.02mL Solvent
 A3041050X010 Pursuit 3 Diphenyl 50 x 1.0 mm
 A3051050X010 Pursuit 3 PFP 50 x 1.0 mm 0.03mL Solvent
 A3040050X010 Pursuit 5 Diphenyl 50 x 1.0 mm
 A6021050X010 Pursuit XRs 3 Diphenyl 50 x 1.0 mm 0.03mL Solvent
 A3031020X020 Pursuit 3 C8 20 x 2.0 mm 0.05mL Solvent
 A3051020X020 Pursuit 3 PFP 20 x 2.0 mm 0.05mL Solvent
 A7000MG3 Pursuit 5 PAH MetaGuard 3.0 mm 3/Pk
 A7001MG3 Pursuit 3 PAH MetaGuard 3.0 mm 3/Pk
 A3041100X010 Pursuit 3 Diphenyl 100 x 1.0 mm 0.06mL Solvent
 A3041030X020 Pursuit 3 Diphenyl 30 x 2.0 mm
 A3051030X020 Pursuit 3 PFP 30 x 2.0 mm 0.07mL Solvent
 A3040030X020 Pursuit 5 Diphenyl 30 x 2.0 mm
 A6021030X020 Pursuit XRs 3 Diphenyl 30 x 2.0 mm 0.07mL Solvent
 A6000030X020 Pursuit XRs 5 C18 30 x 2.0 mm
 A7501030X020 Pursuit XRs Ultra 2.8 C18 30 x 2.0 mm 0.07mL Solvent
 A7511030X020 Pursuit XRS Ultra 2.8 C8 30 x 2.0 mm 0.07mL Solvent
 A7521030X020 Pursuit XRS Ultra 2.8 Diphenyl 30x2.0 mm 0.07mL Solvent
 A3040030X021 Pursuit 5 Diphenyl 30 x 2.1 mm
 A3031050X020 Pursuit 3 C8 50 x 2.0 mm 0.11mL Solvent
 A3041050X020 Pursuit 3 Diphenyl 50 x 2.0 mm
 A3051050X020 Pursuit 3 PFP 50 x 2.0 mm 0.11mL Solvent
 A304201G Pursuit 10u Diphenyl
 A3030050X020 Pursuit 5 C8 50 x 2.0 mm 0.11mL Solvent
 A3040050X020 Pursuit 5 Diphenyl 50 x 2.0 mm
 A3050050X020 Pursuit 5 PFP 50 x 2.0 mm 0.11mL Solvent
 A600201G Pursuit XRs 10 C18 0.11mL Solvent
 A6011050X020 Pursuit XRs 3 C8 50 x 2.0 mm
 A6021050X020 Pursuit XRs 3 Diphenyl 50 x 2.0 mm 0.11mL Solvent
 A6000050X020 Pursuit XRs 5 C18 50 x 2.0 mm
 A6020050X020 Pursuit XRs 5 Diphenyl 50 x 2.0 mm 0.11mL Solvent
 A7501050X020 Pursuit XRs Ultra 2.8 C18 50 x 2.0 mm 0.11mL Solvent
 A7511050X020 Pursuit XRS Ultra 2.8 C8 50 x 2.0 mm 0.11mL Solvent
 A7521050X020 Pursuit XRS Ultra 2.8 Diphenyl 50x2.0 mm 0.11mL Solvent
 A3030MG MetaGuard 4.6 mm Pursuit 5u C8 0.11mL Solvent
 A3031MG MetaGuard 4.6 mm Pursuit 3u C8 0.11mL Solvent
 A3040MG MetaGuard 4.6 mm Pursuit 5u DP 0.11mL Solvent
 A3041MG MetaGuard 4.6 mm Pursuit 3u DP 0.11mL Solvent
 A3050MG MetaGuard 4.6 mm Pursuit 5u PFP 0.11mL Solvent
 A3051MG MetaGuard 4.6 mm Pursuit 3u PFP 0.11mL Solvent
 A6000MG MetaGuard 4.6 mm Pursuit XRs 5U C18, 3/Pk 0.11mL Solvent
 A6001MG MetaGuard 4.6 mm Pursuit XRs 3U C18, 3/P 0.11mL Solvent
 A6002MG MetaGuard 4.6 mm Pursuit XRs 10U C18, 3/P 0.11mL Solvent
 A6010MG MetaGuard 4.6 mm Pursuit XRs 5U C8, 3/Pk 0.11mL Solvent
 A6011MG MetaGuard 4.6 mm Pursuit XRs 3U C8, 3/Pk 0.11mL Solvent
 A6020MG MetaGuard 4.6 mm Pursuit XRs 5U Dp, 3/Pk

Section 1. Identification

A6021MG MetaGuard 4.6 mm Pursuit XRs 3U Dp, 3/Pk
A3030050X021 Pursuit 5 C8 50 x 2.1 mm 0.13mL Solvent
A3040050X021 Pursuit 5 Diphenyl 50 x 2.1 mm
A3051030X030 Pursuit 3 PFP 30 x 3.0 mm 0.15mL Solvent
A6021030X030 Pursuit XRs 3 Diphenyl 30 x 3.0 mm 0.15mL Solvent
A3031100X020 Pursuit 3 C8 100 x 2.0 mm 0.23mL Solvent
A3041100X020 Pursuit 3 Diphenyl 100 x 2.0 mm 0.23mL Solvent
A7001100X020 Pursuit 3 PAH 100 x 2.0 mm 0.23mL Solvent
A3051100X020 Pursuit 3 PFP 100 x 2.0 mm 0.23mL Solvent
A3040100X020 Pursuit 5 Diphenyl 100 x 2.0 mm 0.23mL Solvent
A3050100X020 Pursuit 5 PFP 100 x 2.0 mm 0.23mL Solvent
A6011100X020 Pursuit XRs 3 C8 100 x 2.0 mm 0.23mL Solvent
A6021100X020 Pursuit XRs 3 Diphenyl 100 x 2.0 mm 0.23mL Solvent
A6000100X020 Pursuit XRs 5 C18 100 x 2.0 mm
A7501100X020 Pursuit XRs Ultra 2.8 C18 100 x 2.0 mm
A7511100X020 Pursuit XRS Ultra 2.8 C8 100 x 2.0 mm
A7521100X020 Pursuit XRS Ultra 2.8 Diphenyl 100x2.0 mm 0.23mL Solvent
A3040100X021 Pursuit 5 Diphenyl 100 x 2.1 mm 0.25mL Solvent
A3041050X030 Pursuit 3 Diphenyl 50 x 3.0 mm
A6000050X030 Pursuit XRs 5 C18 50 x 3.0 mm
A3031150X020 Pursuit 3 C8 150 x 2.0 mm 0.34mL Solvent
A3041150X020 Pursuit 3 Diphenyl 150 x 2.0 mm 0.34mL Solvent
A3051150X020 Pursuit 3 PFP 150 x 2.0 mm 0.34mL Solvent
A3030150X020 Pursuit 5 C8 150 x 2.0 mm 0.34mL Solvent
A3040150X020 Pursuit 5 Diphenyl 150 x 2.0 mm 0.34mL Solvent
A3050150X020 Pursuit 5 PFP 150 x 2.0 mm 0.34mL Solvent
A6011150X020 Pursuit XRs 3 C8 150 x 2.0 mm
A6021150X020 Pursuit XRs 3 Diphenyl 150 x 2.0 mm 0.34mL Solvent
A6000150X020 Pursuit XRs 5 C18 150 x 2.0 mm
A6010150X020 Pursuit XRs 5 C8 150 x 2.0 mm
A6020150X020 Pursuit XRs 5 Diphenyl 150 x 2.0 mm 0.34mL Solvent
A7501150X020 Pursuit XRs Ultra 2.8 C18 150X 2.0MM
A7521150X020 Pursuit XRs Ultra 2.8 Diphenyl 150X2.0 mm 0.34mL Solvent
A3041030X046 Pursuit 3 Diphenyl 30 x 4.6 mm
A3030030X046 Pursuit 5 C8 30 x 4.6 mm 0.36mL Solvent
A3040030X046 Pursuit 5 Diphenyl 30 x 4.6 mm
A6021030X046 Pursuit XRs 3 Diphenyl 30 x 4.6 mm 0.36mL Solvent
A3040150X021 Pursuit 5 Diphenyl 150 x 2.1 mm 0.37mL Solvent
A3050150X021 Pursuit 5 PFP 150 x 2.1 mm 0.37mL Solvent
A3041200X020 Pursuit 3 Diphenyl 200 x 2.0 mm 0.45mL Solvent
A3031100X030 Pursuit 3 C8 100 x 3.0 mm
A3041100X030 Pursuit 3 Diphenyl 100 x 3.0 mm 0.51mL Solvent
A7001100X030 Pursuit 3 PAH 100 x 3.0 mm
A7001100R030 Pursuit 3 PAH, S100 x 3.0 Repl.
A3051100X030 Pursuit 3 PFP 100 x 3.0 mm
A7000100R030 PURSUIT 5 PAH, S100 X 3.0 REPL. 0.51mL Solvent
A6000100T030 Pursuit XRs 5-C18 S100 x 3.0 Repl.3 0.51mL Solvent
A6011100X030 Pursuit XRs 3 C8 100 x 3.0 mm
A6021100X030 Pursuit XRs 3 Diphenyl 100 x 3.0 mm 0.51mL Solvent
A6000100X030 Pursuit XRs 5 C18 100 x 3.0 mm
A6011100C030S S Pursuit xRs 3 C8 100 x 3.0 mm Col 0.51mL Solvent
A7000100T030 PURSUIT 5 PAH, S100 X 3.0 REPL.3 0.51mL Solvent
A7001100C030 Pursuit 3 PAH, S100 x 3.0 Col
A6000100R030 Pursuit XRs 5-C18 S100 x 3.0 Repl. 0.51mL Solvent
A7501100X030 Pursuit XRs Ultra 2.8 C18 100 x 3.0 mm
A3041250X020 Pursuit 3 Diphenyl 250 x 2.0 mm 0.57mL Solvent
A3051250X020 Pursuit 3 PFP 250 x 2.0 mm 0.57mL Solvent
A3040250X020 Pursuit 5 Diphenyl 250 x 2.0 mm 0.57mL Solvent
A3050250X020 Pursuit 5 PFP 250 x 2.0 mm 0.57mL Solvent
A6021250X020 Pursuit XRs 3 Diphenyl 250 x 2.0 mm 0.57mL Solvent

Section 1. Identification

A6000250X020 Pursuit XRs 5 C18 250 x 2.0 mm
A6020250X020 Pursuit XRs 5 Diphenyl 250 x 2.0 mm
A3031050X046 Pursuit 3 C8 50 x 4.6 mm 0.60mL Solvent
A3041050X046 Pursuit 3 Diphenyl 50 x 4.6 mm
A3051050X046 Pursuit 3 PFP 50 x 4.6 mm 0.60mL Solvent
A3030050X046 Pursuit 5 C8 50 x 4.6 mm 0.60mL Solvent
A3040050X046 Pursuit 5 Diphenyl 50 x 4.6 mm
A6002050X046S S Pursuit XRs 10 C18 50 x 4.6 mm 0.60mL Solvent
A6001050C046 Pursuit XRs 3-C18, S50 X 4.6 Col
A6011050X046 Pursuit XRs 3 C8 50 x 4.6 mm 0.60mL Solvent
A6021050X046 Pursuit XRs 3 Diphenyl 50 x 4.6 mm 0.60mL Solvent
A6000050X046 Pursuit XRs 5 C18 50 x 4.6 mm
A6020050X046 Pursuit XRs 5 Diphenyl 50 x 4.6 mm 0.60mL Solvent
A3031150X030 Pursuit 3 C8 150 x 3.0 mm 0.76mL Solvent
A3041150X030 Pursuit 3 Diphenyl 150 x 3.0 mm 0.76mL Solvent
A7001150X030S S Pursuit 3 PAH 150 x 3.0 mm 0.76mL Solvent
A3051150X030 Pursuit 3 PFP 150 x 3.0 mm 0.76mL Solvent
A3050150X030 Pursuit 5 PFP 150 x 3.0 mm 0.76mL Solvent
A6000150C030 Pursuit XRs 5-C18 S150 x 3.0 Col 0.76mL Solvent
A6021150X030 Pursuit XRs 3 Diphenyl 150 x 3.0 mm 0.76mL Solvent
A6011150C030 Pursuit XRs 3 C8, S150 x 3.0 Col.
A6000150X030 Pursuit XRs 5 C18 150 x 3.0 mm
A6010150X030 Pursuit XRs 5 C8 150 x 3.0 mm
A6000150R030 Pursuit XRs 5-C18 S150 x 3.0 Repl. 0.76mL Solvent
A7501150X030 Pursuit XRs Ultra 2.8 C18 150 x 3.0 mm
A7511150X030 Pursuit XRs Ultra 2.8 C8 150 x 3.0 mm
A6021075X046 Pursuit XRs 3 Diphenyl 75 x 4.6 mm
A7001100R040S S Pursuit 3 PAH 100 x 4.0 mm
A3030125X040 Pursuit 5 C8 125 x 4.0 mm
A6000125X040 Pursuit XRs 5 C18 125 x 4.0 mm
A6010125X040 Pursuit XRs 5 C8 125 x 4.0 mm
A3031100X046 Pursuit 3 C8 100 x 4.6 mm
A3041100X046 Pursuit 3 Diphenyl 100 x 4.6 mm 1.20mL Solvent
A7001100X046 Pursuit 3 PAH 100 x 4.6 mm
A3041100C046 Pursuit 3 Diphenyl, S100X4.6 mm Col
A7001100R046 Pursuit 3 PAH, S100 x 4.6 Repl.
A3051100X046 Pursuit 3 PFP 100 x 4.6 mm 1.20mL Solvent
A3030100X046 Pursuit 5 C8 100 x 4.6 mm 1.20mL Solvent
A3050100X046 Pursuit 5 PFP 100 x 4.6 mm 1.20mL Solvent
A6000100C046 Pursuit XRs 5-C18 S100 x 4.6 Col 1.20mL Solvent
A6001100C046 Pursuit XRs 3-C18 S100 x 4.6 Col 1.20mL Solvent
A6011100X046 Pursuit XRs 3 C8 100 x 4.6 mm
A6021100X046 Pursuit XRs 3 Diphenyl 100 x 4.6 mm
A6000100X046 Pursuit XRs 5 C18 100 x 4.6 mm
A6010100X046 Pursuit XRs 5 C8 100 x 4.6 mm
A6020100X046 Pursuit XRs 5 Diphenyl 100 x 4.6 mm
A7001100C046 Pursuit 3 PAH, S100 x 4.6 Col
A7001100T046 Pursuit 3 PAH, S100 x 4.6 Repl.3 1.20mL Solvent
A7001100T046ANL ANL Pursuit 3 PAH, S100 x 4.6 Repl.3 1.20mL Solvent
A3040250X030 Pursuit 5 Diphenyl 250 x 3.0 mm 1.27mL Solvent
A3050250X030 Pursuit 5 PFP 250 x 3.0 mm
A6000250X030 Pursuit XRs 5 C18 250 x 3.0 mm
A7000250C030S S Pursuit 5 PAH 250 x 3.0 mm Col 1.27mL Solvent
A6020250X030 Pursuit XRs 5 Diphenyl 250 x 3.0 mm 1.27mL Solvent
A3030150X039 Pursuit 5 C8 150 x 3.9 mm 1.29mL Solvent
A6000150X040 Pursuit XRs 5 C18 150 x 4.0 mm
A6010150X040 Pursuit XRs 5 C8 150 x 4.0 mm
A6020150X040 Pursuit XRs 5 Diphenyl 150 x 4.0 1.36mL Solvent
A6000120X046 Pursuit XRs 5 C18 120 x 4.6 mm
A6000125X046 Pursuit XRs 5 C18 125 x 4.6 mm

Section 1. Identification

A6010125X046 Pursuit XRs 5 C8 125 x 4.6 mm
A3032150X046 Pursuit 10 C8 150 x 4.6 mm
A3031150C046 Pursuit 3 C8 , S150x4.6 Col
A3031150X046 Pursuit 3 C8 150 x 4.6 mm
A3041150X046 Pursuit 3 Diphenyl 150 x 4.6 mm 1.80mL Solvent
A3040150C046 Pursuit 5 Diphenyl, S150X4.6 Col 1.80mL Solvent
A7001150X046S S Pursuit 3 PAH 150 x 4.6 mm conv. Column 1.80mL Solvent
A7001150R046 Pursuit 3 PAH, S150 x 4.6 Repl.
A3051150X046 Pursuit 3 PFP 150 x 4.6 mm
A3030150X046 Pursuit 5 C8 150 x 4.6 mm
A3040150X046 Pursuit 5 Diphenyl 150 x 4.6 mm 1.80mL Solvent
A7000150X046 Pursuit 5 PAH 150 x 4.6 mm
A7000150R046 Pursuit 5 PAH, S150 x 4.6 Repl.
A3050150X046 Pursuit 5 PFP 150 x 4.6 mm
A6000150C046 Pursuit XRs 5-C18 S150 x 4.6 Col 1.80mL Solvent
A6001150C046 Pursuit XRs 3-C18 S150 x 4.6 Col 1.80mL Solvent
A6011150X046 Pursuit XRs 3 C8 150 x 4.6 mm
A6021150X046 Pursuit XRs 3 Diphenyl 150 x 4.6 mm
A6010150C046 Pursuit XRs 5-C8 S150 x 4.6 Col
A6000150X046 Pursuit XRs 5 C18 150 x 4.6 mm
A6010150X046 Pursuit XRs 5 C8 150 x 4.6 mm
A7000150C046 Pursuit 5 PAH, S150 x 4.6 Col
A7000150T046 Pursuit 5 PAH, S150 x 4.6 Repl.3
A6020150X046 Pursuit XRs 5 Diphenyl 150 x 4.6 mm
A7001150C046 Pursuit 3 PAH, S150 x 4.6 Col.
A6000150R046 Pursuit XRs 5-C18 S150 x 4.6 Repl. 1.80mL Solvent
A3030250X040 Pursuit 5 C8 250 x 4.0 mm
A6000250X040 Pursuit XRs 5 C18 250 x 4.0 mm
A6010250X040 Pursuit XRs 5 C8 250 x 4.0 mm
A3050200X046 Pursuit 5 PFP 200 x 4.6 mm
A6000200X046 Pursuit XRs 5 C18 200 x 4.6 mm
A3032050G100 Pursuit 10u C8 50 x 10.0 mm Guard
A6002050G100 Pursuit XRs 10 C18 50 x 10.0 mm Guard
A6000050X100 Pursuit XRs 5 C18 50 x 10.0 mm
A6000050G100 Pursuit XRs 5 C18 50 x 10.0 mm Guard
A3030250C046 Pursuit 5 C8, S250x4.6 Col
A3032250X046 Pursuit 10 C8 250 x 4.6 mm
A3041250X046 Pursuit 3 Diphenyl 250 x 4.6 mm 2.99mL Solvent
A3030250X046 Pursuit 5 C8 250 x 4.6 mm 2.99mL Solvent
A3030250R046 Pursuit 5 C8, S250x4.6 Repl 2.99mL Solvent
A3040250X046 Pursuit 5 Diphenyl 250 x 4.6 mm 2.99mL Solvent
A7000250X046 Pursuit 5 PAH 250 x 4.6 mm
A7000250R046 Pursuit 5 PAH, S250 x 4.6 Repl.
A3050250X046 Pursuit 5 PFP 250 x 4.6 mm
A6000250C046 Pursuit XRs 5-C18 S250 x 4.6 Col2.99mL Solvent
A6002250X046 Pursuit XRs 10 C18 250 x 4.6 mm 2.99mL Solvent
A6011250X046 Pursuit XRs 3 C8 250 x 4.6 mm
A6021250X046 Pursuit XRs 3 Diphenyl 250 x 4.6 mm
A6000250X046 Pursuit XRs 5 C18 250 x 4.6 mm
A6010250X046 Pursuit XRs 5 C8 250 x 4.6 mm
A7000250C046 Pursuit 5 PAH, S250 x 4.6 Col
A7000250T046 Pursuit 5 PAH, S250 x 4.6 Repl.3 2.99mL Solvent
A6020250X046 Pursuit XRs 5 Diphenyl 250 x 4.6 mm 2.99mL Solvent
A6000250R046 Pursuit XRs 5-C18 S250 x 4.6 Repl. 2.99mL Solvent
A3040150X080 Pursuit 5 Diphenyl 150 x 8.0 mm 5.43mL Solvent
A6020100X100 Pursuit XRs 5u DP 100 x 10.0 mm 5.66mL Solvent
A3041150X100 Pursuit 3u DP 150 x 10.0 mm
A3050150X100 Pursuit 5u PFP 150 x 10.0 mm
A6002150X100 Pursuit XRs 10 C18 150x10.0 mm 8.48mL Solvent
A6010150X100 Pursuit XRs 5u C-8 150 x 10.0 mm 8.48mL Solvent

Section 1. Identification

A6000150X100 Pursuit XRs 5 C18 150 x 10.0 mm 8.48mL Solvent

[1.3 Details of the supplier of the safety data sheet](#)

Supplier/Manufacturer : Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051, USA
800-227-9770

[1.4 Emergency telephone number](#)

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

[2.1 Classification of the substance or mixture](#)


OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

[Classification of the substance or mixture](#)

H225 FLAMMABLE LIQUIDS - Category 2
H319 EYE IRRITATION - Category 2A

[2.2 GHS label elements](#)

Hazard pictograms



Signal word

: Danger

Hazard statements

: **H225** - Highly flammable liquid and vapor.
H319 - Causes serious eye irritation.

Precautionary statements

Prevention

: **P280** - Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 - Use explosion-proof electrical, ventilating or lighting equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P233 - Keep container tightly closed.

Response

: **P305 + P351 + P338** - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage

: **P403 + P235** - Store in a well-ventilated place. Keep cool.

Disposal

: **P501** - Dispose of contents and container in accordance with all local, regional, national and international regulations.

[2.3 Other hazards](#)

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

Substance/mixture : Mixture (encapsulated in article)

Ingredient name	%	CAS number
Acetonitrile	≥10 - <25	75-05-8

Contains: Organosilane bonded silica gel

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Section 4. First aid measures

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides
cyanides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Section 6. Accidental release measures

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Industrial applications, Professional applications.

Industrial sector specific solutions : Not available.

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

[8.1 Control parameters](#)

[Occupational exposure limits](#)

Ingredient name	Exposure limits
Acetonitrile	<p>ACGIH TLV (United States, 1/2023). Absorbed through skin. TWA: 20 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 40 ppm 8 hours. TWA: 70 mg/m³ 8 hours. STEL: 60 ppm 15 minutes. STEL: 105 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2020). TWA: 20 ppm 10 hours. TWA: 34 mg/m³ 10 hours.</p> <p>OSHA PEL (United States, 5/2018). TWA: 40 ppm 8 hours. TWA: 70 mg/m³ 8 hours.</p> <p>CAL OSHA PEL (United States, 5/2018). Absorbed through skin. STEL: 105 mg/m³ 15 minutes. STEL: 60 ppm 15 minutes. TWA: 70 mg/m³ 8 hours. TWA: 40 ppm 8 hours.</p>

[Biological exposure indices](#)

No exposure indices known.

[8.2 Exposure controls](#)

[Appropriate engineering controls](#)

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

[Environmental exposure controls](#)

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

[Individual protection measures](#)

[Hygiene measures](#)

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

[Eye/face protection](#)

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

[Skin protection](#)

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Solid. (containing flammable liquid)
- Color** : White.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Neutral.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : Not available.
- Flash point** : Closed cup: -18 to 23°C (-0.4 to 73.4°F) [Based on solvent.]
- Evaporation rate** : Not available.
- Flammability** : Contains: Flammable liquid
- Lower and upper explosion limit/flammability limit** : Not available.

Vapor pressure

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
<input checked="" type="checkbox"/> Acetonitrile	70.88853	9.5	-	-	-	-
water	17.5	2.3	-	92.258	12.3	-

Relative vapor density : Not available.

Relative density : Not available.

Solubility(ies)

Media	Result
<input checked="" type="checkbox"/> Mobile phase	Soluble
Stationary phase	Insoluble

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Section 9. Physical and chemical properties and safety characteristics

Ingredient name	°C	°F	Method
Acetonitrile	524	975.2	-

Decomposition temperature : Not available.

Viscosity : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials
Incompatible with hydrogen fluoride.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetonitrile	LC50 Inhalation Vapor LD50 Oral	Rat Rat	17100 ppm 2460 mg/kg	4 hours -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetonitrile	Eyes - Moderate irritant	Rabbit	-	24 hours 100 uL	-

Sensitization

Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
<input checked="" type="checkbox"/> Pursuit LC Columns with less than 10 ml ACN type solvent	2083.3	4583.3	N/A	45.8	N/A
Acetonitrile	500	1100	N/A	11	N/A

Section 11. Toxicological information

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Acetonitrile	Acute IC50 3685000 µg/l Fresh water	Aquatic plants - <i>Lemna minor</i>	96 hours
	Acute LC50 3600000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 1000000 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours
	Chronic NOEC 1000000 µg/l Fresh water	Aquatic plants - <i>Lemna minor</i>	96 hours
	Chronic NOEC 160000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Acetonitrile	OECD 310 Ready Biodegradability - CO ₂ in Sealed Vessels (Headspace Test)	70 % - Readily - 21 days	-	Activated sludge

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetonitrile	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Acetonitrile	-0.34	3	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

[United States - RCRA Toxic hazardous waste "U" List](#)

Section 13. Disposal considerations

Ingredient	CAS #	Status	Reference number
Acetonitrile (l,T)	75-05-8	Listed	U003

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / : Not regulated.

IATA

Additional information

Remarks: Special provisions

DOT: 47

TDG: 56

MX: 216

IATA: A46

IMDG: 216

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : TSCA 8(a) PAIR: Acetonitrile
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
Clean Water Act (CWA) 307: Acetonitrile

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

Section 15. Regulatory information

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 2
EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	%	Classification
<input checked="" type="checkbox"/> Organosilane bonded silica gel Acetonitrile	≥50 - ≤75 ≥10 - <25	COMBUSTIBLE DUSTS FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Acetonitrile	75-05-8	≥10 - <25
Supplier notification	Acetonitrile	75-05-8	≥10 - <25

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: ACETONITRILE

New York : The following components are listed: Acetonitrile

New Jersey : The following components are listed: ACETONITRILE

Pennsylvania : The following components are listed: ACETONITRILE

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

Section 15. Regulatory information

China	: <input checked="" type="checkbox"/> All components are listed or exempted.
Japan	: Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: <input checked="" type="checkbox"/> All components are listed or exempted.
Taiwan	: <input checked="" type="checkbox"/> All components are listed or exempted.
Thailand	: Not determined.
Turkey	: All components are listed or exempted.
United States	: All components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
<input checked="" type="checkbox"/> FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A	Expert judgment Calculation method

History

Date of issue/Date of revision	: 03/19/2024
Date of previous issue	: 06/04/2021
Version	: 6

Key to abbreviations

: ATE = Acute Toxicity Estimate
: BCF = Bioconcentration Factor
: GHS = Globally Harmonized System of Classification and Labelling of Chemicals
: IATA = International Air Transport Association
: IBC = Intermediate Bulk Container
: IMDG = International Maritime Dangerous Goods
: LogPow = logarithm of the octanol/water partition coefficient
: MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
: N/A = Not available
: UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.