

# Safety Data Sheet

acc. to OSHA HCS

Revision date: 01/08/2025

## 1 Identification

### · Product identifier

· **Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

· **Part no. :** RGO-606-1

### · Restrictions

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/ product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/ product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

· **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use

### · Details of the supplier of the safety data sheet

#### · Manufacturer/Supplier:

Agilent Technologies, Inc.  
5301 Stevens Creek Blvd.  
Santa Clara, CA 95051 USA

#### · Information department:

Telephone: 800-227-9770  
e-mail: [pdl-msds\\_author@agilent.com](mailto:pdl-msds_author@agilent.com)

· **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

## 2 Hazard(s) identification

### · Classification of the substance or mixture



GHS08 Health hazard

Germ Cell Mutagenicity 1B

Carcinogenicity 1B

Specific Target Organ Toxicity - Repeated Exposure 2

H340 May cause genetic defects.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

Eye Irritation 2A

Specific Target Organ Toxicity - Single Exposure 3

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

(Contd. on page 2)

# Safety Data Sheet acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 1)

**· Label elements**
**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**


GHS07 GHS08

**· Signal word** Danger

**· Hazard-determining components of labeling:**

dichloromethane

Gasoline, natural

**· Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

**· Precautionary statements**

P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:**
**· NFPA ratings (scale 0 - 4)**


Health = 2

Fire = 0

Reactivity = 0

(Contd. on page 3)

# Safety Data Sheet acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 2)

## · HMIS-ratings (scale 0 - 4)

|            |    |                |
|------------|----|----------------|
| HEALTH     | *2 | Health = *2    |
| FIRE       | 0  | Fire = 0       |
| REACTIVITY | 0  | Reactivity = 0 |

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

|           |                   |          |
|-----------|-------------------|----------|
| 75-09-2   | dichloromethane   | 96.2264% |
| 8006-61-9 | Gasoline, natural | 3.7736%  |

## 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.

(Contd. on page 4)

# Safety Data Sheet acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 3)

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

**PAC-1:**

|         |                 |         |
|---------|-----------------|---------|
| 75-09-2 | dichloromethane | 200 ppm |
|---------|-----------------|---------|

**PAC-2:**

|         |                 |         |
|---------|-----------------|---------|
| 75-09-2 | dichloromethane | 560 ppm |
|---------|-----------------|---------|

**PAC-3:**

|         |                 |           |
|---------|-----------------|-----------|
| 75-09-2 | dichloromethane | 6,900 ppm |
|---------|-----------------|-----------|

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

**Components with limit values that require monitoring at the workplace:**
**75-09-2 dichloromethane**

|     |                                                                              |
|-----|------------------------------------------------------------------------------|
| PEL | Short-term value: 125 ppm<br>Long-term value: 25 ppm<br>see 29 CFR 1910.1052 |
| REL | See Pocket Guide App. A                                                      |
| TLV | Long-term value: 50 ppm<br>BEI, A3                                           |

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 4)

**8006-61-9 Gasoline, natural**

|     |                                                                                                                         |
|-----|-------------------------------------------------------------------------------------------------------------------------|
| REL | See Pocket Guide App. A                                                                                                 |
| TLV | Short-term value: 1480 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 890 mg/m <sup>3</sup> , 300 ppm<br>bulk handling |

**· Ingredients with biological limit values:**
**75-09-2 dichloromethane**

|     |                                                                                                   |
|-----|---------------------------------------------------------------------------------------------------|
| BEI | 0.3 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Dichloromethane (semi-quantitative) |
|-----|---------------------------------------------------------------------------------------------------|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness  
For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour  
For direct contact with the chemical: butyl rubber: >4 hours

· **Eye protection:**

Safety glasses



Tightly sealed goggles

US

(Contd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 5)

**9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Fluid**Color:** Colorless· **Odor:** Like chlorine· **Odor threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition****Melting point/Melting range:** -95.1 °C (-139.2 °F)**Boiling point/Boiling range:** 40 °C (104 °F)· **Flash point:** Not applicable.· **Flammability (solid, gaseous):** Not applicable.· **Auto igniting:** 605 °C (1,121 °F)· **Decomposition temperature:** Not determined.· **Ignition temperature:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:****Lower:** 13 Vol %**Upper:** 22 Vol %· **Vapor pressure at 20 °C (68 °F):** 360 hPa (270 mm Hg)· **Density at 20 °C (68 °F):** 1.3 g/cm<sup>3</sup> (10.8485 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with****Water at 20 °C (68 °F):** 20 g/l· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:****Dynamic:** Not determined.**Kinematic:** Not determined.· **Solvent content:****Organic solvents:** 96.2 %**VOC content:** 0.00 %

0.0 g/l / 0.00 lb/gal

· **Other information** No further relevant information available.**10 Stability and reactivity**· **Reactivity** No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 6)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 75-09-2 dichloromethane

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | 1,600 mg/kg (rat)  |
| Dermal     | LD50     | >2,000 mg/kg (rat) |
| Inhalative | LC50/4 h | 88 mg/L (rat)      |

### 8006-61-9 Gasoline, natural

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | 14,000 mg/kg (rat)    |
| Dermal     | LD50     | >2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 300,000 mg/L (rat)    |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|           |                   |    |
|-----------|-------------------|----|
| 75-09-2   | dichloromethane   | 2A |
| 8006-61-9 | Gasoline, natural | 2B |

- **NTP (National Toxicology Program)**

|         |                 |   |
|---------|-----------------|---|
| 75-09-2 | dichloromethane | R |
|---------|-----------------|---|

- **OSHA-Ca (Occupational Safety & Health Administration)**

|         |                 |
|---------|-----------------|
| 75-09-2 | dichloromethane |
|---------|-----------------|

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**
  - Water hazard class 2 (Self-assessment): hazardous for water
  - Do not allow product to reach ground water, water course or sewage system.
  - Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
  - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                                                                     |                      |
|-------------------------------------------------------------------------------------|----------------------|
| · <b>Not Regulated, De minimis Quantities</b>                                       | -                    |
| · <b>UN-Number</b>                                                                  | UN1593               |
| · <b>DOT, IMDG, IATA</b>                                                            | UN1593               |
| · <b>UN proper shipping name</b>                                                    | Dichloromethane      |
| · <b>DOT</b>                                                                        | Dichloromethane      |
| · <b>IMDG, IATA</b>                                                                 | DICHLOROMETHANE      |
| · <b>Transport hazard class(es)</b>                                                 |                      |
| · <b>DOT</b>                                                                        |                      |
|  | 6.1 Toxic substances |
| · <b>Class</b>                                                                      | 6.1                  |
| · <b>Label</b>                                                                      | 6.1                  |
| · <b>IMDG, IATA</b>                                                                 |                      |
|  | 6.1 Toxic substances |
| · <b>Class</b>                                                                      | 6.1                  |
| · <b>Label</b>                                                                      | 6.1                  |
| · <b>Packing group</b>                                                              |                      |
| · <b>DOT, IMDG, IATA</b>                                                            | III                  |
| · <b>Environmental hazards:</b>                                                     |                      |
| Not applicable.                                                                     |                      |

(Contd. on page 9)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 8)

|                                                                                  |                                                                                                                  |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| · <b>Special precautions for user</b>                                            | Warning: Toxic substances                                                                                        |
| · <b>Hazard identification number (Kemler code):</b> 60                          |                                                                                                                  |
| · <b>EMS Number:</b>                                                             | F-A,S-A                                                                                                          |
| · <b>Segregation groups</b>                                                      | (SGG10) Liquid halogenated hydrocarbons                                                                          |
| · <b>Stowage Category</b>                                                        | A                                                                                                                |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.                                                                                                  |
| · <b>Transport/Additional information:</b>                                       |                                                                                                                  |
| · <b>DOT</b>                                                                     |                                                                                                                  |
| · <b>Quantity limitations</b>                                                    | On passenger aircraft/rail: 60 L<br>On cargo aircraft only: 220 L                                                |
| · <b>Hazardous substance:</b>                                                    | 1000 lbs, 454 kg                                                                                                 |
| · <b>IMDG</b>                                                                    |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                 | 5L                                                                                                               |
| · <b>Excepted quantities (EQ)</b>                                                | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>                                                  | UN 1593 DICHLOROMETHANE, 6.1, III                                                                                |

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

#### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

#### · Section 313 (Specific toxic chemical listings):

75-09-2 dichloromethane

#### · TSCA (Toxic Substances Control Act):

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/ product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/ product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

All components have the value ACTIVE.

(Contd. on page 10)

# Safety Data Sheet acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 9)

**· Hazardous Air Pollutants**

75-09-2 | dichloromethane

**· Proposition 65**
**· Chemicals known to cause cancer:**

75-09-2 | dichloromethane

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**· Carcinogenic categories**
**· EPA (Environmental Protection Agency)**

75-09-2 | dichloromethane

L

**· TLV (Threshold Limit Value)**

All components have the value A3.

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

All ingredients are listed.

**· National regulations:**
**· Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

**· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

**· Department issuing SDS:** Document Control / Regulatory

**· Contact:** pdl-acg-regulatory-cq@agilent.com

**· Date of preparation / last revision** 01/08/2025 / 4

**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Composite Unleaded Gasoline Standard (1X1 mL)**

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Skin Irritation 2: Skin corrosion/irritation – Category 2  
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A  
Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B  
Carcinogenicity 1B: Carcinogenicity – Category 1B  
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3  
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2  
· \* **Data compared to the previous version altered.**

US