

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

1 Identification

- **Product identifier**
- **Trade name:** GRO Standard (1X1 mL)
- **Part number:** SPA-100-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS06



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

methanol

benzene

1,2-dibromoethane

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 1)

1,2-dichloroethane

· Hazard statements

Highly flammable liquid and vapor.

Toxic if inhaled.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 1

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = *1

Fire = 3

Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures
· Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 2)

· Dangerous components:		
67-56-1	methanol	97.219%
106-93-4	1,2-dibromoethane	0.253%
91-20-3	naphthalene	0.253%
71-43-2	benzene	0.253%
108-88-3	toluene	0.253%
100-41-4	ethylbenzene	0.253%
98-82-8	cumene	0.253%
107-06-2	1,2-dichloroethane	0.253%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 3)

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-56-1	methanol	530 ppm
106-93-4	1,2-dibromoethane	17 ppm
108-38-3	m-xylene	130 ppm
91-20-3	naphthalene	15 ppm
71-43-2	benzene	52 ppm
108-88-3	toluene	67 ppm
100-41-4	ethylbenzene	33 ppm
98-82-8	cumene	50 ppm
107-06-2	1,2-dichloroethane	50 ppm
1634-04-4	tert-butyl methyl ether	50 ppm

· **PAC-2:**

67-56-1	methanol	2,100 ppm
106-93-4	1,2-dibromoethane	24 ppm
108-38-3	m-xylene	920 ppm
91-20-3	naphthalene	83 ppm
71-43-2	benzene	800 ppm
108-88-3	toluene	560 ppm
100-41-4	ethylbenzene	1100* ppm
98-82-8	cumene	300 ppm
107-06-2	1,2-dichloroethane	200 ppm
1634-04-4	tert-butyl methyl ether	570 ppm

· **PAC-3:**

67-56-1	methanol	7200* ppm
106-93-4	1,2-dibromoethane	46 ppm
108-38-3	m-xylene	2500* ppm
91-20-3	naphthalene	500 ppm
71-43-2	benzene	4000* ppm
108-88-3	toluene	3700* ppm
100-41-4	ethylbenzene	1800* ppm
98-82-8	cumene	730 ppm
107-06-2	1,2-dichloroethane	300 ppm
1634-04-4	tert-butyl methyl ether	5300* ppm

US

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

67-56-1 methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

106-93-4 1,2-dibromoethane

PEL	Long-term value: 20 ppm Ceiling limit value: 30; 50* ppm *5-min peak per 8-hr shift
REL	Long-term value: 0.045 ppm Ceiling limit value: 0.13* ppm *15-min; See Pocket Guide App. A
TLV	Skin

91-20-3 naphthalene

PEL	Long-term value: 50 mg/m ³ , 10 ppm
REL	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 5)

TLV Long-term value: 52 mg/m³, 10 ppm
Skin; BEI

71-43-2 benzene

PEL Short-term value: 15* mg/m³, 5* ppm
Long-term value: 3* mg/m³, 1* ppm
*table Z-2 for exclusions in 29CFR1910.1028(d)

REL Short-term value: 1 ppm
Long-term value: 0.1 ppm
See Pocket Guide App. A

TLV Short-term value: 8 mg/m³, 2.5 ppm
Long-term value: 1.6 mg/m³, 0.5 ppm
Skin; BEI

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm
BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm
BEI

98-82-8 cumene

PEL Long-term value: 245 mg/m³, 50 ppm
Skin

REL Long-term value: 245 mg/m³, 50 ppm
Skin

TLV Long-term value: (246) NIC-0.5 mg/m³, (50) NIC-0.1 ppm
NIC-A3

107-06-2 1,2-dichloroethane

PEL Long-term value: 50 ppm
Ceiling limit value: 100; 200* ppm
*5-min peak in any 3 hrs

REL Short-term value: 8 mg/m³, 2 ppm
Long-term value: 4 mg/m³, 1 ppm
See Pocket Guide Apps. A and C

TLV Long-term value: 40 mg/m³, 10 ppm

Ingredients with biological limit values:
67-56-1 methanol

BEI 15 mg/L
Medium: urine
Time: end of shift
Parameter: Methanol (background, nonspecific)

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 6)

71-43-2 benzene

BEI 25 µg/g creatinine
Medium: urine
Time: end of shift Parameter
Parameter: S-Phenylmercapturic acid (background)

500 µg/g creatinine
Medium: urine
Time: end of shift
Parameter: t,t-Muconic acid (background)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
Medium: end-exhaled air
Time: not critical
Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 7)

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form: Fluid

Color: Colorless

· Odor: Alcohol-like

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: -98 °C (-144.4 °F)

Boiling point/Boiling range: 64 °C (147.2 °F)

· Flash point: 9 °C (48.2 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 455 °C (851 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 5.5 Vol %

Upper: 44 Vol %

· Vapor pressure at 20 °C (68 °F): 100 hPa (75 mm Hg)

· Density at 20 °C (68 °F): 0.80679 g/cm³ (6.73266 lbs/gal)

· Relative density Not determined.

· Vapor density Not determined.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 8)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.2 %
VOC content:	99.24 %
	800.7 g/l / 6.68 lb/gal
Solids content:	0.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	21,756 mg/kg (rabbit)
Dermal	LD50	15,718 mg/kg
Inhalative	LC50/4 h	3.08 mg/L

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

106-93-4 1,2-dibromoethane

Oral	LD50	108 mg/kg (rat)
		55 mg/kg (rabbit)
Dermal	LD50	300 mg/kg (rabbit)

91-20-3 naphthalene

Oral	LD50	490 mg/kg (rat)
------	------	-----------------

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 9)

Dermal	LD50	5,000 mg/kg (rat) 20,000 mg/kg (rabbit)
71-43-2 benzene		
Oral	LD50	3,340 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse) >8,260 mg/kg (rabbit)
Inhalative	LC50/4 h	9,980 mg/L (mouse)
108-88-3 toluene		
Oral	LD50	5,580 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/L (mouse) 28.1 mg/L (rat)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,354 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/L (rat)
98-82-8 cumene		
Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/L (mouse)
107-06-2 1,2-dichloroethane		
Oral	LD50	670 mg/kg (rat)
Dermal	LD50	2,800 mg/kg (rat) 2,800 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

106-93-4	1,2-dibromoethane	2A
95-47-6	o-xylene	3
108-38-3	m-xylene	3
106-42-3	p-xylene	3
91-20-3	naphthalene	2B
71-43-2	benzene	1
108-88-3	toluene	3
100-41-4	ethylbenzene	2B

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 10)

98-82-8	cumene	2B
107-06-2	1,2-dichloroethane	2B
1634-04-4	tert-butyl methyl ether	3
· NTP (National Toxicology Program)		
106-93-4	1,2-dibromoethane	R
91-20-3	naphthalene	R
71-43-2	benzene	K
98-82-8	cumene	R
107-06-2	1,2-dichloroethane	R
· OSHA-Ca (Occupational Safety & Health Administration)		
71-43-2	benzene	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Not Regulated, De minimus Quantities** -
- **UN-Number**
- **DOT, IMDG, IATA** UN1992

(Contd. on page 12)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 11)

· **UN proper shipping name**
· **DOT**
· **IMDG, IATA**

Flammable liquids, toxic, n.o.s. (Methanol)
FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL)

· **Transport hazard class(es)**

· **DOT**



· **Class**
· **Label**

3 Flammable liquids
3, 6.1

· **IMDG**



· **Class**
· **Label**

3 Flammable liquids
3/6.1

· **IATA**



· **Class**
· **Label**

3 Flammable liquids
3 (6.1)

· **Packing group**

· **DOT, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**
· **Danger code (Kemler):**
· **EMS Number:**
· **Stowage Category**
· **Stowage Code**

Warning: Flammable liquids
336
F-E,S-D
B
SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**
· **Quantity limitations**

On passenger aircraft/rail: 1 L
On cargo aircraft only: 60 L

· **IMDG**

· **Limited quantities (LQ)**

1L

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 12)

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S.
(METHANOL), 3 (6.1), II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara
· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65
· Chemicals known to cause cancer:

106-93-4 1,2-dibromoethane

91-20-3 naphthalene

71-43-2 benzene

100-41-4 ethylbenzene

98-82-8 cumene

107-06-2 1,2-dichloroethane

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

106-93-4 1,2-dibromoethane

71-43-2 benzene

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

106-93-4 1,2-dibromoethane

71-43-2 benzene

108-88-3 toluene

· Carcinogenic categories
· EPA (Environmental Protection Agency)

106-93-4 1,2-dibromoethane

L

95-47-6 o-xylene

I

108-38-3 m-xylene

I

106-42-3 p-xylene

I

91-20-3 naphthalene

C, CBD

(Contd. on page 14)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 13)

71-43-2	benzene	A, K/L
108-88-3	toluene	II
100-41-4	ethylbenzene	D
98-82-8	cumene	D, CBD
107-06-2	1,2-dichloroethane	B2

· TLV (Threshold Limit Value established by ACGIH)

106-93-4	1,2-dibromoethane	A3
95-47-6	o-xylene	A4
108-38-3	m-xylene	A4
106-42-3	p-xylene	A4
91-20-3	naphthalene	A4
71-43-2	benzene	A1
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
107-06-2	1,2-dichloroethane	A4
1634-04-4	tert-butyl methyl ether	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

106-93-4	1,2-dibromoethane
71-43-2	benzene
107-06-2	1,2-dichloroethane

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· **Contact:** regulatory@ultrasci.com

· **Date of preparation / last revision** 03/31/2019 / 1

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 15)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/31/2019

Version Number 2

Reviewed on 03/31/2019

Trade name: GRO Standard (1X1 mL)

(Contd. of page 14)

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1A: Carcinogenicity – Category 1A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

· * **Data compared to the previous version altered.**

US