

Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

1 Identification

· Product identifier

· Trade name: Benzene-d6 Standard (1X1 mL)

· Part number: STS-100-1

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1A H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

STOT SE 1 H370 Causes damage to organs.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS06

GHS08

· Signal word Danger

(Contd. on page 2)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 1)

· Hazard-determining components of labeling:

methanol

benzene-d6

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic if inhaled.

May cause genetic defects.

May cause cancer.

Causes damage to organs.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

· **vPvB**: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|-------------------------|------------|---------|
| 67-56-1 | methanol | 99.747% |
| 1076-43-3 | benzene-d6 | 0.253% |

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| · PAC-1: | | | |
|-----------|------------|-----------|--|
| 67-56-1 | methanol | 530 ppm | |
| 1076-43-3 | benzene-d6 | 52 ppm | |
| · PAC-2: | | | |
| 67-56-1 | methanol | 2,100 ppm | |
| 1076-43-3 | benzene-d6 | 800 ppm | |
| PAC-3: | | | |
| | methanol | 7200* ppm | |
| 1076-43-3 | benzene-d6 | 4000* ppm | |

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 4)

· Control parameters

| · Components with limit values that require monitoring at the workplace: | | | | |
|--|--|--|--|--|
| 67-56-1 methanol | | | | |
| PEL | Long-term value: 260 mg/m³, 200 ppm | | | |
| REL | Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin | | | |
| TLV | Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI | | | |

· Ingredients with biological limit values:

67-56-1 methanol

BEI 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

(Contd. on page 6)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

· Eye protection:

(Contd. of page 5)



Tightly sealed goggles

| 9 Physical and chemical properties | | |
|---|--|--|
| Information on basic physical and chemical properties | | |
| · General Information | | |
| · Appearance: | | |
| Form: | Fluid | |
| Color: | Colorless | |
| Odor: | Alcohol-like | |
| · Odor threshold: | Not determined. | |
| · pH-value: | Not determined. | |
| · Change in condition | | |
| Melting point/Melting range: | -98 °C (-144.4 °F) | |
| Boiling point/Boiling range: | 64.7 °C (148.5 °F) | |
| · Flash point: | 9 °C (48.2 °F) | |
| · Flammability (solid, gaseous): | Not applicable. | |
| · Ignition temperature: | 455 °C (851 °F) | |
| · Decomposition temperature: | Not determined. | |
| · Auto igniting: | Product is not selfigniting. | |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. | |
| · Explosion limits: | | |
| Lower: | 5.5 Vol % | |
| Upper: | 44 Vol % | |
| · Vapor pressure at 20 °C (68 °F): | 100 hPa (75 mm Hg) | |
| · Density at 20 °C (68 °F): | 0.80038 g/cm ³ (6.67917 lbs/gal) | |
| · Relative density | Not determined. | |
| · Vapor density | Not determined. | |
| · Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| Water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octanol/wate | er): Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |

(Contd. on page 7)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 6)

Solvent content:
Organic solvents: 100.0 %
VOC content: 100.00 %

800.4 g/l / 6.68 lb/gal

Solids content: 0.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| l | · LD/LC50 values that are relevant for classification: | | | | | |
|---|--|----------|--------------|--|--|--|
| | ATE (Acute Toxicity Estimate) | | | | | |
| | Oral | LD50 | 1,978 mg/kg | | | |
| | Dermal | LD50 | 19,778 mg/kg | | | |
| ١ | Inhalative | LC50/4 h | 2.96 mg/L | | | |

67-56-1 methanol

| Oral | LD50 | 5,628 mg/kg (rat) |
|--------|------|-----------------------|
| Dermal | LD50 | 15,800 mg/kg (rabbit) |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Harmful

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 8)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Not Regulated, De minimus Quantities
- · UN-Number
- · DOT, IMDG, IATA UN1230
- · UN proper shipping name
- DOT Methanol solution
 IMDG, IATA METHANOL solution
- · Transport hazard class(es)
- · DOT





Class 3 Flammable liquids

(Contd. on page 9)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 8) 3, 6.1 ·Label · IMDG · Class 3 Flammable liquids ·Label 3/6.1 ·IATA · Class 3 Flammable liquids ·Label 3(6.1)· Packing group · DOT, IMDG, IATA Π · Environmental hazards: Not applicable. Warning: Flammable liquids · Special precautions for user · Danger code (Kemler): 336 · EMS Number: F-E,S-D · Stowage Category В · Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2

15 Regulatory information

· UN "Model Regulation":

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1230 METHANOL SOLUTION, 3 (6.1), II

- ·Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 10)



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 9)

· Section 313 (Specific toxic chemical listings):

67-56-1 methanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· TSCA new (21st Century Act): (Substances not listed)

1076-43-3 benzene-d6

· Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/31/2019 / 2

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances



Printing date 03/31/2019 Version Number 3 Reviewed on 03/31/2019

Trade name: Benzene-d6 Standard (1X1 mL)

(Contd. of page 10)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Muta. 1A: Germ cell mutagenicity - Category 1A

Carc. 1A: Carcinogenicity - Category 1A

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

* Data compared to the previous version altered.

US ·