

Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: EPH Aliphatic Hydrocarbon Standard

· Part number: SWA-310-1

- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: ULTRA Scientific, inc.

250 Smith Street

North Kingstown, RI 02852

USA

· Information department:

Telephone: (401) 294-9400

Fax: (401) 295-2300

E-mail: regulatory@ultrasci.com · Emergency telephone number:

US: (800) 424-9300

Outside US: (703) 527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child. Repr. 2

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

(Contd. of page 1)

· Hazard-determining components of labeling:

n-hexane

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

110-54-3 n-hexane

99.09%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

 \cdot Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

Duotootiv	e Action Criteria for Chemicals	(Contd. of page 3)
· PAC-1:	e Action Criteria for Chemicais	
110-54-3	n-hexane	260 ppm
124-18-5	decane	6.6 ppm
112-40-3	dodecane	1.7 ppm
544-76-3	Cetane	35 mg/m3
111-65-9	octane	230 ppm
· PAC-2:		
110-54-3	n-hexane	2900* ppm
124-18-5	decane	73 ppm
112-40-3	dodecane	18 ppm
544-76-3	Cetane	380 mg/m3
111-65-9	octane	385 ppm
· PAC-3:		·
110-54-3	n-hexane	8600** ppm
124-18-5	decane	440 ppm
112-40-3	dodecane	110 ppm
544-76-3	Cetane	2,800 mg/m3
111-65-9	octane	5000** ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:
110-54-3 n-hexane

	Long-term value: 1800 mg/m³, 500 ppm
REL.	Long-term value: 180 mg/m³, 50 ppm

(Contd. on page 5)



Version Number 1 Reviewed on 03/11/2017 Printing date 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

(Contd. of page 4)

TLV Long-term value: 176 mg/m³, 50 ppm Skin; BEI

· Ingredients with biological limit values:

110-54-3 n-hexane

BEI 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2.5-Hexanedione without hydrolysis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

(Contd. on page 6)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

	(Contd. of page
Color:	Colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	05.00 (100.00)
Melting point/Melting range: Boiling point/Boiling range:	-95 °C (-139 °F) 69 °C (156 °F)
0 1 0 0	• • •
· Flash point:	-22 °C (-8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor
	mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.4 Vol %
· Vapor pressure at 20 °C (68 °F):	110 hPa (83 mm Hg)
· Density at 20 °C (68 °F):	0.7 g/cm ³ (5.842 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	0.1 . //
Water at 20 °C (68 °F):	0.1 g/l
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	00.44
Organic solvents:	99.4 %
VOC content:	99.4 % 993.9 g/l / 8.29 lb/gl
G. 11.	
Solids content: Other information	0.2 % No further relevant information available.
Other information	TWO TUTTION TOTOVAIRE IIITOTIIIALION AVAITAUTE.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 va	lues that are	relevant for	classification:
--------------	---------------	--------------	-----------------

110-54-3 n-hexane

Oral LD50 5000 mg/kg (rat)
Dermal LD50 3000 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

uc



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

(Contd. of page 7)

13 Disposal considerations

- $\cdot \ Waste \ treatment \ methods$
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

4 Transport information	
· UN-Number	
· DOT, IMDG, IATA	UN1993
· UN proper shipping name	
·DOT	Flammable liquids, n.o.s. (Hexanes)
· IMDG	FLAMMABLE LIQUID, N.O.S. (HEXANES, OCTANES),
,,	MARINE POLLUTANT
· IATA	FLAMMABLE LIQUID, N.O.S. (HEXANES)
· Transport hazard class(es)	
· DOT	
11 AMAAII 1 100107	
· Class	3 Flammable liquids
· Label	3
· IMDG	
W W	
· Class	3 Flammable liquids
· Label	3
· IATA	

· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: octane
0	hexane
· Marine pollutant:	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids

(Contd. on page 9)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

(Contd. of page 8) · Danger code (Kemler): 33 · EMS Number: F-E,S-E · Stowage Category В · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT On passenger aircraft/rail: 5 L · Quantity limitations On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 1L Code: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN 1993 FLAMMABLE LIQUIDS, N.O.S. (HEXANES), 3, II,

ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· UN "Model Regulation":

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

110-54-3 n-hexane

· TSCA (Toxic Substances Control Act):

110-54-3 n-hexane

629-94-7 heneicosane

124-18-5 decane

112-40-3 dodecane

544-76-3 Cetane

111-65-9 octane

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

(Contd. of page 9)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

110-54-3 n-hexane

II

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

n-hexane

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

(Contd. on page 11)



Printing date 03/11/2017 Version Number 1 Reviewed on 03/11/2017

Trade name: EPH Aliphatic Hydrocarbon Standard

(Contd. of page 10)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/11/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. $\tilde{2}$: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

US ·