

Printing date 23.03.2025 Revision: 23.03.2025

### 1 Identification

· Product identifier

· Trade name: Calibration Standard (1X1 mL)

· Part number: US-205-1

· Relevant identified uses of the substance or mixture and uses advised against

Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Agilent Technologies Australia Pty Ltd

679 Springvale Road

Mulgrave

Victoria 3170, Australia

· Further information obtainable from:

Telephone: 1800 802 402

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: +(61) - 290372994

## 2 Hazard(s) Identification

· Classification of the substance or mixture



health hazard

Carcinogenicity – Category 1A H350 May cause cancer.

Specific target organ toxicity (repeated exposure) – H373 May cause damage to organs through prolonged or repeated exposure.



Skin corrosion/irritation – Category 2

H315 Causes skin irritation.

Eye damage/irritation – Category 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) – Category H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

dichloromethane (>60 %)

7,12-dimethylbenz[a]anthracene (<10 %)

4-aminobiphenyl (<10 %)

(Contd. on page 2)



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 1)

#### · Hazard statements

P101

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H350 May cause cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P260 Do not breathe vapours.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. P271

Obtain special instructions before use. P201

Do not handle until all safety precautions have been read and understood. P202

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Call a POISON CENTER/doctor if you feel unwell. P312 P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell. P314 IF ON SKIN: Wash with plenty of water. P302+P352

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

## 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

	dichloromethane	>60
	Carcinogenicity – Category 2, H351; Specific target organ toxicity (repeated exposure) – Category 2, H373; Skin corrosion/irritation – Category 2, H315; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H335	
57-97-6	7,12-dimethylbenz[a]anthracene	<10
	Carcinogenicity – Category 1A, H350; ( Acute toxicity - oral – Category 4, H302	
82-68-8	quintozene (ISO)	<109
	Respiratory sensitisation – Category 1, H334;  Acute toxicity - oral – Category 4, H302; Skin sensitisation – Category 1, H317	



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

·SVHC

92-67-1 4-aminobiphenyl

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **4 First Aid Measures**

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **5 Fire Fighting Measures**

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Protective equipment: Mouth respiratory protective device.

#### **6 Accidental Release Measures**

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 3)

Open and handle receptacle with care.

Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

#### · Ingredients with limit values that require monitoring at the workplace:

#### 75-09-2 dichloromethane

WES Long-term value: 174 mg/m³, 50 ppm

#### 82-68-8 quintozene (ISO)

WES Long-term value: 0.5 mg/m<sup>3</sup>

Sen

#### 92-67-1 4-aminobiphenyl

WES Long-term value: (P) ppm Sk

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

### Respiratory protection:

When used as intended with Agilent instruments the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device equipment with appropriate organic or acid gas cartridge.

#### Protection of hands:

Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13mil thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

### · Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

### · Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: > 4 hours

(Contd. on page 5)



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 4)

• Eye protection: Safety glasses



Tightly sealed goggles

## 9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Like chlorine
Odour threshold: Not determined.
pH-value: Not determined.

· Change in condition

• Melting point/freezing point: -95.1 °C • Initial boiling point and boiling range: 40 °C

Flash point: Not applicable.
 Flammability (solid, gas): Not applicable.
 Auto-ignition temperature: 605 °C

• **Decomposition temperature:** Not determined.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: 13 Vol %
Upper: 22 Vol %
Vapour pressure at 20 °C: 360 hPa
Density at 20 °C: 1.3 g/cm³
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not determined.

· Solubility in / Miscibility with

• water at **20** °C: 20 g/l

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

• Dynamic at 20 °C: 0.43 mPas • Kinematic: Not determined.

· Solvent content:

 · Organic solvents:
 99.1 %

 · VOC (EC)
 99.10 %

 · Solids content:
 0.0 %

• Other information No further relevant information available.

## 10 Stability and Reactivity

· Reactivity No further relevant information available.

(Contd. on page 6)



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 5)

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:				
75-09-2 dichloromethane					
Oral	LD50	1,600 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rat)			
Inhalative	LC50/4 h	88 mg/L (rat)			
57-97-6 7,	57-97-6 7,12-dimethylbenz[a]anthracene				
Oral LD50 327 mg/kg (rat)					
82-68-8 qı	82-68-8 quintozene (ISO)				
Oral	LD50	1,100 mg/kg (rat)			
92-67-1 4-	92-67-1 4-aminobiphenyl				
Oral	LD50	500 mg/kg (rat)			

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eve damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity May cause cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## 12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

· Other adverse effects No further relevant information available.

(Contd. of page 6)

## 13 Disposal considerations

- · Waste treatment methods
- ·Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

4 4 7					
4.	<b>Frans</b>	nort	mit	ormai	TOT

· Not Regulated, De minimus Quantities			
	-		
· UN-Number			
· ADG, IMDG, IATA	UN1593		
· UN proper shipping name			
· ADG	1593 DICHLOROMETHANE		
· IMDG, IATA	DICHLOROMETHANE		
· Transport hazard class(es)			
· ADG, IMDG, IATA			
· Class	6.1 Toxic substances.		
· Label	6.1		
· Packing group · ADG, IMDG, IATA	III		
· Environmental hazards:	Not applicable.		
· Special precautions for user	Warning: Toxic substances.		
· Hazard identification number (Kemler code):	60		
EMS Number:	F-A,S-A		
· Segregation groups	(SGG10) Liquid halogenated hydrocarbons		
· Stowage Category	A		
· Transport in bulk according to Annex II of Mar	pol		
and the IBC Code	Not applicable.		
· Transport/Additional information:			
· ADG			
· Limited quantities (LQ)	5L		
· Excepted quantities (EQ)	Code: E1		
	Maximum net quantity per inner packaging: 30 ml		
	Maximum net quantity per outer packaging: 1000 ml		
	(Contd. on pag		



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

Transport category
Tunnel restriction code
E

IMDG
Limited quantities (LQ)
Excepted quantities (EQ)
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":
UN 1593 DICHLOROMETHANE, 6.1, III

## 15 Regulatory information

 $\cdot \ Safety, health \ and \ environmental \ regulations/legislation \ specific \ for \ the \ substance \ or \ mixture$ 

· Australi	an Inventory of Industrial Chemicals	
75-09-2	dichloromethane	
90-13-1	1-chloronaphthalene	
98-86-2	acetophenone	
·Standar	d for the Uniform Scheduling of Medicines and Poisons	
75-09-2	dichloromethane	S5
82-68-8	quintozene (ISO)	S5
98-86-2	acetophenone	S5
	a: Priority Existing Chemicals	·

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Other regulations, limitations and prohibitive regulations

ı	· Substances of very high concern (SVHC) according to REACH, Article 57						
ı	Substances of very light concern (5 vire) according to REACH, Article 37						
I	92-67-1 4-aminobiphenyl						

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

### · Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 9)



Printing date 23.03.2025 Revision: 23.03.2025

Trade name: Calibration Standard (1X1 mL)

(Contd. of page 8)

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H350 May cause cancer.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Contact:

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Acute toxicity - oral - Category 4: Acute toxicity - Category 4

Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2

Eye damage/irritation - Category 2A: Serious eye damage/eye irritation - Category 2A

Respiratory sensitisation - Category 1: Respiratory sensitisation - Category 1

Skin sensitisation – Category 1: Skin sensitisation – Category 1

Carcinogenicity - Category 1A: Carcinogenicity - Category 1A

Carcinogenicity - Category 2: Carcinogenicity - Category 2

Specific target organ toxicity (single exposure) - Category 3: Specific target organ toxicity (single exposure) - Category 3

Specific target organ toxicity (repeated exposure) - Category 2: Specific target organ toxicity (repeated exposure) - Category 2

\* Data compared to the previous version altered.

AII