

# Safety Data Sheet

acc. to OSHA HCS

Revision date: 01/08/2025

## 1 Identification

· **Product identifier**

· **Product Name: Calibration Standard (1X1 mL)**

· **Part no. :** US-255-1

· **Restrictions**

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/ product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/ product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

· **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Agilent Technologies, Inc.  
5301 Stevens Creek Blvd.  
Santa Clara, CA 95051 USA

· **Information department:**

Telephone: 800-227-9770  
e-mail: pdl-msds\_author@agilent.com

· **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

## 2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS06 Skull and crossbones

Acute Toxicity - Inhalation 3

H331 Toxic if inhaled.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1A

H350 May cause cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 1)


**GHS07**

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3

H335 May cause respiratory irritation.

**Label elements**
**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**

**GHS06**
**GHS07**
**GHS08**
**Signal word** Danger

**Hazard-determining components of labeling:**

dichloromethane

2,4,5-trimethylaniline

4,4'-oxydianiline and its salts

2-methoxyaniline

4-methyl-m-phenylene diamine

**Hazard statements**

H331 Toxic if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 2)

- P302+P352 If on skin: Wash with plenty of water.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### \* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

75-09-2	dichloromethane	98.1904%
60-09-3	4-aminoazobenzene	0.1508%
90-04-0	2-methoxyaniline	0.1508%
95-79-4	5-chloro-o-toluidine	0.1508%
95-80-7	4-methyl-m-phenylene diamine	0.1508%
101-14-4	2,2'-dichloro-4,4'-methylenedianiline	0.1508%
101-61-1	N,N,N',N'-tetramethyl-4,4'-methylenedianiline	0.1508%
101-80-4	4,4'-oxydianiline and its salts	0.1508%
110-86-1	pyridine	0.1508%
120-71-8	6-methoxy-m-toluidine	0.1508%
132-32-1	9-ethylcarbazol-3-ylamine	0.1508%
137-17-7	2,4,5-trimethylaniline	0.1508%

US

(Contd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 3)

**4 First-aid measures**

- **Description of first aid measures**
- **General information:**  
 Immediately remove any clothing soiled by the product.  
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
 Remove breathing apparatus only after contaminated clothing have been completely removed.  
 In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**  
 Supply fresh air or oxygen; call for doctor.  
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
 During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to section 13.  
 Ensure adequate ventilation.
- **Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
75-09-2	dichloromethane	200 ppm
60-09-3	4-aminoazobenzene	0.66 mg/m <sup>3</sup>
90-04-0	2-methoxyaniline	1.5 mg/m <sup>3</sup>
95-80-7	4-methyl-m-phenylene diamine	0.015 ppm

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 4)

101-14-4	2,2'-dichloro-4,4'-methylenedianiline	0.03 ppm
101-80-4	4,4'-oxydianiline and its salts	2.2 mg/m <sup>3</sup>
109-06-8	2-methylpyridine	5 ppm
110-86-1	pyridine	3 ppm

**· PAC-2:**

75-09-2	dichloromethane	560 ppm
60-09-3	4-aminoazobenzene	7.2 mg/m <sup>3</sup>
90-04-0	2-methoxyaniline	8.3 mg/m <sup>3</sup>
95-80-7	4-methyl-m-phenylene diamine	3.3 ppm
101-14-4	2,2'-dichloro-4,4'-methylenedianiline	10 mg/m <sup>3</sup>
101-80-4	4,4'-oxydianiline and its salts	24 mg/m <sup>3</sup>
109-06-8	2-methylpyridine	7.7 ppm
110-86-1	pyridine	19 ppm

**· PAC-3:**

75-09-2	dichloromethane	6,900 ppm
60-09-3	4-aminoazobenzene	43 mg/m <sup>3</sup>
90-04-0	2-methoxyaniline	50 mg/m <sup>3</sup>
95-80-7	4-methyl-m-phenylene diamine	20 ppm
101-14-4	2,2'-dichloro-4,4'-methylenedianiline	230 mg/m <sup>3</sup>
101-80-4	4,4'-oxydianiline and its salts	140 mg/m <sup>3</sup>
109-06-8	2-methylpyridine	46 ppm
110-86-1	pyridine	3600* ppm

### 7 Handling and storage

**· Handling:**
**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:** Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

**· Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 5)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**75-09-2 dichloromethane**

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 50 ppm BEI, A3

**90-04-0 2-methoxyaniline**

PEL	Long-term value: 0.5 mg/m <sup>3</sup> Skin
REL	Long-term value: 0.5 mg/m <sup>3</sup> Skin; See Pocket Guide App. A
TLV	Long-term value: 0.5 mg/m <sup>3</sup> Skin; A3, BEI-M

**95-80-7 4-methyl-m-phenylene diamine**

REL	(all isomers); See Pocket Guide App. A
WEEL	Long-term value: 0.005 ppm Skin

**101-14-4 2,2'-dichloro-4,4'-methylenedianiline**

REL	Long-term value: 0.003 mg/m <sup>3</sup> Skin; See Pocket Guide App. A
TLV	Long-term value: 0.01 * ppm Skin; BEI;*inh. fraction and vapor, A2

**110-86-1 pyridine**

PEL	Long-term value: 15 mg/m <sup>3</sup> , 5 ppm
REL	Long-term value: 15 mg/m <sup>3</sup> , 5 ppm
TLV	Long-term value: 1 ppm A3

- **Ingredients with biological limit values:**

**75-09-2 dichloromethane**

BEI	0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)
-----	---

**90-04-0 2-methoxyaniline**

BEI	1.5 % of hemoglobin Medium: blood Time: during or end of shift Parameter: Methemoglobin (background, nonspecific, semi-quantitative)
-----	---

(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 6)

**101-14-4 2,2'-dichloro-4,4'-methylenedianiline**

BEI	- Medium: urine Time: end of shift Parameter: Total MBOCA with hydrolysis (nonquantitative)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness  
 For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour  
 For direct contact with the chemical: butyl rubber: >4 hours

· **Eye protection:**

Safety glasses



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Fluid
<b>Color:</b>	Colorless
<b>Odor:</b>	Like chlorine
<b>Odor threshold:</b>	Not determined.

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 7)

· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	-95.1 °C (-139.2 °F)
<b>Boiling point/Boiling range:</b>	40 °C (104 °F)
· <b>Flash point:</b>	Not applicable.
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Auto igniting:</b>	605 °C (1,121 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	13 Vol %
<b>Upper:</b>	22 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	360 hPa (270 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.3 g/cm <sup>3</sup> (10.8485 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with</b>	
<b>Water at 20 °C (68 °F):</b>	20 g/l
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C (68 °F):</b>	0.43 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	98.3 %
<b>VOC content:</b>	0.15 %
	1.5 g/l / 0.01 lb/gal
<b>Solids content:</b>	1.4 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 8)

 · **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

 · **Information on toxicological effects**

 · **Acute toxicity:**

 · **LD/LC50 values that are relevant for classification:**
**ATE (Acute Toxicity Estimate)**

Oral	LD50	20,801 mg/kg
Dermal	LD50	66,313 mg/kg
Inhalative	LC50/4 h	3.28 mg/L

**75-09-2 dichloromethane**

Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/L (rat)

**90-04-0 2-methoxyaniline**

Oral	LD50	2,000 mg/kg (rat)
------	------	-------------------

**95-79-4 5-chloro-o-toluidine**

Oral	LD50	464 mg/kg (rat)
------	------	-----------------

**101-14-4 2,2'-dichloro-4,4'-methylenedianiline**

Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

**101-61-1 N,N,N',N'-tetramethyl-4,4'-methylenedianiline**

Oral	LD50	3,160 mg/kg (mouse)
------	------	---------------------

**101-80-4 4,4'-oxydianiline and its salts**

Oral	LD50	725 mg/kg (rat)
------	------	-----------------

**110-86-1 pyridine**

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	1,121 mg/kg (rabbit)

**120-71-8 6-methoxy-m-toluidine**

Oral	LD50	1,450 mg/kg (rat)
------	------	-------------------

 · **Primary irritant effect:**

 · **on the skin:** Irritant to skin and mucous membranes.

 · **on the eye:** Irritating effect.

 · **Sensitization:** Sensitization possible through skin contact.

 · **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Irritant

The product can cause inheritable damage.

 · **Carcinogenic categories**

 · **IARC (International Agency for Research on Cancer)**

75-09-2 dichloromethane

2A

(Contd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 9)

60-09-3	4-aminoazobenzene	2B
90-04-0	2-methoxyaniline	2A
95-79-4	5-chloro-o-toluidine	3
95-80-7	4-methyl-m-phenylene diamine	2B
101-14-4	2,2'-dichloro-4,4'-methylenedianiline	1
101-61-1	N,N,N',N'-tetramethyl-4,4'-methylenedianiline	2B
101-80-4	4,4'-oxydianiline and its salts	2B
110-86-1	pyridine	2B
120-71-8	6-methoxy-m-toluidine	2B
137-17-7	2,4,5-trimethylaniline	3

**· NTP (National Toxicology Program)**

75-09-2	dichloromethane	R
90-04-0	2-methoxyaniline	R
95-80-7	4-methyl-m-phenylene diamine	R
101-14-4	2,2'-dichloro-4,4'-methylenedianiline	R
101-61-1	N,N,N',N'-tetramethyl-4,4'-methylenedianiline	R
101-80-4	4,4'-oxydianiline and its salts	R
120-71-8	6-methoxy-m-toluidine	R

**· OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2	dichloromethane	
---------	-----------------	--

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 3 (Self-assessment): extremely hazardous for water  
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
 Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 10)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>Not Regulated, De minimis Quantities</b>	-
· <b>UN-Number</b>	
· <b>DOT, IMDG, IATA</b>	UN1593
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Dichloromethane
· <b>IMDG, IATA</b>	DICHLOROMETHANE
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	6.1 Toxic substances
· <b>Label</b>	6.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	6.1 Toxic substances
· <b>Label</b>	6.1
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Warning: Toxic substances
· <b>Hazard identification number (Kemler code):</b>	60
· <b>EMS Number:</b>	F-A,S-A
· <b>Segregation groups</b>	(SGG10) Liquid halogenated hydrocarbons
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L

(Contd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 11)

· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1593 DICHLOROMETHANE, 6.1, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

75-09-2	dichloromethane
60-09-3	4-aminoazobenzene
90-04-0	2-methoxyaniline
95-80-7	4-methyl-m-phenylene diamine
101-14-4	2,2'-dichloro-4,4'-methylenedianiline
101-61-1	N,N,N',N'-tetramethyl-4,4'-methylenedianiline
101-80-4	4,4'-oxydianiline and its salts
109-06-8	2-methylpyridine
110-86-1	pyridine
120-71-8	6-methoxy-m-toluidine

· **TSCA (Toxic Substances Control Act):**

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/ product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/ product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

75-09-2	dichloromethane	ACTIVE
60-09-3	4-aminoazobenzene	ACTIVE
90-04-0	2-methoxyaniline	ACTIVE
95-79-4	5-chloro-o-toluidine	ACTIVE
95-80-7	4-methyl-m-phenylene diamine	ACTIVE
101-14-4	2,2'-dichloro-4,4'-methylenedianiline	ACTIVE

(Contd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 12)

101-61-1	N,N,N',N'-tetramethyl-4,4'-methylenedianiline	ACTIVE
101-80-4	4,4'-oxydianiline and its salts	ACTIVE
109-06-8	2-methylpyridine	ACTIVE
110-86-1	pyridine	ACTIVE
120-71-8	6-methoxy-m-toluidine	ACTIVE
132-32-1	9-ethylcarbazol-3-ylamine	ACTIVE

**· Hazardous Air Pollutants**

75-09-2	dichloromethane
90-04-0	2-methoxyaniline
95-80-7	4-methyl-m-phenylene diamine
101-14-4	2,2'-dichloro-4,4'-methylenedianiline

**· Proposition 65**
**· Chemicals known to cause cancer:**

75-09-2	dichloromethane
60-09-3	4-aminoazobenzene
90-04-0	2-methoxyaniline
95-79-4	5-chloro-o-toluidine
95-80-7	4-methyl-m-phenylene diamine
101-14-4	2,2'-dichloro-4,4'-methylenedianiline
101-61-1	N,N,N',N'-tetramethyl-4,4'-methylenedianiline
101-80-4	4,4'-oxydianiline and its salts
110-86-1	pyridine
120-71-8	6-methoxy-m-toluidine
137-17-7	2,4,5-trimethylaniline

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**· Carcinogenic categories**
**· EPA (Environmental Protection Agency)**

75-09-2	dichloromethane	L
101-61-1	N,N,N',N'-tetramethyl-4,4'-methylenedianiline	B2

**· TLV (Threshold Limit Value)**

75-09-2	dichloromethane	A3
90-04-0	2-methoxyaniline	A3
101-14-4	2,2'-dichloro-4,4'-methylenedianiline	A2
110-86-1	pyridine	A3

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

75-09-2	dichloromethane
---------	-----------------

(Contd. on page 14)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date: 01/08/2025

Revision date: 01/08/2025

**Product Name: Calibration Standard (1X1 mL)**

(Contd. of page 13)

90-04-0	2-methoxyaniline
95-80-7	4-methyl-m-phenylene diamine
101-14-4	2,2'-dichloro-4,4'-methylenedianiline

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**  
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.  
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- **Contact:**
- **Date of preparation / last revision** 01/08/2025 / 3
- **Abbreviations and acronyms:**  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Acute Toxicity - Inhalation 3: Acute toxicity – Category 3  
 Skin Irritation 2: Skin corrosion/irritation – Category 2  
 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A  
 Sensitization - Skin 1: Skin sensitisation – Category 1  
 Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B  
 Carcinogenicity 1A: Carcinogenicity – Category 1A  
 Toxic to Reproduction 2: Reproductive toxicity – Category 2  
 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3  
 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2
- **\* Data compared to the previous version altered.**