Printing date 30.03.2019

Agilent

Version number 2

Revision: 30.03.2019

1 Identification

- · Product identifier
- · Trade name: Pesticides Calibration Standard (1X1 mL)
- · Part number: US-360-1
- Relevant identified uses of the substance or mixture and uses advised against Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet
- **Manufacturer/Supplier:** Agilent Technologies Australia Pty Ltd 679 Springvale Road Mulgrave Victoria 3170, Australia
- Further information obtainable from: Telephone: 1800 802 402
 e-mail: pdl-msds_author@agilent.com
 Emergency telephone number: CHEMTREC®: +(61) - 290372994

2 Hazard(s) Identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). • Hazard pictograms



Signal word Danger
Hazard statements
Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary statements
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Ground/bond container and receiving equipment.

(Contd. on page 2)

⁻ AU

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

(Contd. of page 1) Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

| 67-64-1 | acetone | 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336 | 99.849% | | | |
|---|---------|---|---------|--|--|--|
| • Additional information: For the wording of the listed hazard phrases refer to section 16. | | | | | | |

4 First Aid Measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)



Printing date 30.03.2019

Version number 2

Printing date 30.03.2019

Version number 2

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

(Contd. of page 2)

5 Fire Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.



AU

Version number 2

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

(Contd. of page 3)

| For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Tightly sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties General Information | 0 | dients with limit values that require monitoring at the workplace: |
|--|-----------|--|
| WES Long-term value: 1185 mg/m³, 500 ppm WES Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm Additional information: The lists valid during the making were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Protection of hands: Although not recommended for constant contact with the chemicals or for clean | 67-64 | -1 acetone |
| WES Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm Additional information: The lists valid during the making were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes and skin. Reprintory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protection needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1ln. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber: 1 hour For normal use: | NES | Short-term value: 2375 mg/m ³ , 1000 ppm |
| Long-term value: 1185 mg/m³, 500 ppm Additional information: The lists valid during the making were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protectin needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical; butyl rubber gloves are recommended 12-15 mil thickness For normal use: nitrile rubber, 11-13 mil thickness For ourset in the chemical; butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber; 1 hour For origet contact with the chemical; butyl rubber; > 4 hours <th></th> <th>Long-term value: 1185 mg/m³, 500 ppm</th> | | Long-term value: 1185 mg/m ³ , 500 ppm |
| Long-term value: 1185 mg/m³, 500 ppm Additional information: The lists valid during the making were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protectin needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical; butyl rubber gloves are recommended 12-15 mil thickness For normal use: nitrile rubber, 11-13 mil thickness For ourset in the chemical; butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber; 1 hour For origet contact with the chemical; butyl rubber; > 4 hours <td>WES</td> <td>Short-term value: 2375 mg/m³, 1000 ppm</td> | WES | Short-term value: 2375 mg/m ³ , 1000 ppm |
| Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protecti needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro device equipment with appropriate organic or acid gas cartridge. Protection of hands: Athough not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For direct contact with the chemical: butyl rubber; 12-15 mil thickness For direct contact with the chemical: butyl rubber; > 4 hours Perotection: For direct contact with the chemical: butyl rubber: > 4 hours Experiments Ex | | |
| Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protection exedd. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Prepretion: Tightly sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties General Information | Addit | ional information: The lists valid during the making were used as basis. |
| Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protecti needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness. Protection of gloves For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber; >4 hours Protection: Digthy sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties | Expos | sure controls |
| Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Repiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protection needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber; >4 hours Eye protection: Over the stand of the properties Physical and Chemical Properties | | |
| Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Repiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protection needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For afrect contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Digital and Chemical Properties Information on basic physical and chemical properties General Information | | |
| Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protection eneeded. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For direct contact with the chemical: butyl rubber, 12-15 mil thickness For direct contact with the chemical: butyl rubber: > 4 hours Protection: Protection: Physical and Chemical Properties Physical and Chemical Properties Conceral Information | | |
| Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protecti- needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro- device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber, 11-13 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Oriection: Physical and Chemical Properties Information on basic physical and chemical properties General Information | | |
| Avoid contact with the eyes. Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protecti- needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro- device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber; 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Or Display sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties General Information | | |
| Avoid contact with the eyes and skin. Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protecti- needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent appro- device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For direct contact with the chemical: butyl rubber, 12-15 mil thickness For direct contact with the chemical: butyl rubber; > 4 hours Portection: Postection: Physical and Chemical Properties Information on basic physical and chemical properties General Information | | |
| Respiratory protection: When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protectineedd. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Tightly sealed goggles | | |
| When used as intended with Agilent instruments the use of the product under normal laboratory condition with standard practices does not result in significant airborne exposures and therefore respiratory protectineeded. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber: 1 hour For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Tightly sealed goggles Physical and Chemical Properties General Information | | |
| with standard practices does not result in significant airborne exposures and therefore respiratory protection ended. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Physical and Chemical Properties Information on basic physical and chemical properties | | |
| needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. • Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness • Penetration time of glove material For normal use: nitrile rubber: 1 hour For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: • Eye protection: • Tightly sealed goggles • Information on basic physical and chemical properties • General Information | with s | tandard practices does not result in significant airborne exposures and therefore respiratory protection i |
| Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approdevice equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Dysical and Chemical Properties Information on basic physical and chemical properties General Information | | |
| device equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber: 1 hour For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: | | |
| Protection of hands: Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber, 11-13 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Tightly sealed goggles | | |
| Although not recommended for constant contact with the chemicals or for clean up, nitrile gloves 11-13m thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. • Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness • Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: • Tightly sealed goggles • Information on basic physical and chemical properties • General Information | | |
| thickness are recommended for normal use. The breakthrough time is 1hr. For cleaning a spill where there contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Tightly sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties General Information | | |
| contact of the chemical, butyl rubber gloves are recommended 12-15mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Tightly sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties General Information | | |
| exceeding 4 hrs. Supplier recommendations should be followed. • Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness • Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: • Eye protection: • Tightly sealed goggles • Information on basic physical and chemical properties • General Information | | |
| Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: • Eye protection: Tightly sealed goggles Physical and Chemical Properties • Information on basic physical and chemical properties • General Information | | |
| For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness • Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: • Eye protection: • Tightly sealed goggles • Physical and Chemical Properties • Information on basic physical and chemical properties • General Information | | |
| For direct contact with the chemical: butyl rubber, 12-15 mil thickness • Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: • Tightly sealed goggles Physical and Chemical Properties • Information on basic physical and chemical properties • General Information | Mate | ral of gloves |
| Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours Eye protection: Tightly sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties General Information | | |
| For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: Tightly sealed goggles • Physical and Chemical Properties • Information on basic physical and chemical properties • General Information | | |
| For direct contact with the chemical: butyl rubber: > 4 hours • Eye protection: • Tightly sealed goggles • Physical and Chemical Properties • Information on basic physical and chemical properties • General Information | | |
| Eye protection: Tightly sealed goggles Physical and Chemical Properties Information on basic physical and chemical properties General Information | For no | ormal use: nitrile rubber: 1 hour |
| Tightly sealed goggles Physical and Chemical Properties • Information on basic physical and chemical properties • General Information | For di | rect contact with the chemical: butyl rubber: >4 hours |
| Physical and Chemical Properties · Information on basic physical and chemical properties · General Information | Eye p | rotection: |
| Physical and Chemical Properties Information on basic physical and chemical properties | | |
| Physical and Chemical Properties · Information on basic physical and chemical properties · General Information | \square | |
| · Information on basic physical and chemical properties · General Information | | j Tightly sealed goggles |
| Information on basic physical and chemical properties General Information | | |
| · General Information | | |
| · Information on basic physical and chemical properties · General Information | | |
| · General Information | Phys | ical and Chemical Properties |
| · General Information | Inform | nation on basic physical and chemical properties |
| | | |
| | | |
| Form: Fluid | | |
| Colour: Colourless | | |
| • Odour: Colouress • Odour: Characteristic | | |
| (Contracteristic | ()//// | |



Printing date 30.03.2019

according to WHS Regulations



Printing date 30.03.2019

Version number 2

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

| | (Contd. of page 4 |
|---|---|
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| Change in condition Melting point/freezing point: Initial boiling point and boiling range | -94.7 °C e: 55.8-56.6 °C |
| · Flash point: | -17 °C |
| · Flammability (solid, gas): | Not applicable. |
| · Ignition temperature: | 465 °C |
| · Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: Lower: Upper: | 2.6 Vol % 13 Vol % |
| · Vapour pressure at 20 °C: | 245.3 hPa |
| Density at 20 °C: Relative density Vapour density Evaporation rate | 0.791 g/cm ³ Not determined. Not determined. Not determined. |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: Dynamic at 20 °C: Kinematic: | 32 mPas Not determined. |
| · Solvent content: Organic solvents: VOC (EC) | 99.8 % 99.85 % |
| Solids content: • Other information | 0.1 % No further relevant information available. |

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

according to WHS Regulations

Printing date 30.03.2019

Version number 2

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

[•] Information on toxicological effects

· Acute toxicity

| | The toxicity | | | | |
|-------------------------|---|--|--|--|--|
| · LD/LC50 | · LD/LC50 values relevant for classification: | | | | |
| 67-64-1 ac | 67-64-1 acetone | | | | |
| Oral | Oral LD50 5,800 mg/kg (rat) | | | | |
| Dermal | Dermal LD50 20,000 mg/kg (rabbit) | | | | |
| 15972-60- | 15972-60-8 alachlor (ISO) | | | | |
| Oral | Oral LD50 930 mg/kg (rat) | | | | |
| Dermal | Dermal LD50 3,500 mg/kg (rabbit) | | | | |
| 21087-64- | 21087-64-9 metribuzin (ISO) | | | | |
| Oral | Oral LD50 1,090 mg/kg (rat) | | | | |
| Dermal | Dermal LD50 >20,000 mg/kg (rabbit) | | | | |
| Inhalative | Inhalative LC50/4 h >860 mg/L (rat) | | | | |
| | Primary irritant effect: | | | | |
| ¹ Skin corre | · Skin corrosion/irritation No irritant effect. | | | | |

· Serious eye damage/irritation Irritating effect.

• Respiratory or skin sensitisation No sensitising effects known.

• Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)

AI



according to WHS Regulations

Printing date 30.03.2019

Version number 2

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

(Contd. of page 6)

AU

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

| Not Regulated, De minimus Quantities | <u>-</u> |
|--|--|
| UN-Number | |
| ADG, IMDG, IATA | UN1090 |
| UN proper shipping name | |
| ADG | 1090 ACETONE solution |
| IMDG, IATA | ACETONE solution |
| Transport hazard class(es) | |
| ADG, IMDG, IATA | |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| Packing group | |
| ADG, IMDG, IATA | II |
| Environmental hazards: | Not applicable. |
| Special precautions for user | Warning: Flammable liquids. |
| Danger code (Kemler): | 33 |
| EMS Number: | F-E,S-D |
| Stowage Category | В |
| Transport in bulk according to Annex I | |
| and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| ADG | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| Transport category | 2 |
| Tunnel restriction code | D/E |



according to WHS Regulations

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

(Contd. of page 7)

·IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN 1090 ACETONE SOLUTION, 3, II

· UN "Model Regulation":

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

| · Australian Inventory of Chemical Substances | | | |
|---|--|--------|--|
| 67-64-1 | acetone | | |
| 27314-13-2 | norflurazon | | |
| 15972-60-8 | alachlor (ISO) | | |
| 957-51-7 | diphenamid (ISO) | | |
| 1114-71-2 | pebulate (ISO) | | |
| 60168-88-9 | fenarimol (ISO) | | |
| 1929-77-7 | S-propyl dipropylthiocarbamate | | |
| 21087-64-9 | metribuzin (ISO) | | |
| 43121-43-3 | triadimefon (ISO) | | |
| 122-34-9 | simazine (ISO) | | |
| 1014-70-6 | 2,4-bis(ethylamino)-6-methylthio-1,3,5-triazine | | |
| 7287-19-6 | prometryn | | |
| · Standard fo | or the Uniform Scheduling of Medicines and Poisons | | |
| 67-64-1 | acetone | S5 | |
| 15972-60-8 | alachlor (ISO) | S7 | |
| 957-51-7 | diphenamid (ISO) | S5 | |
| 1114-71-2 | pebulate (ISO) | S6 | |
| 60168-88-9 | fenarimol (ISO) | S5 | |
| 1929-77-7 | S-propyl dipropylthiocarbamate | S5 | |
| 43121-43-3 | triadimefon (ISO) | S5, S6 | |
| 7287-19-6 | prometryn | S5 | |

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $50{,}000\ t$

 \cdot Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

ΔT



Printing date 30.03.2019

Version number 2

Ι

Printing date 30.03.2019

Version number 2

Revision: 30.03.2019

Trade name: Pesticides Calibration Standard (1X1 mL)

(Contd. of page 8)

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Relevant phrases

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

