Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

1 Identification · Product identifier · Trade name: Dibutylamine · Part number: WRK-1800 · CAS Number: 111-92-2 · EC number: 203-921-8 · Index number: 612-049-00-0 · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA · Information department: Telephone: 800-227-9770 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: 1-800-424-9300 2 Hazard(s) identification · Classification of the substance or mixture GHS02 Flame Flam. Liq. 3 H226 Flammable liquid and vapor. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. _____ · Label elements • GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning

- Hazard-determining components of labeling: di-n-butylamine
- Hazard statements Flammable liquid and vapor.

(Contd. on page 2)

Version Number 2

Reviewed on 03/25/2019



Trade name: Dibutylamine

Printing date 03/25/2019

	(Contd. of page
Harmful if swallowed, in contact with skin or if inhaled.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Call a poison center/doctor if you feel unwell.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Specific treatment (see on this label).	
Rinse mouth.	
Take off contaminated clothing and wash it before reuse.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Classification system:	
NFPA ratings (scale 0 - 4)	
Health $= 2$	
Fire = 2	
\mathbf{V} Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
HEALTH 2 Health = 2	
Fire 2 Fire = 2	
$\frac{1}{\text{REACTIVITY}[0]} \text{ Reactivity} = 0$	
REACTIVITY 0	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	
Composition/information on ingredients	
Chemical characterization: Substances	
CAS No. Description	
111-92-2 di-n-butylamine	
Identification number(s)	
EC number: 203-921-8	

· Index number: 612-049-00-0

(Contd. on page 3)

US

Reviewed on 03/25/2019

Trade name: Dibutylamine

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately rinse with water.

• After eye contact: Rinse opened eye for several minutes under running water.

- After swallowing: Immediately call a doctor.
- · Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.	
Environmental precautions: Do not allow to enter sewers/ surface or ground water.	
Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
PAC-1:	
	0.45 pj
PAC-2:	
	5 pj
	(Contd. on pa



Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Dibutylamine

(Contd. of page 3)

21 ppm

7 Handling and storage

· Handling:

· **PAC-3**:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-92-2 di-n-butylamine

WEEL Ceiling limit value: 5 ppm

Skin

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

(Contd. on page 5)

US



Version Number 2

Printing date 03/25/2019

⁻

Reviewed on 03/25/2019

Trade name: Dibutylamine

Printing date 03/25/2019

(Contd. of page 4)

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

 Information on basic physical and c General Information 	
Appearance:	
Form:	Fluid
Color:	Colorless
Odor:	Amine-like
Odor threshold:	Not determined.
· pH-value:	Not determined.
• Change in condition	
Melting point/Melting range:	-60 °C (-76 °F)
Boiling point/Boiling range:	159 °C (318.2 °F)
· Flash point:	40 °C (104 °F)
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	260 °C (500 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
• Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	1.9 hPa (1.4 mm Hg)
Density at 20 °C (68 °F):	0.767 g/cm3 (6.40062 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.





Version Number 2

Version Number 2

Reviewed on 03/25/2019

Trade name: Dibutylamine

Printing date 03/25/2019

		(Contd. of page 5
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	50 g/l	
· Partition coefficient (n-octanol/wa	iter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	189 mg/kg (rat)
	LD50	769 mg/kg (rabbit)
Inhalative	LC50/4 h	1.15 mg/L (rat)

111-92-2 di-n-butylamine

Oral	LD50	189 mg/kg (rat)
Dermal		769 mg/kg (rabbit)
Inhalative	LC50/4 h	1.15 mg/L (rat)

Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

Substance is not listed.

·NTP (National Toxicology Program)

Substance is not listed.

(Contd. on page 7)



Version Number 2

Reviewed on 03/25/2019

Trade name: Dibutylamine

Printing date 03/25/2019

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, IMDG, IATA	UN2248	
· UN proper shipping name		
DOT	Di-n-butylamine	
· IMDG, IATA	DI-n-BUTYLAMINE	
• Transport hazard class(es) • DOT		
· Class	8 Corrosive substances	



(Contd. of page 6)

Reviewed on 03/25/2019

Printing date 03/25/2019

Agilent

Version Number 2

	(Contd. of page	
Label	8, 3	
IMDG		
Class	8 Corrosive substances	
Label	8/3	
IATA		
Class	8 Corrosive substances	
Label	8 (3)	
Packing group DOT, IMDG, IATA	II	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Corrosive substances	
Danger code (Kemler):	83	
EMS Number:	8-04	
Stowage Category	А	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 1 L	
	On cargo aircraft only: 30 L	
IMDG		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E2	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
UN "Model Regulation":	UN 2248 DI-N-BUTYLAMINE, 8 (3), II, ENVIRONMENTALLY	
	HAZARDOUS	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

Substance is not listed.

(Contd. on page 9)

US -

Reviewed on 03/25/2019

Printing date 03/25/2019

Version Number 2

Trade name: Dibutylamine

(Contd. of page 8)

· Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

· Proposition 65

· Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

Substance is not listed.

• TLV (Threshold Limit Value established by ACGIH)

Substance is not listed. • NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Date of preparation / last revision 03/25/2019 / 1

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

* * Data compared to the previous version altered.