



280-DS Specifications

Specification Sheet



Redefining Mechanical Qualification, the 280-DS Mechanical Qualification System provides quantitative values for all physical parameters of the dissolution apparatus. It is designed to take quick, accurate measurements at the proper locations as prescribed by current industry regulations.

System

Parameter	Details	Measurement
Ambient Temperature		10 - 35°C
Humidity (non-condensing)		< 75%
Electrical Requirements	USB 2.0 port	
	Voltage	5V
	Current	500 mA
Dimensions and Weight	Instrument Module	
	Height	5 cm
	Width	7.5 cm
	Depth	5 cm
	Weight	0.4 kg
	Vessel Module	
	Max Height	20 cm
	Width	8 cm
	Depth	13 cm
Weight	0.6 kg	

Vessel Module

Parameter	Range	Display Resolution	Tolerance
Vessel Diameter	98-106 mm	0.1 mm	+/- 0.1 mm
Paddle/Basket Height	23-28 mm	0.1 mm	+/- 0.2 mm
Vessel/Shaft Centering	0-2 mm	0.1 mm	+/- 0.2 mm
Vessel Verticality	+/- 1.5°	0.1°	+/- 0.1°
Shaft Verticality	+/- 1.5°	0.1°	+/- 0.1°
Basket/Shaft Wobble	1.5 mm	0.1 mm	+/- 0.1 mm
Shaft Rotational Speed	20-250 RPM	0.1 RPM	+/- 0.2 RPM

Instrument Module

Parameter	Range	Display Resolution	Tolerance
Temperature	30-45°C	0.1°C	+/- 0.1°C
Vibration	Frequency	0-250 Hz	0.1Hz
	Amplitude	10 - 50 mG	1 mG
	Amplitude	>50 - 100 mG	1 mG
Plate Level	+/- 1.5°	0.1°	+/- 0.1°



For more information

Learn more

www.agilent.com/lifesciences/280-DS

**Find an Agilent customer center
in your country**

www.agilent.com/lifesciences/contactus

U.S. and Canada

1-800-227-9770

agilent_inquiries@agilent.com

Europe

info_agilent@agilent.com

Asia Pacific

adinquiry_aplsca@agilent.com

Product specifications and descriptions in this document are subject to change without notice.

© Agilent Technologies, Inc., 2012
Printed in the USA, August 24, 2012
5991-0111EN



Agilent Technologies