## SAFETY DATA SHEET



SFC Caffeine in Methanol Standard, Part Number 5190-0552

## **Section 1. Identification**

#### 1.1 Product identifier

Product name : SFC Caffeine in Methanol Standard, Part Number 5190-0552

Part no. (chemical kit) : 5190-0552

Part no. : SFC Caffeine in Methanol Standard 5190-0552-6

(Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/ 5190-0552-1

mL)

SFC Caffeine in Methanol Standard (10.0 5190-0552-2

μg/mL)

SFC Caffeine in Methanol Standard (50.0 5190-0552-3

μg/mL)

SFC Caffeine in Methanol Standard (100.0 5190-0552-4

μg/mL)

SFC Caffeine in Methanol Standard (200.0 5190-0552-5

μg/mL)

Validation date : 2/1/2024

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagents and Standards for A

: Reagents and Standards for Analytical Chemistry Laboratory Use

SFC Caffeine in Methanol Standard (Solvent 1 X 2 ml

Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL) 1 X 2 ml SFC Caffeine in Methanol Standard (10.0 µg/ 1 X 2 ml

mL)

SFC Caffeine in Methanol Standard (50.0 µg/ 2 X 2 ml

mL)

SFC Caffeine in Methanol Standard (100.0 µg/ 1 X 2 ml

mL)

SFC Caffeine in Methanol Standard (200.0 µg/ 1 X 2 ml

mL)

#### 1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer : Agilent Technologies, Inc.

5301 Stevens Creek Blvd Santa Clara, CA 95051, USA

800-227-9770

#### 1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

## Section 2. Hazards identification

#### 2.1 Classification of the substance or mixture

**OSHA/HCS** status

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This material is considered hazardous by the OSHA

**Date of issue**: 02/01/2024 1/53

Standard (100.0 µg/mL) SFC Caffeine in Methanol Standard (200.0 µg/mL) Hazard Communication Standard (29 CFR 1910.1200). This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

#### Classification of the substance or mixture

# SFC Caffeine in Methanol Standard (Solvent Blank)

H225 FLAMMABLE LIQUIDS - Category 2
H301 ACUTE TOXICITY (oral) - Category 3
H311 ACUTE TOXICITY (dermal) - Category 3
H331 ACUTE TOXICITY (inhalation) - Category 3

H370 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

# SFC Caffeine in Methanol Standard (2.0 µg/mL)

H225 FLAMMABLE LIQUIDS - Category 2
H301 ACUTE TOXICITY (oral) - Category 3
H311 ACUTE TOXICITY (dermal) - Category 3
H331 ACUTE TOXICITY (inhalation) - Category 3

H370 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

# SFC Caffeine in Methanol Standard (10.0 µg/mL)

H225 FLAMMABLE LIQUIDS - Category 2
H301 ACUTE TOXICITY (oral) - Category 3
H311 ACUTE TOXICITY (dermal) - Category 3
H331 ACUTE TOXICITY (inhalation) - Category 3

H370 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

# SFC Caffeine in Methanol Standard (50.0 µg/mL)

H225 FLAMMABLE LIQUIDS - Category 2
H301 ACUTE TOXICITY (oral) - Category 3
H311 ACUTE TOXICITY (dermal) - Category 3
H331 ACUTE TOXICITY (inhalation) - Category 3

H370 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

# SFC Caffeine in Methanol Standard (100.0 µg/mL)

H225 FLAMMABLE LIQUIDS - Category 2
H301 ACUTE TOXICITY (oral) - Category 3
H311 ACUTE TOXICITY (dermal) - Category 3
H331 ACUTE TOXICITY (inhalation) - Category 3

H370 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

# SFC Caffeine in Methanol Standard (200.0 µg/mL)

H225 FLAMMABLE LIQUIDS - Category 2
H301 ACUTE TOXICITY (oral) - Category 3
H311 ACUTE TOXICITY (dermal) - Category 3
H331 ACUTE TOXICITY (inhalation) - Category 3

H370 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

#### 2.2 GHS label elements

**Date of issue**: 02/01/2024 **2/53** 

Hazard	ni	icto	a	ra	m	C
I IUZUI U	м.		ч	·		•

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

: SFC Caffeine in Methanol

Standard (200.0 µg/mL)

: SFC Caffeine in Methanol

Standard (Solvent Blank)

SFC Caffeine in Methanol

Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)































Danger

Danger

Danger

Danger





Signal word

**Hazard statements** 

Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol Standard (10.0 µg/mL) SFC Caffeine in Methanol Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL) SFC Caffeine in Methanol

Danger

Danger

H225 - Highly flammable liquid and vapor.

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled.

H370 - Causes damage to organs. (central nervous system (CNS), optic nerve)

H225 - Highly flammable liquid and vapor.

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled.

H370 - Causes damage to organs.

H225 - Highly flammable liquid and vapor.

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled.

H370 - Causes damage to organs.

H225 - Highly flammable liquid and vapor.

02/01/2024 Date of issue: 3/53

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol

Standard (200.0 µg/mL)

contact with skin or if inhaled.
H370 - Causes damage to organs.

H301 + H311 + H331 - Toxic if swallowed, in

H225 - Highly flammable liquid and vapor.

H301 + H311 + H331 - Toxic if swallowed, in

contact with skin or if inhaled. H370 - Causes damage to organs.

H225 - Highly flammable liquid and vapor.

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled.

H370 - Causes damage to organs.

#### Precautionary statements

**Prevention** 

: SFC Caffeine in Methanol Standard (Solvent Blank)

P280 - Wear protective gloves and protective clothing.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P233 - Keep container tightly closed.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling. P280 - Wear protective gloves and protective

clothing.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P233 - Keep container tightly closed.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves and protective

clothing

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P233 - Keep container tightly closed.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves and protective clothing.

P210 - Keep away from heat, hot surfaces, sparks,

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol

Standard (50.0 µg/mL)

**Date of issue**: 02/01/2024 **4/53** 

open flames and other ignition sources. No

smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P233 - Keep container tightly closed.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves and protective

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P233 - Keep container tightly closed.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling. P280 - Wear protective gloves and protective

clothing.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P233 - Keep container tightly closed.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

P308 + P311 - IF exposed: Call a POISON

CENTER or doctor.

P304 + P340, P311 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor.

P301 + P310 - IF SWALLOWED: Immediately call

a POISON CENTER or doctor.

P361 + P364 - Take off immediately all

contaminated clothing and wash it before reuse. P302 + P312, P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with

plenty of water.

P308 + P311 - IF exposed: Call a POISON

CENTER or doctor.

P304 + P340, P311 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor.

P301 + P310 - IF SWALLOWED: Immediately call

a POISON CENTER or doctor.

P361 + P364 - Take off immediately all

contaminated clothing and wash it before reuse.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol

Standard (200.0 µg/mL)

: SFC Caffeine in Methanol Response Standard (Solvent Blank)

> SFC Caffeine in Methanol Standard (2.0 µg/mL)

02/01/2024 Date of issue: 5/53

SFC Caffeine in Methanol
Standard (10.0 µg/mL)

P302 + P312, P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water.

P308 + P311 - IF exposed: Call a POISON

CENTER or doctor.

P304 + P340, P311 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor.

P301 + P310 - IF SWALLOWED: Immediately call

a POISON CENTER or doctor.

P361 + P364 - Take off immediately all

contaminated clothing and wash it before reuse. P302 + P312, P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with

plenty of water.

SFC Caffeine in Methanol Standard (50.0 µg/mL)

P308 + P311 - IF exposed: Call a POISON

CENTER or doctor.

P304 + P340, P311 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor.

P301 + P310 - IF SWALLOWED: Immediately call

a POISON CENTER or doctor.

P361 + P364 - Take off immediately all

contaminated clothing and wash it before reuse. P302 + P312. P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with

plenty of water.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

P308 + P311 - IF exposed: Call a POISON

CENTER or doctor.

P304 + P340, P311 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor.

P301 + P310 - IF SWALLOWED: Immediately call

a POISON CENTER or doctor.

P361 + P364 - Take off immediately all

contaminated clothing and wash it before reuse. P302 + P312. P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with

plenty of water.

P308 + P311 - IF exposed: Call a POISON

CENTER or doctor.

P304 + P340, P311 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor.

P301 + P310 - IF SWALLOWED: Immediately call

a POISON CENTER or doctor.

P361 + P364 - Take off immediately all

contaminated clothing and wash it before reuse. P302 + P312. P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with

plenty of water.

Storage

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol Standard (10.0 µg/mL) SFC Caffeine in Methanol

Standard (50.0 µg/mL)

SFC Caffeine in Methanol

P403 + P235 - Store in a well-ventilated place.

Keep cool.

P403 + P235 - Store in a well-ventilated place.

P403 + P235 - Store in a well-ventilated place.

Keep cool.

P403 + P235 - Store in a well-ventilated place.

Keep cool.

P403 + P235 - Store in a well-ventilated place.

02/01/2024 Date of issue: 6/53

#### **Disposal**

Standard (100.0 µg/mL) Keep cool.

P403 + P235 - Store in a well-ventilated place. SFC Caffeine in Methanol Standard (200.0 µg/mL)

Keep cool.

SFC Caffeine in Methanol

P501 - Dispose of contents and container in Standard (Solvent Blank) accordance with all local, regional, national and

international regulations.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

P501 - Dispose of contents and container in accordance with all local, regional, national and

international regulations.

SFC Caffeine in Methanol Standard (10.0 µg/mL)

P501 - Dispose of contents and container in accordance with all local, regional, national and

international regulations.

SFC Caffeine in Methanol Standard (50.0 µg/mL)

P501 - Dispose of contents and container in accordance with all local, regional, national and

international regulations.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

P501 - Dispose of contents and container in accordance with all local, regional, national and

international regulations.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

P501 - Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Supplemental label elements

: SFC Caffeine in Methanol Standard (Solvent Blank)

None known.

None known.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

None known.

SFC Caffeine in Methanol Standard (10.0 µg/mL)

None known.

SFC Caffeine in Methanol Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL)

None known.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

None known.

#### 2.3 Other hazards

Hazards not otherwise classified

: SFC Caffeine in Methanol Standard (Solvent Blank)

None known.

SFC Caffeine in Methanol

None known.

Standard (2.0 µg/mL) SFC Caffeine in Methanol

None known.

Standard (10.0 µg/mL) SFC Caffeine in Methanol Standard (50.0 µg/mL)

None known.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

None known.

SFC Caffeine in Methanol

None known.

Standard (200.0 µg/mL)

## Section 3. Composition/information on ingredients

Substance/mixture

SFC Caffeine in Methanol Standard

Substance

(Solvent Blank)

SFC Caffeine in Methanol Standard

Mixture

(2.0 ug/mL)

SFC Caffeine in Methanol Standard

Mixture

Mixture

 $(10.0 \mu g/mL)$ 

SFC Caffeine in Methanol Standard

 $(50.0 \, \mu g/mL)$ 

SFC Caffeine in Methanol Standard

Mixture

 $(100.0 \mu g/mL)$ 

02/01/2024 Date of issue: 7/53

## Section 3. Composition/information on ingredients

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Mixture

Ingredient name	%	CAS number
SFC Caffeine in Methanol Standard (Solvent Blank)		
Methanol	100	67-56-1
SFC Caffeine in Methanol Standard (2.0 μg/mL)		
Methanol	≥90	67-56-1
SFC Caffeine in Methanol Standard (10.0 μg/mL)		
Methanol	≥90	67-56-1
SFC Caffeine in Methanol Standard (50.0 μg/mL)		
Methanol	≥90	67-56-1
SFC Caffeine in Methanol Standard (100.0 μg/mL)		
Methanol	≥90	67-56-1
SFC Caffeine in Methanol Standard (200.0 μg/mL)		
Methanol	≥90	67-56-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### 4.1 Description of necessary first aid measures

Eye contact : SFC Caffeine in Methanol Standard (Solvent Blank)

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

SFC Caffeine in Methanol Standard (10.0 µg/mL)

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison

center or physician.

Date of issue: 02/01/2024 8/53

SFC Caffeine in Methanol Standard (50.0 µg/mL)

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

Inhalation

: SFC Caffeine in Methanol Standard (Solvent Blank)

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or selfcontained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or selfcontained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SFC Caffeine in Methanol

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or selfcontained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get

Standard (10.0 µg/mL)

02/01/2024 Date of issue:

SFC Caffeine in Methanol Standard (50.0 µg/mL)

medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

: SFC Caffeine in Methanol Standard (Solvent Blank) Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at

**Date of issue**: 02/01/2024 **10/53** 

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Ingestion : SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to

Date of issue: 02/01/2024 11/53

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Date of issue:** 02/01/2024 **12/53** 

# 4.2 Most important symptoms/effects, acute and delayed Potential acute health effects

Eye contact

: FC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

No known significant effects or critical hazards.

**Inhalation** 

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

Skin contact

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Ingestion

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with skin.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with skin.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with skin.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with skin.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with skin.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with skin.

Toxic if swallowed. Causes damage to organs following a single exposure if swallowed. Toxic if swallowed. Causes damage to organs following a single exposure if swallowed. Toxic if swallowed. Causes damage to organs following a single exposure if swallowed. Toxic if swallowed. Causes damage to organs following a single exposure if swallowed. Toxic if swallowed. Causes damage to organs following a single exposure if swallowed. Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

#### Over-exposure signs/symptoms

**Date of issue:** 02/01/2024 **13/53** 

## First aid massures

Eye contact

Inhalation

Skin contact

Ingestion

Jt	きしい	IUII	4. Г	11121	aiu	IIIEas	ures

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

SFC Caffeine in Methanol No specific data. Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL) SFC Caffeine in Methanol Standard (200.0 µg/mL)

SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol Standard (10.0 µg/mL) SFC Caffeine in Methanol

Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

No specific data. No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

No specific data.

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: SFC Caffeine in Methanol Standard (Solvent Blank)

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SFC Caffeine in Methanol Standard (10.0 µg/mL)

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Date of issue: 02/01/2024 14/53

**Specific treatments** 

**Protection of first-aiders** 

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

: SFC Caffeine in Methanol Standard (Solvent Blank)

> SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol Standard (10.0 µg/mL) SFC Caffeine in Methanol Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

SFC Caffeine in Methanol

Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

No specific treatment.

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

No antino all la talen investi di di

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

**Date of issue :** 02/01/2024 **15/53** 

SFC Caffeine in Methanol Standard (200.0 µg/mL)

before removing it, or wear gloves.

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

Use dry chemical, CO2, water spray (fog) or foam.

Use dry chemical, CO2, water spray (fog) or foam.

Use dry chemical, CO2, water spray (fog) or foam.

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing media

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

: SFC Caffeine in Methanol Standard (Solvent Blank) Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Date of issue: 02/01/2024 16/53

## Section 5. Fire-fighting measures

SFC Caffeine in Methanol Standard (10.0 µg/mL)

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

SFC Caffeine in Methanol Standard (50.0 µg/mL)

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products

: SFC Caffeine in Methanol Standard (Solvent Blank) Decomposition products may include the following

materials: carbon dioxide carbon monoxide Formaldehyde.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Decomposition products may include the following materials:

carbon dioxide carbon monoxide Formaldehyde.

SFC Caffeine in Methanol Standard (10.0 µg/mL)

Decomposition products may include the following

materials: carbon dioxide carbon monoxide Formaldehyde.

SFC Caffeine in Methanol Standard (50.0 µg/mL)

Decomposition products may include the following

materials: carbon dioxide carbon monoxide Formaldehyde.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Decomposition products may include the following materials:

carbon dioxide carbon monoxide

**Date of issue**: 02/01/2024 **17/53** 

## Section 5. Fire-fighting measures

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Formaldehyde.

Decomposition products may include the following materials:

carbon dioxide carbon monoxide Formaldehyde.

#### **5.3 Advice for firefighters**

Special protective actions for fire-fighters

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Special protective equipment for fire-fighters

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive

Date of issue: 02/01/2024 18/53

## Section 5. Fire-fighting measures

SFC Caffeine in Methanol Standard (100.0 µg/mL)

pressure mode.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive

pressure mode.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive

No action shall be taken involving any personal

pressure mode.

## Section 6. Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist.

**Date of issue**: 02/01/2024 19/53

## Section 6. Accidental release measures

SFC Caffeine in Methanol Standard (200.0 µg/mL)

For emergency responders : SFC Caffeine in Methanol

Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

**6.2 Environmental** precautions

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol

Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Avoid dispersal of spilled material and runoff and

02/01/2024 Date of issue: 20/53

## Section 6. Accidental release measures

Standard (100.0 µg/mL)

contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if watersoluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill

area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if watersoluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of

via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if watersoluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of

via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if watersoluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of

via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if watersoluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an

appropriate waste disposal container. Dispose of

via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if watersoluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an

appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

02/01/2024 Date of issue: 21/53

#### 7.1 Precautions for safe handling

**Protective measures** 

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Put on appropriate personal protective equipment

(see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved

Date of issue: 02/01/2024 22/53

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Advice on general occupational hygiene

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating. lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face

Date of issue: 02/01/2024 23/53

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

7.2 Conditions for safe storage, including any incompatibilities

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Store between the following temperatures: 18 to 25°C (64.4 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Store between the following temperatures: 18 to 25°C (64.4 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Store between the following temperatures: 18 to 25°C (64.4 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from

**Date of issue:** 02/01/2024 **24/53** 

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Store between the following temperatures: 18 to 25°C (64.4 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Store between the following temperatures: 18 to 25°C (64.4 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Store between the following temperatures: 18 to 25°C (64.4 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

**Date of issue:** 02/01/2024 **25/53** 

Recommendations	: SFC Caffeine in Methanol	Industrial applications, Professional applications.
	Standard (Solvent Blank)	
	SFC Caffeine in Methanol	Industrial applications, Professional applications.
	Standard (2.0 µg/mL)	
	SFC Caffeine in Methanol	Industrial applications, Professional applications.
	Standard (10.0 µg/mL)	
	SFC Caffeine in Methanol	Industrial applications, Professional applications.
	Standard (50.0 µg/mL)	
	SFC Caffeine in Methanol	Industrial applications, Professional applications.
	Standard (100.0 µg/mL)	, , , , , , , , , , , , , , , , , , , ,
	SFC Caffeine in Methanol	Industrial applications, Professional applications.
	Standard (200.0 µg/mL)	
The first of the control of the cont	, , , ,	NI. A M. I. I.
Industrial sector specific	: SFC Caffeine in Methanol	Not available.
solutions	Standard (Solvent Blank)	
	SFC Caffeine in Methanol	Not available.
	Standard (2.0 µg/mL)	
	SFC Caffeine in Methanol	Not available.
	Standard (10.0 µg/mL)	
	SFC Caffeine in Methanol	Not available.
	Standard (50.0 μg/mL)	
	SFC Caffeine in Methanol	Not available.
	Standard (100.0 µg/mL)	140t available.
	` . • ,	NI. A M. I. I.
	SFC Caffeine in Methanol	Not available.
	Standard (200.0 µg/mL)	

# Section 8. Exposure controls/personal protection

#### **8.1 Control parameters**

**Occupational exposure limits** 

Ingredient name	Exposure limits			
SFC Caffeine in Methanol Standard (Solvent Blank)				
Methanol	ACGIH TLV (United States, 1/2023).			
	Absorbed through skin.			
	TWA: 200 ppm 8 hours.			
	TWA: 262 mg/m <sup>3</sup> 8 hours.			
	STEL: 250 ppm 15 minutes.			
	STEL: 328 mg/m³ 15 minutes.			
	OSHA PEL 1989 (United States, 3/1989).			
	Absorbed through skin.			
	TWA: 200 ppm 8 hours.			
	TWA: 260 mg/m³ 8 hours.			
	STEL: 250 ppm 15 minutes.			
	STEL: 325 mg/m³ 15 minutes.			
	NIOSH REL (United States, 10/2020).			
	Absorbed through skin.			
	TWA: 200 ppm 10 hours.			
	TWA: 260 mg/m³ 10 hours.			
	STEL: 250 ppm 15 minutes.			
	STEL: 325 mg/m³ 15 minutes.			
	OSHA PEL (United States, 5/2018).			
	TWA: 200 ppm 8 hours.			
	TWA: 260 mg/m³ 8 hours.			
	CAL OSHA PEL (United States, 5/2018).			
	Absorbed through skin.			
	STEL: 325 mg/m³ 15 minutes.			
	STEL: 250 ppm 15 minutes.			
	C: 1000 ppm			
	TWA: 260 mg/m³ 8 hours.			
	TWA: 200 ppm 8 hours.			

**Date of issue :** 02/01/2024 **26/53** 

#### SFC Caffeine in Methanol Standard (2.0 µg/mL)

Methanol

#### ACGIH TLV (United States, 1/2023).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 262 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 328 mg/m³ 15 minutes.

#### OSHA PEL 1989 (United States, 3/1989).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes.

#### NIOSH REL (United States, 10/2020).

#### Absorbed through skin.

TWA: 200 ppm 10 hours. TWA: 260 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes.

#### OSHA PEL (United States, 5/2018).

TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours.

#### CAL OSHA PEL (United States, 5/2018).

#### Absorbed through skin.

STEL: 325 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes.

C: 1000 ppm

TWA: 260 mg/m³ 8 hours. TWA: 200 ppm 8 hours.

#### SFC Caffeine in Methanol Standard (10.0 µg/mL)

Methanol

#### ACGIH TLV (United States, 1/2023).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 262 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 328 mg/m³ 15 minutes.

#### OSHA PEL 1989 (United States, 3/1989).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes.

#### NIOSH REL (United States, 10/2020).

#### Absorbed through skin.

TWA: 200 ppm 10 hours. TWA: 260 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 5/2018).

#### TWA: 200 ppm 8 hours. TWA: 260 mg/m<sup>3</sup> 8 hours.

CAL OSHA PEL (United States, 5/2018).

#### Absorbed through skin.

STEL: 325 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes.

C: 1000 ppm

**Date of issue**: 02/01/2024 **27/53** 

TWA: 260 mg/m³ 8 hours. TWA: 200 ppm 8 hours.

#### SFC Caffeine in Methanol Standard (50.0 µg/mL)

Methanol

#### ACGIH TLV (United States, 1/2023).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 262 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 328 mg/m³ 15 minutes.

#### OSHA PEL 1989 (United States, 3/1989).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes.

#### NIOSH REL (United States, 10/2020).

#### Absorbed through skin.

TWA: 200 ppm 10 hours. TWA: 260 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 5/2018).

## TWA: 200 ppm 8 hours.

TWA: 260 mg/m³ 8 hours.

## CAL OSHA PEL (United States, 5/2018).

#### Absorbed through skin.

STEL: 325 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes.

C: 1000 ppm

TWA: 260 mg/m<sup>3</sup> 8 hours. TWA: 200 ppm 8 hours.

#### SFC Caffeine in Methanol Standard (100.0 µg/mL)

Methanol

#### ACGIH TLV (United States, 1/2023).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 262 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 328 mg/m³ 15 minutes.

#### OSHA PEL 1989 (United States, 3/1989).

#### Absorbed through skin.

TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes.

#### NIOSH REL (United States, 10/2020).

#### Absorbed through skin.

TWA: 200 ppm 10 hours. TWA: 260 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes. OSHA PEL (United States, 5/2018).

#### TWA: 200 ppm 8 hours. TWA: 260 mg/m<sup>3</sup> 8 hours.

CAL OSHA PEL (United States, 5/2018). Absorbed through skin.

Date of issue: 02/01/2024 28/53

STEL: 325 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes. C: 1000 ppm TWA: 260 mg/m³ 8 hours. TWA: 200 ppm 8 hours.

#### SFC Caffeine in Methanol Standard (200.0 µg/mL)

Methanol

#### ACGIH TLV (United States, 1/2023).

Absorbed through skin.
TWA: 200 ppm 8 hours.
TWA: 262 mg/m³ 8 hours.
STEL: 250 ppm 15 minutes.
STEL: 328 mg/m³ 15 minutes.

#### OSHA PEL 1989 (United States, 3/1989).

Absorbed through skin.
TWA: 200 ppm 8 hours.
TWA: 260 mg/m³ 8 hours.
STEL: 250 ppm 15 minutes.
STEL: 325 mg/m³ 15 minutes.

#### NIOSH REL (United States, 10/2020).

Absorbed through skin.
TWA: 200 ppm 10 hours.
TWA: 260 mg/m³ 10 hours.
STEL: 250 ppm 15 minutes.
STEL: 325 mg/m³ 15 minutes.
OSHA PEL (United States, 5/2018).

TWA: 200 ppm 8 hours. TWA: 260 mg/m<sup>3</sup> 8 hours.

## CAL OSHA PEL (United States, 5/2018).

Absorbed through skin.
STEL: 325 mg/m³ 15 minutes.
STEL: 250 ppm 15 minutes.

C: 1000 ppm

TWA: 260 mg/m<sup>3</sup> 8 hours. TWA: 200 ppm 8 hours.

#### **Biological exposure indices**

Ingredient name	Exposure indices		
FC Caffeine in Methanol Standard (Solvent Blank)			
Methanol	ACGIH BEI (United States, 1/2023) BEI: 15 mg/l, methanol [in urine]. Sampling time: end of shift.		
SFC Caffeine in Methanol Standard (2.0 μg/mL)			
Methanol	ACGIH BEI (United States, 1/2023) BEI: 15 mg/l, methanol [in urine]. Sampling time: end of shift.		
SFC Caffeine in Methanol Standard (10.0 μg/mL)			
Methanol	ACGIH BEI (United States, 1/2023) BEI: 15 mg/l, methanol [in urine]. Sampling time: end of shift.		

Date of issue: 02/01/2024 29/53

#### SFC Caffeine in Methanol Standard (50.0 µg/mL)

, , ,

ACGIH BEI (United States, 1/2023)
BEI: 15 mg/l, methanol [in urine]. Sampling

time: end of shift.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Methanol ACGIH BEI (United States, 1/2023)

BEI: 15 mg/l, methanol [in urine]. Sampling

time: end of shift.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Methanol ACGIH BEI (United States, 1/2023)

BEI: 15 mg/l, methanol [in urine]. Sampling

time: end of shift.

#### 8.2 Exposure controls

Methanol

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

## Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Date of issue: 02/01/2024 30/53

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Α	D	p	е	a	ra	n	C	е
_	_	_	_	_			_	_

Physical state : SFC Caffeine in Methanol Liquid. [Clear.]

Standard (Solvent Blank)

SFC Caffeine in Methanol Liquid. Standard (2.0 µg/mL)

SFC Caffeine in Methanol Liquid.

Standard (10.0 µg/mL)
SFC Caffeine in Methanol Liquid.

Standard (50.0 µg/mL)
SFC Caffeine in Methanol Liquid.

Standard (100.0 µg/mL)
SFC Caffeine in Methanol Liquid.

Standard (200.0 µg/mL)

Color : SFC Caffeine in Methanol Colorless.

Standard (Solvent Blank)
SFC Caffeine in Methanol Colorless.

Standard (2.0 µg/mL)
SFC Caffeine in Methanol Colorless.
Standard (10.0 µg/mL)

SFC Caffeine in Methanol Colorless.
Standard (50.0 µg/mL)

SFC Caffeine in Methanol Colorless.
Standard (100.0 µg/mL)

SFC Caffeine in Methanol Colorless.
Standard (200.0 µg/mL)

Odor : SFC Caffeine in Methanol Characteristic.

Standard (Solvent Blank)
SFC Caffeine in Methanol Not available.

Standard (2.0 µg/mL)
SFC Caffeine in Methanol
Standard (10.0 µg/mL)
Not available.

SFC Caffeine in Methanol Not available. Standard (50.0 µg/mL)

SFC Caffeine in Methanol Not available.
Standard (100.0 µg/mL)

SFC Caffeine in Methanol Not available.
Standard (200.0 µg/mL)

Odor threshold : SFC Caffeine in Methanol Not available.

Standard (100.0 µg/mL)

Standard (Solvent Blank)
SFC Caffeine in Methanol
Not available.

Standard (2.0 µg/mL)
SFC Caffeine in Methanol
Not available.

Standard (10.0 μg/mL)
SFC Caffeine in Methanol Not available.

Standard (50.0 µg/mL)
SFC Caffeine in Methanol
Not available.

**Date of issue:** 02/01/2024 **31/53** 

Occion 5. i nysica	i and chemical properti	ies and salety characterist
	SFC Caffeine in Methanol Standard (200.0 µg/mL)	Not available.
рН	: SFC Caffeine in Methanol Standard (Solvent Blank)	Not available.
	SFC Caffeine in Methanol Standard (2.0 µg/mL)	Not available.
	SFC Caffeine in Methanol Standard (10.0 μg/mL)	Not available.
	SFC Caffeine in Methanol Standard (50.0 µg/mL)	Not available.
	SFC Caffeine in Methanol Standard (100.0 µg/mL)	Not available.
	SFC Caffeine in Methanol Standard (200.0 µg/mL)	Not available.
Melting point/freezing point	: SFC Caffeine in Methanol Standard (Solvent Blank)	-98°C (-144.4°F)
	SFC Caffeine in Methanol Standard (2.0 µg/mL)	-98°C (-144.4°F)
	SFC Caffeine in Methanol Standard (10.0 µg/mL)	-98°C (-144.4°F)
	SFC Caffeine in Methanol Standard (50.0 μg/mL)	-98°C (-144.4°F)
	SFC Caffeine in Methanol Standard (100.0 µg/mL)	-98°C (-144.4°F)
	SFC Caffeine in Methanol Standard (200.0 µg/mL)	-98°C (-144.4°F)
Boiling point, initial boiling point, and boiling range	: SFC Caffeine in Methanol Standard (Solvent Blank)	64.8°C (148.6°F)
	SFC Caffeine in Methanol Standard (2.0 µg/mL)	64.8°C (148.6°F)
	SFC Caffeine in Methanol Standard (10.0 μg/mL)	64.8°C (148.6°F)
	SFC Caffeine in Methanol Standard (50.0 μg/mL)	64.8°C (148.6°F)
	SFC Caffeine in Methanol Standard (100.0 µg/mL)	64.8°C (148.6°F)
	SFC Caffeine in Methanol Standard (200.0 µg/mL)	64.8°C (148.6°F)
Flash point	: SFC Caffeine in Methanol Standard (Solvent Blank)	Closed cup: 11.1°C (52°F) [Abel-Pensky]
	SFC Caffeine in Methanol Standard (2.0 µg/mL)	Closed cup: 11.1°C (52°F)
	SFC Caffeine in Methanol Standard (10.0 μg/mL)	Closed cup: 11.1°C (52°F)
	SFC Caffeine in Methanol Standard (50.0 μg/mL)	Closed cup: 11.1°C (52°F)
	SFC Caffeine in Methanol Standard (100.0 µg/mL)	Closed cup: 11.1°C (52°F)
	SFC Caffeine in Methanol Standard (200.0 µg/mL)	Closed cup: 11.1°C (52°F)
Evaporation rate	: SFC Caffeine in Methanol Standard (Solvent Blank)	2.1 (butyl acetate = 1)
	SFC Caffeine in Methanol Standard (2.0 µg/mL)	Not available.
	SFC Caffeine in Methanol Standard (10.0 µg/mL)	Not available.
	SFC Caffeine in Methanol Standard (50.0 µg/mL)	Not available.

**Date of issue**: 02/01/2024 32/53

		SFC Caffeine in Methanol Standard (100.0 µg/mL)	Not available.
		SFC Caffeine in Methanol Standard (200.0 µg/mL)	Not available.
Flammability	:	SFC Caffeine in Methanol Standard (Solvent Blank)	Not applicable.
		SFC Caffeine in Methanol Standard (2.0 µg/mL)	Not applicable.
		SFC Caffeine in Methanol Standard (10.0 µg/mL)	Not applicable.
		SFC Caffeine in Methanol Standard (50.0 µg/mL)	Not applicable.
		SFC Caffeine in Methanol Standard (100.0 µg/mL)	Not applicable.
		SFC Caffeine in Methanol Standard (200.0 µg/mL)	Not applicable.
Lower and upper explosion	:	SFC Caffeine in Methanol	Lower: 6.7%
limit/flammability limit		Standard (Solvent Blank)	Upper: 36%
		SFC Caffeine in Methanol	Lower: 6.7%
		Standard (2.0 µg/mL)	
		SFC Caffeine in Methanol	Upper: 36% Lower: 6.7%
		Standard (10.0 µg/mL)	LOWGI. 0.7 70
		очантами (того ружие)	Upper: 36%
		SFC Caffeine in Methanol	Lower: 6.7%
		Standard (50.0 µg/mL)	
			Upper: 36%
		SFC Caffeine in Methanol Standard (100.0 µg/mL)	Lower: 6.7%
		0500 % :	Upper: 36%
		SFC Caffeine in Methanol Standard (200.0 µg/mL)	Lower: 6.7%
		_	Upper: 36%
Vapor pressure	:	SFC Caffeine in Methanol Standard (Solvent Blank)	13.3 kPa (100 mm Hg)
		SFC Caffeine in Methanol Standard (2.0 µg/mL)	13.3 kPa (100 mm Hg)
		SFC Caffeine in Methanol Standard (10.0 µg/mL)	13.3 kPa (100 mm Hg)
		SFC Caffeine in Methanol Standard (50.0 µg/mL)	13.3 kPa (100 mm Hg)
		SFC Caffeine in Methanol Standard (100.0 µg/mL)	13.3 kPa (100 mm Hg)
		SFC Caffeine in Methanol Standard (200.0 µg/mL)	13.3 kPa (100 mm Hg)
Relative vapor density	:	SFC Caffeine in Methanol Standard (Solvent Blank)	1.1 [Air = 1]
		SFC Caffeine in Methanol Standard (2.0 µg/mL)	1.1 [Air = 1]
		SFC Caffeine in Methanol Standard (10.0 µg/mL)	1.1 [Air = 1]
		SFC Caffeine in Methanol Standard (50.0 µg/mL)	1.1 [Air = 1]
		SFC Caffeine in Methanol Standard (100.0 µg/mL)	1.1 [Air = 1]
		SFC Caffeine in Methanol Standard (200.0 µg/mL)	1.1 [Air = 1]

**Date of issue**: 02/01/2024 33/53

•		
Relative density	: SFC Caffeine in Methanol	0.791
	Standard (Solvent Blank) SFC Caffeine in Methanol	0.791
	Standard (2.0 µg/mL)	0.791
	SFC Caffeine in Methanol	0.791
	Standard (10.0 µg/mL)	
	SFC Caffeine in Methanol	0.791
	Standard (50.0 µg/mL)	
	SFC Caffeine in Methanol	0.791
	Standard (100.0 µg/mL) SFC Caffeine in Methanol	0.791
	Standard (200.0 µg/mL)	0.701
Solubility(ies)	: Media	Result
	SFC Caffeine in Methanol Sta	
	(Solvent Blank)	Truck G
	water	Soluble
	SFC Caffeine in Methanol Sta	ndard
	(2.0 μg/mL)	
	water	Soluble
	SFC Caffeine in Methanol Sta (10.0 µg/mL)	ndard
	water	Soluble
	SFC Caffeine in Methanol Sta	
	(50.0 μg/mL)	
	water	Soluble
	SFC Caffeine in Methanol Sta	ndard
	(100.0 µg/mL)	Calubia
	water SFC Caffeine in Methanol Sta	Soluble
	(200.0 µg/mL)	
	water	Soluble
Partition coefficient: n-	: SFC Caffeine in Methanol	-0.77
octanol/water	Standard (Solvent Blank)	
	SFC Caffeine in Methanol	Not applicable.
	Standard (2.0 µg/mL)	Nick conficely
	SFC Caffeine in Methanol Standard (10.0 μg/mL)	Not applicable.
	SFC Caffeine in Methanol	Not applicable.
	Standard (50.0 µg/mL)	***
	SFC Caffeine in Methanol	Not applicable.
	Standard (100.0 µg/mL)	Nick conficely
	SFC Caffeine in Methanol Standard (200.0 µg/mL)	Not applicable.
Auto-ignition temperature	: SFC Caffeine in Methanol	385°C (725°F) [DIN 51794]
Auto-ignition temperature	Standard (Solvent Blank)	363 C (723 F) [DIN 31794]
	SFC Caffeine in Methanol	385°C (725°F)
	Standard (2.0 µg/mL)	
	SFC Caffeine in Methanol	385°C (725°F)
	Standard (10.0 µg/mL)	20E°C (72E°E)
	SFC Caffeine in Methanol Standard (50.0 µg/mL)	385°C (725°F)
	SFC Caffeine in Methanol	385°C (725°F)
	Standard (100.0 µg/mL)	
	SFC Caffeine in Methanol	385°C (725°F)
	Standard (200.0 µg/mL)	

**Date of issue:** 02/01/2024 34/53

**Decomposition temperature** 

SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol

Standard (10.0 µg/mL)
SFC Caffeine in Methanol

Standard (50.0 µg/mL) SFC Caffeine in Methanol

Standard (100.0 µg/mL) SFC Caffeine in Methanol Standard (200.0 µg/mL) Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

**Viscosity** 

SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Dynamic: 0.54 to 0.59 mPa·s (0.54 to 0.59 cP)

Not available.

Not available.

Not available.

Not available.

Not available.

Particle characteristics
Median particle size

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL) SFC Caffeine in Methanol

Standard (200.0 µg/mL)

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

## Section 10. Stability and reactivity

10.1 Reactivity

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

No specific test data related to reactivity available for this product or its ingredients.

No specific test data related to reactivity available for this product or its ingredients.

No specific test data related to reactivity available

for this product or its ingredients.

No specific test data related to reactivity available for this product or its ingredients.

No specific test data related to reactivity available

for this product or its ingredients.

No specific test data related to reactivity available

for this product or its ingredients.

Date of issue: 02/01/2024 35/53

## Section 10. Stability and reactivity

#### 10.2 Chemical stability

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

The product is stable.

## 10.3 Possibility of hazardous reactions

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use,

hazardous reactions will not occur.

Under normal conditions of storage and use,

hazardous reactions will not occur.

Under normal conditions of storage and use,

hazardous reactions will not occur.

Under normal conditions of storage and use,

hazardous reactions will not occur.

Under normal conditions of storage and use,

hazardous reactions will not occur.

#### 10.4 Conditions to avoid

: SFC Caffeine in Methanol Standard (Solvent Blank) Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

SFC Caffeine in Methanol Standard (10.0 µg/mL)

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

SFC Caffeine in Methanol Standard (50.0 µg/mL)

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Date of issue: 02/01/2024 36/53

## Section 10. Stability and reactivity

### 10.5 Incompatible materials

: SFC Caffeine in Methanol Reactive or incompatible with the following Standard (Solvent Blank) materials:

oxidizing materials

SFC Caffeine in Methanol Reactive or incompatible with the following

Standard (2.0 µg/mL) materials:

oxidizing materials

SFC Caffeine in Methanol Reactive or incompatible with the following

Standard (10.0 µg/mL) materials:

oxidizing materials

SFC Caffeine in Methanol Reactive or incompatible with the following

Standard (50.0 µg/mL) materials:

oxidizing materials

SFC Caffeine in Methanol Reactive or incompatible with the following Standard (100.0 µg/mL)

materials:

oxidizing materials SFC Caffeine in Methanol Reactive or incompatible with the following

Standard (200.0 µg/mL) materials:

oxidizing materials

### 10.6 Hazardous decomposition products

: SFC Caffeine in Methanol Standard (Solvent Blank)

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SFC Caffeine in Methanol Standard (2.0 µg/mL)

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SFC Caffeine in Methanol Standard (10.0 µg/mL)

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SFC Caffeine in Methanol Standard (50.0 µg/mL)

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SFC Caffeine in Methanol Standard (100.0 µg/mL)

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SFC Caffeine in Methanol Standard (200.0 µg/mL)

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

## **Section 11. Toxicological information**

### 11.1 Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
SFC Caffeine in Methanol Standard (Solvent Blank)				
Methanol	LC50 Inhalation Vapor LC50 Inhalation Vapor LC50 Inhalation Vapor LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rat Rat Rat Rat Rabbit Rat	189.95 mg/l 145000 ppm 83.84 mg/l 64000 ppm 15800 mg/kg 5600 mg/kg	1 hours 1 hours 4 hours 4 hours -
SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol	LC50 Inhalation Vapor LC50 Inhalation Vapor LC50 Inhalation Vapor LC50 Inhalation Vapor	Rat Rat Rat Rat	189.95 mg/l 145000 ppm 83.84 mg/l 64000 ppm	1 hours 1 hours 4 hours 4 hours

02/01/2024 Date of issue: 37/53

	LD50 Dermal	Rabbit	15800 mg/kg	
	LD50 Oral	Rat	5600 mg/kg	-
	LD30 Oral	Nat	3000 mg/kg	-
SFC Caffeine in Methanol Standard (10.0 µg/mL)				
Methanol	LC50 Inhalation Vapor	Rat	189.95 mg/l	1 hours
	LC50 Inhalation Vapor	Rat	145000 ppm	1 hours
	LC50 Inhalation Vapor	Rat	83.84 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	_
			3.1.9	
SFC Caffeine in Methanol Standard (50.0 µg/mL)				
Methanol	LC50 Inhalation Vapor	Rat	189.95 mg/l	1 hours
	LC50 Inhalation Vapor	Rat	145000 ppm	1 hours
	LC50 Inhalation Vapor	Rat	83.84 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
SFC Caffeine in Methanol Standard (100.0 µg/mL)				
Methanol	LC50 Inhalation Vapor	Rat	189.95 mg/l	1 hours
	LC50 Inhalation Vapor	Rat	145000 ppm	1 hours
	LC50 Inhalation Vapor	Rat	83.84 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
SFC Caffeine in Methanol Standard (200.0 µg/mL)				
Methanol	LC50 Inhalation Vapor	Rat	189.95 mg/l	1 hours
	LC50 Inhalation Vapor	Rat	145000 ppm	1 hours
	LC50 Inhalation Vapor	Rat	83.84 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	4 110015
	LD50 Dermai LD50 Oral	Rat	15800 mg/kg   5600 mg/kg	-
	LD30 Olai	nat	5000 mg/kg	-

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
SFC Caffeine in Methanol Standard (Solvent Blank)					
Methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	40 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
SFC Caffeine in Methanol Standard (2.0 µg/mL)					
Methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	40 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
SFC Caffeine in Methanol Standard (10.0 µg/mL)					

**Date of issue:** 02/01/2024 38/53

		-			
Methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	40 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
SFC Caffeine in Methanol					
Standard (50.0 µg/mL)					
Methanol	Eyes - Moderate irritant	Rabbit	_	24 hours 100	_
	-,			mg	
	Eyes - Moderate irritant	Rabbit	-	40 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
SFC Caffeine in Methanol					
Standard (100.0 µg/mL)					
Methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	40 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
SFC Caffeine in Methanol					
Standard (200.0 µg/mL)					
Methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
	From Mandamata institut	D. I. I. I		mg	
	Eyes - Moderate irritant	Rabbit	-	40 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	

### **Sensitization**

Not available.

### **Mutagenicity**

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

**Reproductive toxicity** 

**Conclusion/Summary**: Not available.

**Teratogenicity** 

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
SFC Caffeine in Methanol Standard (Solvent Blank) Methanol	Category 1	-	central nervous system (CNS), optic nerve
SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol	Category 1	-	central nervous system (CNS), optic nerve
SFC Caffeine in Methanol Standard (10.0 µg/mL) Methanol	Category 1	-	central nervous system (CNS),

Date of issue: 02/01/2024 39/53

			optic nerve
SFC Caffeine in Methanol Standard (50.0 µg/mL) Methanol	Category 1	-	central nervous system (CNS), optic nerve
SFC Caffeine in Methanol Standard (100.0 μg/mL) Methanol	Category 1	-	central nervous system (CNS), optic nerve
SFC Caffeine in Methanol Standard (200.0 μg/mL) Methanol	Category 1	-	central nervous system (CNS), optic nerve

Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

# Information on the likely routes of exposure

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

**Eye contact** 

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

No known significant effects or critical hazards.

Inhalation

SFC Caffeine in Methanol Standard (Solvent Blank)
SFC Caffeine in Methanol Standard (2.0 μg/mL)
SFC Caffeine in Methanol Standard (10.0 μg/mL)
SFC Caffeine in Methanol Standard (50.0 μg/mL)
SFC Caffeine in Methanol Standard (100.0 μg/mL)
SFC Caffeine in Methanol Standard (100.0 μg/mL)

Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs following a single exposure if inhaled. Toxic if inhaled. Causes damage to organs

**Date of issue :** 02/01/2024 **40/53** 

### **Skin contact**

Standard (200.0 µg/mL)

SFC Caffeine in Methanol

Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol Standard (10.0 µg/mL)

Standard (50.0 µg/mL) SFC Caffeine in Methanol Standard (100.0 µg/mL) SFC Caffeine in Methanol Standard (200.0 µg/mL)

SFC Caffeine in Methanol

following a single exposure if inhaled.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with

skin.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with

skin.

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with

Toxic in contact with skin. Causes damage to organs following a single exposure in contact with

skin.

Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Ingestion

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL)

SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL)

SFC Caffeine in Methanol Standard (200.0 µg/mL)

: SFC Caffeine in Methanol Standard (Solvent Blank)

SFC Caffeine in Methanol Standard (2.0 µg/mL)

SFC Caffeine in Methanol Standard (10.0 µg/mL) SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL) SFC Caffeine in Methanol

Standard (200.0 µg/mL)

No specific data.

## Inhalation

02/01/2024 Date of issue: 41/53

Skin contact

Ingestion

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol

Standard (10.0 µg/mL) SFC Caffeine in Methanol Standard (50.0 µg/mL)

SFC Caffeine in Methanol Standard (100.0 µg/mL) SFC Caffeine in Methanol

Standard (200.0 µg/mL)

 FC Caffeine in Methanol Standard (Solvent Blank)
 SFC Caffeine in Methanol Standard (2.0 μg/mL)
 SFC Caffeine in Methanol

Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol

Standard (200.0 µg/mL)

No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

### Short term exposure

**Potential immediate** 

effects

: Not available.

: Not available.

Potential delayed effects

Long term exposure

**Potential immediate** 

effects

: Not available.

: Not available.

### Potential chronic health effects

Potential delayed effects

General

: SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

Carcinogenicity

Standard (100.0 μg/mL)
SFC Caffeine in Methanol
Standard (200.0 μg/mL)

: SFC Caffeine in Methanol
Standard (Solvent Blank)
SFC Caffeine in Methanol
Standard (2.0 μg/mL)
SFC Caffeine in Methanol
Standard (10.0 μg/mL)
SFC Caffeine in Methanol
Standard (50.0 μg/mL)
SFC Caffeine in Methanol
Standard (100.0 μg/mL)

No known significant effects or critical hazards.

**Date of issue:** 02/01/2024 **42/53** 

### Mutagenicity

Standard (200.0 µg/mL)

: SFC Caffeine in Methanol Standard (Solvent Blank)
SFC Caffeine in Methanol Standard (2.0 µg/mL)
SFC Caffeine in Methanol Standard (10.0 µg/mL)
SFC Caffeine in Methanol Standard (50.0 µg/mL)
SFC Caffeine in Methanol Standard (100.0 µg/mL)
SFC Caffeine in Methanol Standard (200.0 µg/mL)

SFC Caffeine in Methanol

## No known significant effects or critical hazards.

### Reproductive toxicity

SFC Caffeine in Methanol Standard (Solvent Blank) SFC Caffeine in Methanol Standard (2.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL)

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
SFC Caffeine in Methanol Standard (Solvent					
Blank) Methanol	100	300	N/A	3	N/A
SFC Caffeine in Methanol Standard (2.0 µg/mL) SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol	100.0 100	300.0 300	N/A N/A	3.0	N/A N/A
SFC Caffeine in Methanol Standard (10.0 μg/mL) SFC Caffeine in Methanol Standard (10.0 μg/mL) Methanol	100.0 100	300.0 300	N/A N/A	3.0	N/A N/A
SFC Caffeine in Methanol Standard (50.0 μg/mL) SFC Caffeine in Methanol Standard (50.0 μg/mL) Methanol	100.0 100	300.0 300	N/A N/A	3.0	N/A N/A
SFC Caffeine in Methanol Standard (100.0 μg/mL) SFC Caffeine in Methanol Standard (100.0 μg/mL) Methanol	100.0 100	300.0 300	N/A N/A	3.0	N/A N/A
SFC Caffeine in Methanol Standard (200.0 μg/mL) SFC Caffeine in Methanol Standard (200.0 μg/mL) Methanol	100.0 100	300.1 300	N/A N/A	3.0 3	N/A N/A

**Date of issue:** 02/01/2024 **43/53** 

#### Other information : SFC Caffeine in Methanol Adverse symptoms may include the following: Standard (Solvent Blank) blurred or double vision, Eye contact can result in corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage. Repeated exposure may cause skin dryness or cracking. SFC Caffeine in Methanol Adverse symptoms may include the following: blurred or double vision, Eye contact can result in Standard (2.0 µg/mL) corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage. Narcotic effect. May cause nervous system disturbances. SFC Caffeine in Methanol Adverse symptoms may include the following: Standard (10.0 µg/mL) blurred or double vision, Eye contact can result in corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage. Narcotic effect. May cause nervous system disturbances. SFC Caffeine in Methanol Adverse symptoms may include the following: Standard (50.0 µg/mL) blurred or double vision, Eye contact can result in corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage. Narcotic effect. May cause nervous system disturbances. SFC Caffeine in Methanol Adverse symptoms may include the following: blurred or double vision, Eye contact can result in Standard (100.0 µg/mL) corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage. Narcotic effect. May cause nervous system disturbances. SFC Caffeine in Methanol Adverse symptoms may include the following: blurred or double vision, Eye contact can result in Standard (200.0 µg/mL) corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage. Narcotic effect. May cause nervous

## Section 12. Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
SFC Caffeine in Methanol			
Standard (Solvent Blank)			
Methanol	Acute EC50 2736 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 μg/l Marine water	Crustaceans - <i>Crangon crangon</i> - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - Danio rerio - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
SFC Caffeine in Methanol Standard (2.0 µg/mL)			
Methanol	Acute EC50 2736 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute LC50 2500000 μg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours

system disturbances.

Date of issue: 02/01/2024 44/53

	Acute LC50 290 mg/l Fresh water	Fish - <i>Danio rerio</i> - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
SFC Caffeine in Methanol Standard (10.0 µg/mL)			
Methanol	Acute EC50 2736 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - <i>Crangon crangon</i> - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - <i>Danio rerio</i> - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
SFC Caffeine in Methanol Standard (50.0 µg/mL)			
Methanol	Acute EC50 2736 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - <i>Danio rerio</i> - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
SFC Caffeine in Methanol Standard (100.0 µg/mL)			
Methanol	Acute EC50 2736 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - <i>Danio rerio</i> - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
SFC Caffeine in Methanol Standard (200.0 µg/mL)			
Methanol	Acute EC50 2736 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - <i>Danio rerio</i> - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours

## 12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
SFC Caffeine in Methanol Standard (Solvent Blank) Methanol	-	-	Readily
SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol	-	-	Readily
SFC Caffeine in Methanol Standard (10.0 µg/mL) Methanol	-	-	Readily

**Date of issue:** 02/01/2024 **45/53** 

_			
SFC Caffeine in Methanol Standard (50.0 µg/mL) Methanol	-	-	Readily
SFC Caffeine in Methanol Standard (100.0 µg/mL) Methanol	-	-	Readily
SFC Caffeine in Methanol Standard (200.0 µg/mL) Methanol	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
SFC Caffeine in Methanol Standard (Solvent Blank) Methanol	-0.77	<10	Low
SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol	-0.77	<10	Low
SFC Caffeine in Methanol Standard (10.0 µg/mL) Methanol	-0.77	<10	Low
SFC Caffeine in Methanol Standard (50.0 µg/mL) Methanol	-0.77	<10	Low
SFC Caffeine in Methanol Standard (100.0 µg/mL) Methanol	-0.77	<10	Low
SFC Caffeine in Methanol Standard (200.0 µg/mL) Methanol	-0.77	<10	Low

### **12.4 Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

12.5 Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

### 13.1 Waste treatment methods

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been

**Date of issue**: 02/01/2024 **46/53** 

## Section 13. Disposal considerations

cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS#	Status	Reference number
SFC Caffeine in Methanol Standard (Solvent Blank) Methanol (I)	67-56-1	Listed	U154
SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol (I)	67-56-1	Listed	U154
SFC Caffeine in Methanol Standard (10.0 μg/mL) Methanol (I)	67-56-1	Listed	U154
SFC Caffeine in Methanol Standard (50.0 μg/mL) Methanol (I)	67-56-1	Listed	U154
SFC Caffeine in Methanol Standard (100.0 µg/mL) Methanol (I)	67-56-1	Listed	U154
SFC Caffeine in Methanol Standard (200.0 µg/mL) Methanol (I)	67-56-1	Listed	U154

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1230	UN1230	UN1230	UN1230	UN1230
UN proper shipping name	Methanol solution	METHANOL solution	METANOL solution	METHANOL solution	Methanol solution
Transport hazard class(es)	3	3 (6.1)	3 (6.1)	3 (6.1)	3 (6.1)
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.

**Additional information** 

**Date of issue**: 02/01/2024 **47/53** 

## **Section 14. Transport information**

Remarks: Excepted Quantity

**DOT Classification** : Reportable quantity 5000.4 lbs / 2270.2 kg. Package sizes shipped in quantities less

than the product reportable quantity are not subject to the RQ (reportable quantity)

transportation requirements.

Limited quantity Yes.

Packaging instruction Exceptions: 150. Non-bulk: 202. Bulk: 242. Quantity limitation Passenger aircraft/rail: 1 L. Cargo aircraft: 60 L.

Special provisions IB2, T7, TP2

Product classified as per the following sections of the Transportation of Dangerous **TDG Classification** 

Goods Regulations: 2.18-2.19 (Class 3), 2.26-2.36 (Class 6).

**Explosive Limit and Limited Quantity Index 1** Passenger Carrying Road or Rail Index 1

Special provisions 43

**Mexico Classification** : Special provisions 279

**IMDG** : Emergency schedules F-E, S-D

Special provisions 279

**IATA** Quantity limitation Passenger and Cargo Aircraft: 1 L. Packaging instructions: 352.

Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger

Aircraft: 1 L. Packaging instructions: Y341.

**Special provisions** A113

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

## Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined **U.S. Federal regulations** 

Clean Air Act Section 112 Listed

(b) Hazardous Air **Pollutants (HAPs)** 

Clean Air Act Section 602 : Not listed

**Class I Substances** 

Clean Air Act Section 602 : Not listed

**Class II Substances** 

**DEA List I Chemicals** : Not listed

(Precursor Chemicals)

**DEA List II Chemicals** : Not listed

(Essential Chemicals)

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

02/01/2024 Date of issue: 48/53

## ection 15 Regulatory information

ection 13. Kegt	ilatory ilitoriliation
Classification	: FC Caffeine in Methanol Standard

ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3

ACUTE TOXICITY (inhalation) - Category 3

FLAMMABLE LIQUIDS - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

SFC Caffeine in Methanol Standard (2.0 µg/ FLAMMABLE LIQUIDS - Category 2

mL)

(Solvent Blank)

ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

SFC Caffeine in Methanol Standard (10.0

µg/mL)

FLAMMABLE LIQUIDS - Category 2

ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

SFC Caffeine in Methanol Standard (50.0

µg/mL)

FLAMMABLE LIQUIDS - Category 2

ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

SFC Caffeine in Methanol Standard (100.0

µg/mL)

FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3

FLAMMABLE LIQUIDS - Category 2

ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

SFC Caffeine in Methanol Standard (200.0

µg/mL)

ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3
ACUTE TOXICITY (inhalation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

### Composition/information on ingredients

Name	%	Classification
SFC Caffeine in Methanol Standard (Solvent Blank) Methanol	100	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol	≥90	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SFC Caffeine in Methanol Standard (10.0 μg/mL) Methanol	≥90	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SFC Caffeine in Methanol Standard (50.0 μg/mL)		

Date of issue: 02/01/2024 49/53

# Section 15. Regulatory information

Methanol	≥90	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SFC Caffeine in Methanol Standard (100.0 µg/mL) Methanol	≥90	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SFC Caffeine in Methanol Standard (200.0 µg/mL) Methanol	≥90	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	SFC Caffeine in Methanol Standard (Solvent Blank) Methanol	67-56-1	100
	SFC Caffeine in Methanol Standard (2.0 μg/mL) Methanol	67-56-1	≥90
	SFC Caffeine in Methanol Standard (10.0 μg/ mL) Methanol	67-56-1	≥90
	SFC Caffeine in Methanol Standard (50.0 µg/mL) Methanol	67-56-1	≥90
	SFC Caffeine in Methanol Standard (100.0 μg/ mL) Methanol	67-56-1	≥90
	SFC Caffeine in Methanol Standard (200.0 μg/ mL) Methanol	67-56-1	≥90
Supplier notification	SFC Caffeine in Methanol Standard (Solvent Blank)  Methanol	67-56-1	100
	SFC Caffeine in Methanol Standard (2.0 μg/mL) Methanol	67-56-1	≥90
	SFC Caffeine in Methanol Standard (10.0 µg/mL) Methanol	67-56-1	≥90
	SFC Caffeine in Methanol Standard (50.0 µg/mL) Methanol	67-56-1	≥90
eto of issue: 02/01	/2024		50/53

**Date of issue:** 02/01/2024 50/53

## **Section 15. Regulatory information**

SFC Caffeine in Methanol Standard (100.0 µg/		
mL)		
Methanol	67-56-1	≥90
SFC Caffeine in Methanol Standard (200.0 µg/		
mL)		
Methanol	67-56-1	≥90

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### **State regulations**

New Jersey : The following components are listed: METHYL ALCOHOL

Pennsylvania : The following components are listed: METHANOL

### California Prop. 65

▲ WARNING: This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
SFC Caffeine in Methanol Standard (Solvent Blank) Methanol	-	Yes.
SFC Caffeine in Methanol Standard (2.0 µg/mL) Methanol	-	Yes.
SFC Caffeine in Methanol Standard (10.0 µg/mL) Methanol	-	Yes.
SFC Caffeine in Methanol Standard (50.0 µg/mL) Methanol	-	Yes.
SFC Caffeine in Methanol Standard (100.0 µg/mL) Methanol	-	Yes.
SFC Caffeine in Methanol Standard (200.0 µg/mL) Methanol	-	Yes.

### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

### **Inventory list**

Date of issue: 02/01/2024 51/53

## Section 15. Regulatory information

**Australia** : All components are listed or exempted. Canada : All components are listed or exempted. **China** : All components are listed or exempted.

**Japan** Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): All components are listed or exempted.

**New Zealand** : All components are listed or exempted. **Philippines** All components are listed or exempted. Republic of Korea : All components are listed or exempted. **Taiwan** : All components are listed or exempted. **Thailand** All components are listed or exempted. **Turkey** : All components are listed or exempted. **United States** : All components are active or exempted. **Viet Nam** : All components are listed or exempted.

### Section 16. Other information

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	On basis of test data Expert judgment Expert judgment On basis of test data Expert judgment
SFC Caffeine in Methanol Standard (2.0 μg/mL) FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	On basis of test data Calculation method Calculation method Calculation method Calculation method
SFC Caffeine in Methanol Standard (10.0 μg/mL) FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	On basis of test data Calculation method Calculation method Calculation method Calculation method
SFC Caffeine in Methanol Standard (50.0 μg/mL) FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	On basis of test data Calculation method Calculation method Calculation method Calculation method
SFC Caffeine in Methanol Standard (100.0 μg/mL) FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	On basis of test data Calculation method Calculation method Calculation method Calculation method
SFC Caffeine in Methanol Standard (200.0 μg/mL) FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3	On basis of test data Calculation method

02/01/2024 Date of issue: 52/53

### Section 16. Other information

ACUTE TOXICITY (dermal) - Category 3

ACUTE TOXICITY (inhalation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

Calculation method

Calculation method

### **History**

Date of issue/Date of

revision

Date of previous issue : 02/26/2021

Version : 6

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available UN = United Nations

Indicates information that has changed from previously issued version.

: 02/01/2024

### **Notice to reader**

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

Date of issue: 02/01/2024 53/53