

This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

Revision date 12-Apr-2024 Revision Number 1

1. Identification

Product identifier

Product Name Lithium Standard: 10000 µg/mL Li in 5% HNO3 [100ml bottle]

Other means of identification

Product Code(s) 5190-8408

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Reagents and Standards for Analytical Chemical Laboratory Use

Restrictions on useNot to be used for human or animal consumption

Details of the supplier of the safety data sheet

Supplier Address

Agilent Technologies, Inc. 5301 Stevens Creek Blvd Santa Clara, CA 95051, USA

800-227-9770

E-mail pdl-msds_author@agilent.com

Emergency telephone number

Emergency Telephone

CHEMTREC®: 1-800-424-9300

2. Hazard(s) identification

Classification

Classified according to OSHA.

Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Corrosive to metals	Category 1

AGHS / EN Page 1/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 µg/mL Li in 5% HNO3 [100ml bottle]

Revision date 12-Apr-2024

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Danger

Hazard statements

Classified according to OSHA.

Causes severe skin burns and eye damage

May cause damage to organs through prolonged or repeated exposure

May be corrosive to metals



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/clothing and eye/face protection Do not breathe dust/fume/gas/mist/vapors/spray Keep only in original packaging

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Immediately call a POISON CENTER or doctor

IF SWALLOWED: Rinse mouth, Do NOT induce vomiting

Absorb spillage to prevent material damage

Precautionary Statements - Storage

Store in corrosion resistant container with a resistant inner liner

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available.

AGHS / EN Page 2/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 μg/mL Li in 5%

HNO3 [100ml bottle]

Revision date 12-Apr-2024

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical nature

aqueous solution.

Chemical name	CAS No.	Weight-%	Trade secret
Nitric Acid	7697-37-2	5 - <10	*
Lithium carbonate	554-13-2	1 - <3	*

Additional information

The concentration of the acid stated in this SDS is calculated as an absolute mass concentration (%w/v). This is less than the acid concentration stated on the product label and COA, which reflects a percent value of the commercially available concentrated aqueous form of the acid.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical

attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open

while rinsing. Do not rub affected area. Get immediate medical attention.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. Get immediate medical attention.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Get immediate medical attention.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

AGHS / EN Page 3/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 μg/mL Li in 5%

HNO3 [100ml bottle]

Revision date 12-Apr-2024

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood

pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. Fire-fighting measures

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition

can lead to release of irritating gases and vapors.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Attention! Corrosive material. Evacuate personnel to safe

areas. Keep people away from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

AGHS / EN Page 4/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 μg/mL Li in 5%

HNO3 [100ml bottle]

Revision date 12-Apr-2024

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials. Please refer to the manufacturer's certificate for specific storage and transport temperature conditions. Store only in the original receptacle unless other advice is given on the CoA.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Nitric Acid	TWA: 2 ppm	TWA: 2 ppm	IDLH: 25 ppm
7697-37-2	STEL: 4 ppm	TWA: 5 mg/m ³	TWA: 2 ppm
		(vacated) TWA: 2 ppm	TWA: 5 mg/m³
		(vacated) TWA: 5 mg/m ³	STEL: 4 ppm
		(vacated) STEL: 4 ppm	STEL: 10 mg/m ³
		(vacated) STEL: 10 mg/m ³	

AGHS / EN Page 5/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 μg/mL Li in 5%

HNO3 [100ml bottle]

Revision date 12-Apr-2024

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield. Avoid contact with eyes. Wear safety

glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Impervious gloves. The protective gloves to be used must comply

with the specifications of EC Directive 89/686/EEC and the related standard EN374. Wear

protective Neoprene™ gloves.

Skin and body protectionLong sleeved clothing. Chemical resistant apron. Wear suitable protective clothing.

exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

General hygiene considerations Regular cleaning of equipment, work area and clothing is recommended. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Wear

suitable gloves and eye/face protection.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical stateLiquidAppearanceLiquidColorcolorlessOdorOdorless

Odor threshold No information available

AGHS / EN Page 6/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

None known

None known

5190-8408 - Lithium Standard: 10000 μg/mL Li in 5%

HNO3 [100ml bottle]

Revision date 12-Apr-2024

<u>Property</u>	<u>Values</u>	Remarks • Method
рН	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling rang	eNo data available	None known
Flash point	No data available	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
• • • • • • • • • • • • • • • • • • •		

No data available

No data available

Other information

Kinematic viscosity

Dynamic viscosity

Explosive properties
Oxidizing properties
No information available
VOC content
No information available
No information available
No information available
No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions
None under normal processing.

Conditions to avoid Exposure to air or moisture over prolonged periods.

Incompatible materials Oxidizing agent. Acids. Bases.

Hazardous decomposition products None known based on information supplied.

AGHS / EN Page 7/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 μg/mL Li in 5%

HNO3 [100ml bottle]

Revision date 12-Apr-2024

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Pulmonary edema can be fatal.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage.

(based on components). Corrosive to the eyes and may cause severe damage including

blindness. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung

damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 52,500.00 mg/kg ATEmix (inhalation-vapor) 44.20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Nitric Acid	-	-	= 2500 ppm (Rat) 1 h
7697-37-2			ATE (vapours) = 2.65 mg/L
Lithium carbonate	= 525 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	> 2.17 mg/L (Rat) 4 h

AGHS / EN Page 8/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - $\,$ Lithium Standard: 10000 µg/mL Li in 5%

HNO3 [100ml bottle]

Revision date 12-Apr-2024

554-13-2

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes severe skin burns and eye

damage.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye damage. Causes

burns

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

Other adverse effects No information available.

Interactive effects No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Lithium carbonate	-	LC50: =30.3mg/L (96h,	-	-

AGHS / EN Page 9/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 μ g/mL Li in 5%

Revision date 12-Apr-2024

HNO3 [100ml bottle]

554-13-2 Oncorhynchus mykiss)

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Nitric Acid	-2.3
7697-37-2	

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as

a hazardous waste.

14. Transport information

DOT

UN number or ID number UN2031

Extended proper shipping name Nitric acid mixture

Transport hazard class(es) 8
Packing group

Reportable Quantity (RQ) (Nitric Acid: RQ (kg)= 454.00) Nitric Acid: RQ (lb)= 1000.00

Reportable quantity (kg) Nitric Acid: RQ (kg)= 7567.00

(calculated)

Reportable quantity (lbs) Nitric Acid: RQ (lb)= 16667.00

(calculated)

Special Provisions A6, B2, B47, B53, IB2, T8, TP2

DOT Marine Pollutant NP

Description UN2031, Nitric acid mixture, 8, II

Emergency Response Guide 157

AGHS / EN Page 10/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 µg/mL Li in 5% HNO3 [100ml bottle]

Revision date 12-Apr-2024

Number

TDG

UN number or ID number UN2031

UN proper shipping name Nitric acid mixture

Transport hazard class(es) 8
Packing group II
Marine pollutant NP

Description UN2031, Nitric acid mixture, 8, II

<u>MEX</u>

UN number or ID number UN2031

UN proper shipping name Nitric acid mixture

Transport hazard class(es) 8
Packing group | |

Description UN2031, Nitric acid mixture, 8, II

IATA

UN number or ID number UN2031

UN proper shipping name Nitric acid mixture

Transport hazard class(es) 8
Packing group | |

Description UN2031, Nitric acid mixture, 8, II

ERG Code 8L

<u>IMDG</u>

UN number or ID number UN2031

UN proper shipping name Nitric acid mixture

Transport hazard class(es) 8
Packing group II
EmS-No. F-A, S-B
Marine pollutant NP

Description UN2031, Nitric acid mixture, 8, II

15. Regulatory information

International Inventories

TSCA LGC, to the best of its ability, has confirmed that the chemical substances in this product are

listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb 2019, as

amended Feb 2021.".

AGHS / EN Page 11/14



Chemical name

Nitric Acid

Lithium carbonate

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

Inventory Listin

Present

Present

CAS No.

7697-37-2

554-13-2

5190-8408 - Lithium Standard: 10000 μg/mL Li in 5%

HNO3 [100ml bottle]

Commercial Activity
Designation

Revision date 12-Apr-2024

Active

Active

DSL/NDSL EINECS/ELINCS ENCS	Contact supplier for inventory compliance status. Contact supplier for inventory compliance status. Contact supplier for inventory compliance status.
IECSC	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AIIC	Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Nitric Acid - 7697-37-2	1.0
Lithium carbonate - 554-13-2	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Nitric Acid	1000 lb	-	-	Χ

AGHS / EN Page 12/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 $\mu g/mL$ Li in 5%

Revision date 12-Apr-2024

HNO3 [100ml bottle]

7697-37-2		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Nitric Acid 7697-37-2	1000 lb	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name Lithium carbonate - 554-13-2		California Proposition 65	
		Developmental	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water	-	-	X
7732-18-5			
Nitric Acid 7697-37-2	X	X	Х
Lithium carbonate 554-13-2	Х	X	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPAHealth hazards3Flammability0Instability0Special hazards-HMISHealth hazards3 *Flammability0Physical hazards0Personal protectionX

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

AGHS / EN Page 13/14



This safety data sheet was created pursuant to the requirements of: OSHA HCS2012

5190-8408 - Lithium Standard: 10000 μ g/mL Li in 5% HNO3 [100ml bottle]

Revision date 12-Apr-2024

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision date 12-Apr-2024

Revision NoteNo information available.

Disclaimer

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

End of Safety Data Sheet

AGHS / EN Page 14/14