

SAFETY DATA SHEET

Gas Clean Filter Kit for TCD, Part Number CP738408

Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier

Product name : Gas Clean Filter Kit for TCD, Part Number CP738408
Part no. (chemical kit) : CP738408
Part no. : Gas Clean Filter Oxygen CP17970
Gas Clean Filter Moisture CP17971
Validation date : 3/6/2024

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : ☒ Analytical chemistry.
☒ Gas Clean Filter Oxygen 1 x 200 ml
Gas Clean Filter Moisture 1 x 200 ml

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer : Agilent Technologies, Inc.
5301 Stevens Creek Blvd
Santa Clara, CA 95051, USA
800-227-9770

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

OSHA/HCS status : Gas Clean Filter Oxygen This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Gas Clean Filter Moisture This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

Gas Clean Filter Oxygen





H332 ACUTE TOXICITY (inhalation) - Category 4
H317 SKIN SENSITIZATION - Category 1
H350 CARCINOGENICITY - Category 1A
H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
H400 AQUATIC HAZARD (ACUTE) - Category 1
H411 AQUATIC HAZARD (LONG-TERM) - Category 2

Gas Clean Filter Moisture

H350 CARCINOGENICITY - Category 1A
H372 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Ingredients of unknown toxicity : Gas Clean Filter Oxygen Percentage of the mixture consisting of ingredient (s) of unknown acute inhalation toxicity: > 60%

Section 2. Hazards identification

	Gas Clean Filter Moisture	Percentage of the mixture consisting of ingredient (s) of unknown hazards to the aquatic environment: 100%
2.2 GHS label elements		
Hazard pictograms	: Gas Clean Filter Oxygen	  
	Gas Clean Filter Moisture	
Signal word	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Danger Danger
Hazard statements	: Gas Clean Filter Oxygen	H317 - May cause an allergic skin reaction. H332 - Harmful if inhaled. H350 - May cause cancer. H373 - May cause damage to organs through prolonged or repeated exposure. (brain) H400 - Very toxic to aquatic life. H411 - Toxic to aquatic life with long lasting effects.
	Gas Clean Filter Moisture	H350 - May cause cancer. H372 - Causes damage to organs through prolonged or repeated exposure. (lungs)
Precautionary statements		
Prevention	: Gas Clean Filter Oxygen	P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing and eye or face protection. P273 - Avoid release to the environment. P260 - Do not breathe dust.
	Gas Clean Filter Moisture	P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing and eye or face protection. P260 - Do not breathe dust. P270 - Do not eat, drink or smoke when using this product.
Response	: Gas Clean Filter Oxygen	P391 - Collect spillage. P308 + P313 - IF exposed or concerned: Get medical advice or attention. P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water.
	Gas Clean Filter Moisture	P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not applicable. Not applicable.
Disposal	:	

Section 2. Hazards identification

	Gas Clean Filter Oxygen	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
	Gas Clean Filter Moisture	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	None known. None known.
2.3 Other hazards		
Hazards not otherwise classified	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	None known. None known.

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product’s directions for use it may present potential health and safety hazards.

Substance/mixture	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Mixture (encapsulated in article) Mixture (encapsulated in article)
-------------------	--	--

Ingredient name	%	CAS number
Gas Clean Filter Oxygen		
Copper oxide, Activated	≤10	1317-38-0
Manganese dioxide	≤10	1313-13-9
nickel monoxide	<1	1313-99-1
Gas Clean Filter Moisture		
crystalline silica, respirable powder	≤10	14808-60-7
cristobalite	≤10	14464-46-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

Eye contact	: Gas Clean Filter Oxygen	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
	Gas Clean Filter Moisture	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Section 4. First aid measures

Inhalation

: Gas Clean Filter Oxygen

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Gas Clean Filter Moisture

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Gas Clean Filter Oxygen

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Gas Clean Filter Moisture

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Gas Clean Filter Oxygen

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical

Gas Clean Filter Moisture

Section 4. First aid measures

personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Inhalation	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Skin contact	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Ingestion	: Gas Clean Filter Oxygen Gas Clean Filter Moisture

No known significant effects or critical hazards.
No known significant effects or critical hazards.
Harmful if inhaled.
No known significant effects or critical hazards.
May cause an allergic skin reaction.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Inhalation	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Skin contact	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Ingestion	: Gas Clean Filter Oxygen Gas Clean Filter Moisture

No specific data.
No specific data.
No specific data.
No specific data.
Adverse symptoms may include the following:
irritation
redness
No specific data.
No specific data.
No specific data.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Specific treatments	: Gas Clean Filter Oxygen Gas Clean Filter Moisture
Protection of first-aiders	: Gas Clean Filter Oxygen Gas Clean Filter Moisture

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
No specific treatment.
No specific treatment.
No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media : Gas Clean Filter Oxygen
Gas Clean Filter Moisture

Use an extinguishing agent suitable for the surrounding fire.
Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : Gas Clean Filter Oxygen
Gas Clean Filter Moisture

None known.
None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the chemical : Gas Clean Filter Oxygen

This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. No specific fire or explosion hazard.

Hazardous thermal decomposition products : Gas Clean Filter Oxygen
Gas Clean Filter Moisture

Decomposition products may include the following materials:
metal oxide/oxides
Decomposition products may include the following materials:
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Gas Clean Filter Oxygen
Gas Clean Filter Moisture

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Gas Clean Filter Oxygen
Gas Clean Filter Moisture

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Gas Clean Filter Oxygen
Gas Clean Filter Moisture

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal

Section 6. Accidental release measures

For emergency responders : Gas Clean Filter Oxygen

Gas Clean Filter Moisture

risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Gas Clean Filter Oxygen

Gas Clean Filter Moisture

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Gas Clean Filter Oxygen

Gas Clean Filter Moisture

Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures : Gas Clean Filter Oxygen

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

Section 7. Handling and storage

	Gas Clean Filter Moisture	Empty containers retain product residue and can be hazardous. Do not reuse container. Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Gas Clean Filter Oxygen	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
	Gas Clean Filter Moisture	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Gas Clean Filter Oxygen	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
	Gas Clean Filter Moisture	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Section 7. Handling and storage


Recommendations	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Industrial applications, Professional applications. Industrial applications, Professional applications.
Industrial sector specific solutions	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
<div>  Gas Clean Filter Oxygen Copper oxide, Activated </div>	<p>NIOSH REL (United States, 10/2020). [COPPER FUME] TWA: 0.1 mg/m³, (as Cu) 10 hours. Form: Fume</p> <p>OSHA PEL 1989 (United States, 3/1989). [Copper Fume (as Cu)] TWA: 0.1 mg/m³, (as Cu) 8 hours. Form: Fume</p> <p>ACGIH TLV (United States, 1/2023). [copper fume] TWA: 0.2 mg/m³ 8 hours. Form: Fume</p> <p>CAL OSHA PEL (United States, 5/2018). [copper salts] TWA: 1 mg/m³, (as Cu) 8 hours. Form: dust and mist</p>
Manganese dioxide	<p>OSHA PEL 1989 (United States, 3/1989). [Manganese compounds (as Mn)] CEIL: 5 mg/m³, (as Mn)</p> <p>OSHA PEL (United States, 5/2018). [Manganese compounds] CEIL: 5 mg/m³, (as Mn)</p> <p>NIOSH REL (United States, 10/2020). [manganese compounds and fume] TWA: 1 mg/m³, (as Mn) 10 hours. Form: Fume STEL: 3 mg/m³, (as Mn) 15 minutes. Form: Fume</p> <p>OSHA PEL 1989 (United States, 3/1989). [Manganese fume] TWA: 1 mg/m³, (as Mn) 8 hours. Form: Fume STEL: 3 mg/m³, (as Mn) 15 minutes. Form: Fume</p> <p>ACGIH TLV (United States, 1/2023). [Manganese and inorganic compounds] TWA: 0.1 mg/m³, (as Mn) 8 hours. Form: Inhalable fraction TWA: 0.02 mg/m³, (as Mn) 8 hours. Form: Respirable fraction</p> <p>CAL OSHA PEL (United States, 5/2018). [manganese and compounds] TWA: 0.2 mg/m³, (as Mn) 8 hours.</p>
nickel monoxide	<p>OSHA PEL 1989 (United States, 3/1989). [Nickel, metal and insoluble compounds (as Ni)]</p>

Section 8. Exposure controls/personal protection

Gas Clean Filter Moisture

crystalline silica, respirable powder

cristobalite

TWA: 1 mg/m³, (as Ni) 8 hours.
ACGIH TLV (United States, 1/2023). [Nickel, insoluble inorganic compounds]

TWA: 0.2 mg/m³, (as Ni) 8 hours. Form: Inhalable fraction

NIOSH REL (United States, 10/2020). [nickel metal and other compounds]

TWA: 0.015 mg/m³, (as Ni) 10 hours.

OSHA PEL (United States, 5/2018). [Nickel, metal and insoluble compounds]

TWA: 1 mg/m³, (as Ni) 8 hours.

CAL OSHA PEL (United States, 5/2018). [nickel, insoluble compounds]

TWA: 0.1 mg/m³, (as Ni) 8 hours.

CAL OSHA PEL (United States, 5/2018).

TWA: 0.05 mg/m³ 8 hours.

OSHA PEL Z3 (United States, 6/2016).

TWA: 250 mppcf / (%SiO₂+5) 8 hours. Form: Respirable

TWA: 10 mg/m³ / (%SiO₂+2) 8 hours. Form: Respirable

OSHA PEL 1989 (United States, 3/1989).

TWA: 0.1 mg/m³, (as quartz) 8 hours. Form: Respirable dust

OSHA PEL (United States, 5/2018). [Silica, crystalline]

TWA: 50 µg/m³ 8 hours. Form: Respirable dust

ACGIH TLV (United States, 1/2023). [Silica, crystalline]

TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction

NIOSH REL (United States, 10/2020).

[SILICA, CRYSTALLINE]

TWA: 0.05 mg/m³ 10 hours. Form: respirable dust

OSHA PEL Z3 (United States, 6/2016).

TWA: 250 mppcf / 2 x (%SiO₂+5) 8 hours. Form: Respirable

TWA: 10 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Respirable

TWA: 30 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Total dust

OSHA PEL 1989 (United States, 3/1989).

TWA: 0.05 mg/m³, (as quartz) 8 hours. Form: Respirable dust

OSHA PEL (United States, 5/2018). [Silica, crystalline]

TWA: 50 µg/m³ 8 hours. Form: Respirable dust

ACGIH TLV (United States, 1/2023). [Silica, crystalline]

TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction

NIOSH REL (United States, 10/2020).

[SILICA, CRYSTALLINE]

Section 8. Exposure controls/personal protection

	<p>TWA: 0.05 mg/m³ 10 hours. Form: respirable dust</p> <p>CAL OSHA PEL (United States, 5/2018).</p> <p>TWA: 0.05 mg/m³ 8 hours. Form: respirable dust</p>
--	--

Biological exposure indices

Ingredient name	Exposure indices
Gas Clean Filter Oxygen nickel monoxide	<p>ACGIH BEI (United States, 1/2023) [nickel and inorganic compounds]</p> <p>BEI: 30 µg/l, nickel [in urine after exposure to soluble compounds]. Sampling time: post-shift at end of workweek.</p> <p>BEI: 5 µg/l, nickel [in urine after exposure to elemental nickel and poorly soluble compounds]. Sampling time: post-shift at end of workweek.</p>

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.








Section 8. Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Solid. [Granular solid.] Solid. [Granular solid.]						
Color	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Brown. [Dark] Tan.						
Odor	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Odor threshold	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
pH	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Melting point/freezing point	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Boiling point, initial boiling point, and boiling range	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Flash point	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not applicable. Closed cup: >535°C (>995°F)						
Evaporation rate	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Flammability	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Lower and upper explosion limit/flammability limit	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not applicable. Not applicable.						
Vapor pressure	:  Not available.							
Relative vapor density	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not applicable. Not applicable.						
Relative density	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Solubility(ies)	: <table border="1"><thead><tr><th>Media</th><th>Result</th></tr></thead><tbody><tr><td> Gas Clean Filter Oxygen water</td><td>Soluble</td></tr><tr><td> Gas Clean Filter Moisture water</td><td>Soluble</td></tr></tbody></table>	Media	Result	 Gas Clean Filter Oxygen water	Soluble	 Gas Clean Filter Moisture water	Soluble	
Media	Result							
 Gas Clean Filter Oxygen water	Soluble							
 Gas Clean Filter Moisture water	Soluble							
Partition coefficient: n-octanol/water	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not applicable. Not applicable.						
Auto-ignition temperature	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not applicable. Not applicable.						
Decomposition temperature	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not available. Not available.						
Viscosity	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Not applicable. Not applicable.						

Section 9. Physical and chemical properties and safety characteristics

Particle characteristics

Median particle size	: Gas Clean Filter Oxygen	Not available.
	Gas Clean Filter Moisture	Not available.

Section 10. Stability and reactivity

10.1 Reactivity	: Gas Clean Filter Oxygen	No specific test data related to reactivity available for this product or its ingredients.
	Gas Clean Filter Moisture	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Gas Clean Filter Oxygen	The product is stable.
	Gas Clean Filter Moisture	The product is stable.
10.3 Possibility of hazardous reactions	: Gas Clean Filter Oxygen	Under normal conditions of storage and use, hazardous reactions will not occur.
	Gas Clean Filter Moisture	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Gas Clean Filter Oxygen	No specific data.
	Gas Clean Filter Moisture	No specific data.
10.5 Incompatible materials	: Gas Clean Filter Oxygen	May react or be incompatible with oxidizing materials.
	Gas Clean Filter Moisture	May react or be incompatible with oxidizing materials.
10.6 Hazardous decomposition products	: Gas Clean Filter Oxygen	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
	Gas Clean Filter Moisture	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Gas Clean Filter Oxygen	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
Copper oxide, Activated	LD50 Oral	Rat	470 mg/kg	-
Manganese dioxide	LD50 Oral	Rat	3478 mg/kg	-
nickel monoxide	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5.08 mg/l	4 hours

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity


Conclusion/Summary : Not available.

Carcinogenicity

Section 11. Toxicological information

Conclusion/Summary : Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
 Gas Clean Filter Oxygen nickel monoxide	-	1	Known to be a human carcinogen.
Gas Clean Filter Moisture crystalline silica, respirable powder	+	1	Known to be a human carcinogen.
cristobalite	+	1	Known to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)


Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Gas Clean Filter Oxygen Manganese dioxide nickel monoxide	Category 2 Category 1	inhalation inhalation	brain lungs
Gas Clean Filter Moisture crystalline silica, respirable powder cristobalite	Category 1 Category 1	inhalation inhalation	lungs lungs

Aspiration hazard

Not available.

Information on the likely routes of exposure :  Gas Clean Filter Oxygen
Gas Clean Filter Moisture

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.
Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	No known significant effects or critical hazards. No known significant effects or critical hazards.
Inhalation	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	Harmful if inhaled. No known significant effects or critical hazards.
Skin contact	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	May cause an allergic skin reaction. No known significant effects or critical hazards.
Ingestion	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	No known significant effects or critical hazards. No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	No specific data. No specific data.
Inhalation	: Gas Clean Filter Oxygen Gas Clean Filter Moisture	No specific data. No specific data.

Section 11. Toxicological information

Skin contact	: Gas Clean Filter Oxygen	Adverse symptoms may include the following: irritation redness
	: Gas Clean Filter Moisture	No specific data.
Ingestion	: Gas Clean Filter Oxygen	No specific data.
	: Gas Clean Filter Moisture	No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.


Potential chronic health effects

General	: Gas Clean Filter Oxygen	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
	: Gas Clean Filter Moisture	Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: Gas Clean Filter Oxygen	May cause cancer. Risk of cancer depends on duration and level of exposure.
	: Gas Clean Filter Moisture	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: Gas Clean Filter Oxygen	No known significant effects or critical hazards.
	: Gas Clean Filter Moisture	No known significant effects or critical hazards.
Reproductive toxicity	: Gas Clean Filter Oxygen	No known significant effects or critical hazards.
	: Gas Clean Filter Moisture	No known significant effects or critical hazards.

Numerical measures of toxicity


Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Gas Clean Filter Oxygen					
Gas Clean Filter Oxygen	4579.9	27472.5	N/A	N/A	1.6
Copper oxide, Activated	470	2500	N/A	N/A	N/A
Manganese dioxide	3478	N/A	N/A	N/A	1.5

Other information	:  Gas Clean Filter Oxygen	Adverse symptoms may include the following: pulmonary fibrosis (dust). May cause skin sensitization.
--------------------------	---	---

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
 Gas Clean Filter Oxygen Copper oxide, Activated	Acute LC50 2.6 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
Manganese dioxide	Acute LC50 >56000 ppm Fresh water	Fish - <i>Gambusia affinis</i> - Adult	96 hours
	Acute EC50 >100 mg/l Fresh water	Algae - <i>Desmodesmus subspicatus</i>	72 hours
	Acute EC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 >100 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Acute NOEC >100 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Chronic NOEC 10 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	8 days

12.2 Persistence and degradability

Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Gas Clean Filter Oxygen nickel monoxide	-	5613	High

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / IATA : Not regulated.

Special precautions for user : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : **TSCA 8(a) CDR Exempt/Partial exemption**: Not determined
Clean Water Act (CWA) 307: Copper oxide, Activated; nickel monoxide
Clean Water Act (CWA) 311: Sulphuric acid

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
Gas Clean Filter Oxygen Sulphuric acid	≤0.1	Yes.	1000	66.3	1000	66.3

SARA 304 RQ : 4000000 lbs / 1816000 kg

SARA 311/312

Classification :  Gas Clean Filter Oxygen
 Gas Clean Filter Moisture

ACUTE TOXICITY (inhalation) - Category 4
 SKIN SENSITIZATION - Category 1
 CARCINOGENICITY - Category 1A
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
 CARCINOGENICITY - Category 1A
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Composition/information on ingredients

Section 15. Regulatory information

Name	%	Classification
Gas Clean Filter Oxygen Copper oxide, Activated Manganese dioxide	≤10 ≤10	ACUTE TOXICITY (oral) - Category 4 OXIDIZING SOLIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
nickel monoxide	<1	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Gas Clean Filter Moisture crystalline silica, respirable powder cristobalite	≤10 ≤10	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Gas Clean Filter Oxygen Copper oxide, Activated Manganese dioxide nickel monoxide	1317-38-0 1313-13-9 1313-99-1	≤10 ≤10 <1
Supplier notification	Gas Clean Filter Oxygen Copper oxide, Activated Manganese dioxide nickel monoxide	1317-38-0 1313-13-9 1313-99-1	≤10 ≤10 <1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: ALUMINUM OXIDE; SILICA, CRYSTALLINE, QUARTZ; CRISTOBALITE DUST

New York

: None of the components are listed.

New Jersey

: The following components are listed: ALUMINUM OXIDE; COPPER compounds; SILICA, QUARTZ; SILICA, CRISTOBALITE; NICKEL OXIDE

Pennsylvania

: The following components are listed: ALUMINUM OXIDE; COPPER COMPOUNDS; QUARTZ DUST; CRISTOBALITE DUST; MANGANESE COMPOUNDS

California Prop. 65

WARNING: This product can expose you to chemicals including Silica, crystalline, Silica, crystalline, Nickel oxide and Strong inorganic acid mists containing sulfuric acid, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Gas Clean Filter Oxygen Nickel oxide Strong inorganic acid mists containing sulfuric acid	- -	- -
Gas Clean Filter Moisture Silica, crystalline Silica, crystalline	- -	- -

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Section 15. Regulatory information

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: Not determined.
China	: All components are listed or exempted.
Japan	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: All components are listed or exempted.
Thailand	: All components are listed or exempted.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
Gas Clean Filter Oxygen ACUTE TOXICITY (inhalation) - Category 4 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method
Gas Clean Filter Moisture CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method Calculation method

History

Date of issue/Date of revision	: 03/06/2024
Date of previous issue	: 11/09/2021
Version	: 6

Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
UN = United Nations

📌 Indicates information that has changed from previously issued version.

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.