SAFETY DATA SHEET



537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : 537.1 Internal primary dilution std, Part Number PFS-537-IPDS

Part no. : PFS-537-IPDS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagents and Standards for Analytical Chemistry Laboratory Use

vial 1 x 1.2 ml

Uses advised against : None known.

1.3 Details of the supplier of the safety data sheet

Agilent Technologies Deutschland GmbH Hewlett-Packard-Str. 8

76337 Waldbronn

Germany 0800 603 1000

e-mail address of person : pdl-msds_author@agilent.com

responsible for this SDS

1.4 Emergency telephone number

Emergency telephone: CHEMT

number (with hours of

operation)

: CHEMTREC®: +(44)-870-8200418

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

H225FLAMMABLE LIQUIDSCategory 2H301ACUTE TOXICITY (oral)Category 3H311ACUTE TOXICITY (dermal)Category 3H331ACUTE TOXICITY (inhalation)Category 3H370SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURECategory 1

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :







Signal word : Danger

Hazard statements: H225 - Highly flammable liquid and vapour.

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled.

H370 - Causes damage to organs.

Precautionary statements

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 1/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 2: Hazards identification

: P280 - Wear protective gloves and protective clothing. **Prevention**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 - Do not breathe vapour.

: P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor. Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

: P501 - Dispose of contents and container in accordance with all local, regional, national **Disposal**

and international regulations.

Hazardous ingredients

Supplemental label

: methanol

elements

: Not applicable.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market

and use of certain dangerous substances, mixtures and articles

Special packaging requirements

Tactile warning of

danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do

not result in classification : None known.

SECTION 3: Composition/information on ingredients

: Mixture 3.2 Mixtures

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
|-------------------------|-------------------------------|-----|---|---|---------|
| methanol | EC: 200-659-6 CAS: 67-56-1 | ≥90 | Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 (central nervous system (CNS), optic nerve) | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 3 mg/l STOT SE 1, H370: $C \ge 10\%$ STOT SE 2, H371: $3\% \le C < 10\%$ | [1] [2] |
| | | | See Section 16 for the full text of the H statements declared above. | | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version: 1 2/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 3: Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention. If necessary, call a poison center or physician.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth

with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain

an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.

Inhalation : Toxic if inhaled. Causes damage to organs following a single exposure if inhaled.

Skin contact : Toxic in contact with skin. Causes damage to organs following a single exposure in

contact with skin.

Ingestion: Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 3/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide Formaldehyde.

5.3 Advice for firefighters

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 4/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Storage

: Store between the following temperatures: room temperature. Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

| Category | Notification and MAP threshold | P Safety report threshold |
|----------|--------------------------------|---------------------------|
| H2 | 50 tonne | 200 tonne |
| H3 | 50 tonne | 200 tonne |
| P5c | 5000 tonne | 50000 tonne |

7.3 Specific end use(s)

Recommendations: Industrial applications, Professional applications.

Industrial sector specific

solutions

: Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|-------------------------|--|
| Methanol | NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values |
| | OELV: 200 ppm 8 hours. OELV: 260 mg/m³ 8 hours. |

Biological exposure indices

| Product/ingredient name | Exposure indices |
|-------------------------|---|
| | NAOSH (Ireland, 1/2011) BMGV: 15 mg/l, methanol [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases. |

Date of issue/Date of revision: 02/05/2024Date of previous issue: No previous validationVersion: 1

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|-------------------------|------|--------------------------|-----------------------|-----------------------|----------|
| Methanol | DNEL | Short term Oral | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Oral | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 4 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 20 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Dermal | 20 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Inhalation | 26 mg/m³ | General population | Local |
| | DNEL | Long term Inhalation | 26 mg/m³ | General population | Local |
| | DNEL | Short term Inhalation | 26 mg/m³ | General population | Systemic |
| | DNEL | Long term Inhalation | 26 mg/m³ | General population | Systemic |
| | DNEL | Short term Inhalation | 130 mg/m³ | Workers | Local |
| | DNEL | Long term Inhalation | 130 mg/m³ | Workers | Local |
| | DNEL | Short term Inhalation | 130 mg/m³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 130 mg/m ³ | Workers | Systemic |

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 6/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 8: Exposure controls/personal protection

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour : Colourless. Odour : Pungent. **Odour threshold** : Not available.

Melting point/freezing

point

Initial boiling point and : 64.7°C

boiling range

Flammability : Not applicable. **Upper/lower flammability** : Lower: 6% or explosive limits **Upper: 36%**

Flash point : Closed cup: 9.7°C [Based on solvent.] : 455°C

: -98°C

Auto-ignition

temperature

Not available.

Decomposition temperature

pΗ Not available. Not available. **Viscosity**

Solubility(ies) Media Result

water Soluble

Miscible with water Yes. Partition coefficient: n-

octanol/water

: -0.77

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version: 1 7/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 9: Physical and chemical properties

Vapour pressure : 13 kPa (97.7 mm Hg) [room temperature]

54.7 kPa (410 mm Hg) [50°C]

Evaporation rate : Not available.

Relative density : Not available.

Density : 0.791 g/cm³ [25°C]

Vapour density : 1.11 [Air = 1]

Explosive properties : Not available.

Oxidising properties : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapour to accumulate in low or confined areas.

10.5 Incompatible

materials

: Reactive or incompatible with the following materials:

oxidising materials

Reactive or incompatible with the following materials: reducing materials and acids.

Acid Chlorides anhydride Alkali metal salt.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|--|---|---|---|
| Methanol | LC50 Inhalation Vapour LC50 Inhalation Vapour LC50 Inhalation Vapour LC50 Inhalation Vapour LD50 Dermal LD50 Oral | Rat Rat Rat Rat Rabbit Rat | 189.95 mg/l 145000 ppm 83.84 mg/l 64000 ppm 15800 mg/kg 5600 mg/kg | 1 hours 1 hours 4 hours 4 hours - |

Acute toxicity estimates

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 8/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 11: Toxicological information

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|------------------|-------------------|--------------------------------|-----------------------------------|--|
| 537.1 Internal primary dilution std, Part Number PFS-537-IPDS Methanol | 100.0 | | N/A N/A | | N/A N/A |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--|---------|-------|----------------------|-------------|
| Methanol | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 | - |
| | Eves Moderate irritant | Rabbit | | mg | |
| | Eyes - Moderate irritant Skin - Moderate irritant | Rabbit | - | 40 mg 24 hours 20 | - |
| | | | | mg | |

Skin : Repeated exposure may cause skin dryness or cracking.

Eyes: May cause eye irritation.

Sensitiser

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Repeated or prolonged exposure to the substance can produce reproductive system

damage.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---|
| Methanol | Category 1 | - | central nervous system (CNS), optic nerve |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation: Toxic if inhaled. Causes damage to organs following a single exposure if inhaled.

Ingestion : Toxic if swallowed. Causes damage to organs following a single exposure if swallowed.
 Skin contact : Toxic in contact with skin. Causes damage to organs following a single exposure in

contact with akin

contact with skin.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No specific data.Ingestion: No specific data.Skin contact: No specific data.Eye contact: No specific data.

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 9/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 11: Toxicological information

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

: Not available.

effects

Potential delayed

effects

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed

: Not available.

effects

Potential chronic health effects

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Adverse symptoms may include the following: blurred or double vision, Eye contact can result in corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage. Narcotic effect. May cause nervous system disturbances.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--|--|----------------------|
| Methanol | Acute EC50 2736 mg/l Marine water | Algae - <i>Ulva pertusa</i> | 96 hours |
| | Acute LC50 2500000 μg/l Marine water | Crustaceans - <i>Crangon crangon</i> - Adult | 48 hours |
| | Acute LC50 3289 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> - Neonate | 48 hours |
| | Acute LC50 290 mg/l Fresh water Chronic NOEC 9.96 mg/l Marine water | Fish - <i>Danio rerio</i> - Egg Algae - <i>Ulva pertusa</i> | 96 hours 96 hours |

12.2 Persistence and degradability

Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Methanol | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|---|--------|-----|-----------|
| 537.1 Internal primary dilution std, Part Number PFS-537-IPDS | -0.77 | - | Low |
| Methanol | -0.77 | <10 | Low |

12.4 Mobility in soil

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version: 1 10/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 12: Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Packaging
Methods of disposal

: The classification of the product may meet the criteria for a hazardous waste.

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA |
|----------------------------------|-------------------|-------------------|-------------------|
| 14.1 UN number or ID number | UN1230 | UN1230 | UN1230 |
| 14.2 UN proper shipping name | METHANOL solution | METHANOL solution | Methanol solution |
| 14.3 Transport hazard class(es) | 3 (6.1) | 3 (6.1) | 3 (6.1) |
| 14.4 Packing group | II | II | II |
| 14.5 Environmental hazards | No. | No. | No. |

Additional information

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version :1 11/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 14: Transport information

Remarks: Excepted Quantity

ADR/RID : <u>Hazard identification number</u> 336

Limited quantity 1 L Special provisions 279 Tunnel code (D/E)

IMDG : <u>Emergency schedules</u> F-E, S-D

Special provisions 279

IATA : **Quantity limitation** Passenger and Cargo Aircraft: 1 L. Packaging instructions: 352.

Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger

Aircraft: 1 L. Packaging instructions: Y341.

Special provisions A113

14.6 Special precautions

for user

instruments

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

14.7 Transport in bulk according to IMO

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product / Ingredient name | Identifiers | Designation [Usage] |
|--|-------------------------------|---------------------|
| 537.1 Internal primary dilution std, Part Number PFS-537-IPDS | - | 3 |
| | EC: 200-659-6 CAS: 67-56-1 | 69 |
| Perfluorooctanoic acid (13C8) | CAS: 1350614-84-4 | 68 |

Label : Not applicable.

Other EU regulations

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category | |
|-----------------|--|
| H2 H3 P5c | |
| H3 | |
| P5c | |

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 12/14

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 15: Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

Canada : All components are listed or exempted.

China : Not determined.

Eurasian Economic

Union

: Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

: Not determined. **New Zealand** : Not determined. **Philippines** Republic of Korea : Not determined. **Taiwan** : Not determined. **Thailand** : Not determined. **Turkey** : Not determined. **United States** : Not determined. **Viet Nam** : Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments might still

be required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|--------------------|-----------------------|
| Flam. Liq. 2, H225 | On basis of test data |
| Acute Tox. 3, H301 | Calculation method |
| Acute Tox. 3, H311 | Calculation method |
| Acute Tox. 3, H331 | Calculation method |
| STOT SE 1, H370 | Calculation method |

537.1 Internal primary dilution std, Part Number PFS-537-IPDS

SECTION 16: Other information

Full text of abbreviated H statements

| TOXIC II IIII aled. | H301 H311 | Highly flammable liquid and vapour. Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. |
|-------------------------------|--------------|---|
| H370 Causes damage to organs. | | |

Full text of classifications [CLP/GHS]

| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
|--------------|--|
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| STOT SÉ 1 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - |
| | Category 1 |

Date of issue/ Date of

revision

: 02/05/2024

Date of previous issue

: No previous validation

Version : 1

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

Date of issue/Date of revision : 02/05/2024 Date of previous issue : No previous validation Version : 1 14/14