# SAFETY DATA SHEET

Agilent Technologies

1/13

PLgel in ethylbenzene - 10-30 ml

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

#### **1.1 Product identifier**

Product name	: PLgel in ethylbenzene - 10-30 ml
Part no.	: FL1110-8520, PL1010-6300, PL1010-5200, PL1115-9999EDG

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses	: Analytical chemistry. chromatography column	
	Solvent volume: 10 - 30 ml	
	PL1110-8520 PLgel 5um 100A 600 x 7.5mm	
	PL1010-6300 PLgel 3 µm MIXED-E, 300 x 10 mm	
	PL1010-5200 PLgel 20um Mixed-A, 250 x 10mm,16mL	
	PL1115-9999EDG GPC Custom Column, max 30mL solver	nt

#### 1.3 Details of the supplier of the safety data sheet

Agilent Technologies LDA UK Ltd. 5500 Lakeside Cheadle Royal Business Park, Cheadle, Cheshire, SK8 3GR United Kingdom Tel: +44 (0) 345 712 5292 e-mail address of person : pdl-msds\_author@agilent.com responsible for this SDS

1.4 Emergency telephone number

Emergency telephone : CHEMTREC®: +(44)-870-8200418 number (with hours of operation)

### **SECTION 2: Hazards identification**

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the	substance or mixture	
Product definition	: Mixture (encapsulated in article)	
<b>Classification accordin</b>	ig to Regulation (EC) No. 1272/2008 [CLP/GHS]	
<b>H</b> 225	FLAMMABLE LIQUIDS	Category 2
H332	ACUTE TOXICITY (inhalation)	Category 4
H373	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	Category 2
H304	ASPIRATION HAZARD	Category 1
Ingredients of unknow toxicity	<ul> <li>Percentage of the mixture consisting of ingredient(s) of toxicity: 10 - 30%</li> </ul>	f unknown acute inhalation
Ingredients of unknow ecotoxicity	n : Contains 30% of components with unknown hazards to	o the aquatic environment
See Section 16 for the fu	Ill text of the H statements declared above.	

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision : 21/04/2022 Date of previous issue : 02/04/2019 Version : 5	5 ,
---	-----

## **SECTION 2: Hazards identification**

ż

### 2.2 Label elements

Hazard pictograms



Signal word	:	Danger
Hazard statements		<ul> <li>Highly flammable liquid and vapour.</li> <li>H304 - May be fatal if swallowed and enters airways.</li> <li>H332 - Harmful if inhaled.</li> <li>H373 - May cause damage to organs through prolonged or repeated exposure.</li> </ul>
Precautionary statements		
Prevention	:	210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe vapour.
Response	:	₱314 - Get medical advice/attention if you feel unwell. P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	- ethylbenzene
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging require	m	<u>ents</u>
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

### **SECTION 3: Composition/information on ingredients**

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

3.1 Substances : Mixture (encapsulated in article)

### **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
ethylbenzene	EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥50 - ≤75	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	eyelids. C	By flush eyes with plenty of water, occasionally lifting the upper and lower Check for and remove any contact lenses. Continue to rinse for at least 10 Get medical attention following exposure or if feeling unwell.
Inhalation	s suspecto or self-con espiratory nay be da Get medic center or p	ictim to fresh air and keep at rest in a position comfortable for breathing. If it ed that fumes are still present, the rescuer should wear an appropriate mask nationed breathing apparatus. If not breathing, if breathing is irregular or if arrest occurs, provide artificial respiration or oxygen by trained personnel. It ingerous to the person providing aid to give mouth-to-mouth resuscitation. Fal attention following exposure or if feeling unwell. If necessary, call a poison obysician. If unconscious, place in recovery position and get medical attention ely. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt nd.
Skin contact	hoes. Co	aminated skin with plenty of water. Remove contaminated clothing and ontinue to rinse for at least 10 minutes. Get medical attention following or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly se.
Ingestion	with water person is o eels sick a ungs and pe kept low inconscio attention ir	al attention immediately. Call a poison center or physician. Wash out mouth . Remove dentures if any. If material has been swallowed and the exposed conscious, give small quantities of water to drink. Stop if the exposed person as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter cause damage. Do not induce vomiting. If vomiting occurs, the head should w so that vomit does not enter the lungs. Never give anything by mouth to an us person. If unconscious, place in recovery position and get medical mmediately. Maintain an open airway. Loosen tight clothing such as a collar, waistband.
Protection of first-aiders	uspected elf-contai	shall be taken involving any personal risk or without suitable training. If it is that fumes are still present, the rescuer should wear an appropriate mask or ned breathing apparatus. It may be dangerous to the person providing aid to n-to-mouth resuscitation.
4.2 Most important symptor	nd effect	ts, both acute and delayed
Potential acute health effe		
Eye contact	lo known	significant effects or critical hazards.
Inhalation	larmful if	inhaled.
Skin contact	lo known	significant effects or critical hazards.

### **SECTION 4: First aid measures**

Ingestion	: May be fatal if swallowed and enters airways.
Over-exposure signs/s	symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: Adverse symptoms may include the following: nausea or vomiting
4.3 Indication of any im	mediate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>

**Specific treatments** : No specific treatment.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	<ul> <li>Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.</li> </ul>
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire- fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions	s, protective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### SECTION 6: Accidental release measures

6.3 Methods and material for	or containment and cleaning up
Methods for cleaning up	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

	•
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Storage Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

#### **Danger criteria**

	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

#### 7.3 Specific end use(s)

Recommendations			
Industrial sector specific			
solutions			

: Industrial applications, Professional applications.

SECTION 8: Exposure controls/personal protection

: Not available.

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

#### 8.1 Control parameters

#### **Occupational exposure limits**

### **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	nrough skin. STEL: 552 mg/m³ 15 minutes.		
5	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 552 mg/m <sup>3</sup> 15 minutes. STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours. TWA: 441 mg/m <sup>3</sup> 8 hours.		

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
ethylbenzene	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	15 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	293 mg/m³	Workers	Local
	DMEL	Long term Inhalation	442 mg/m³	Workers	Local
	DMEL	Short term Inhalation	884 mg/m³	Workers	Systemic

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

Appropriate engineering	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or
controls	other engineering controls to keep worker exposure to airborne contaminants below any
	recommended or statutory limits. The engineering controls also need to keep gas,
	vapour or dust concentrations below any lower explosive limits. Use explosion-proof
	ventilation equipment.

#### Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	

### **SECTION 8: Exposure controls/personal protection**

Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

9.1 mornation on basic pri	y s	ical and chemical properties
Appearance		
Physical state	:	Solid.(containing flammable liquid)
Colour	:	White.
Odour	:	Aromatic.
Odour threshold	:	Not available.
Melting point/freezing point	:	-95°C
Initial boiling point and boiling range	:	136°C (276.8°F)
Flammability (solid, gas)	:	Contains: Flammable liquid.
Upper/lower flammability or explosive limits	:	Lower: 0.8% Upper: 6.7%
Flash point	:	Closed cup: 21°C (69.8°F)
Auto-ignition temperature	:	432.22°C (810°F)
Decomposition temperature	:	Not available.
рН	:	Not available.
Viscosity	1	Not available.
Solubility(ies)	:	Mobile phase / Stationary phase: Insoluble.
Miscible with water	1	No.
Partition coefficient: n- octanol/water	:	Not applicable.
Vapour pressure	:	

### **SECTION 9: Physical and chemical properties**

		Ingredient name	Vapou	r Pressu	ire at 20°C	Va	pour pres	ssure at 50°C
			mm Hg	kPa	Method	mm Hg	kPa	Method
		ethylbenzene	9.3	1.2				
Evaporation rate	:	Not available.					I	
Relative density	:	0.9						
Density	:	0.9 g/cm <sup>3</sup> [20°C (68°	F)]					
Vapour density	:	Not available.						
Oxidising properties	:	Not available.						
Particle characteristics								
Median particle size	:	Not applicable.						

No additional information.

SECTION 10: Stabi	lity and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
<b>e</b> thylbenzene	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg 3500 mg/kg	-

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Lgel in ethylbenzene - 10-30 ml ethylbenzene			N/A N/A	11 11	N/A N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethylbenzene	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	500 mg 24 hours 15 mg	-
Skin :	Repeated exposure may cause skin dryness or cracking.				

# **SECTION 11: Toxicological information**

Sensitiser	
<b>Conclusion/Summary</b>	: Not available.
Mutagenicity	
<b>Conclusion/Summary</b>	: Not available.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: Not available.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.
Specific target organ tox	<u>kicity (single exposure)</u>
Not available.	

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

#### **Aspiration hazard**

Product/ingredient name		Result			
PLgel in ethylbenzene - 1 ethylbenzene	0-30 ml	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1			
Information on likely routes of exposure	: Routes of entry anticipated: Ora	l, Dermal, Inhalation.			
Potential acute health ef	<u>fects</u>				
Inhalation	: Harmful if inhaled.				
Ingestion	: May be fatal if swallowed and er	May be fatal if swallowed and enters airways.			
Skin contact	: No known significant effects or o	critical hazards.			
Eye contact	: No known significant effects or o	No known significant effects or critical hazards.			
Symptoms related to the	physical, chemical and toxicologic	cal characteristics			
Inhalation	: No specific data.				
Ingestion	: Adverse symptoms may include nausea or vomiting	the following:			
Skin contact	: No specific data.				
Eye contact	: No specific data.				
Delayed and immediate	<u>effects as well as chronic effects fr</u>	om short and long-tern	<u>n exposure</u>		
<u>Short term exposure</u>					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Long term exposure					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Potential chronic health	<u>effects</u>				
General	: May cause damage to organs the	rough prolonged or repe	ated exposure.		
Carcinogenicity	: No known significant effects or o	critical hazards.			
Mutagenicity	: No known significant effects or o	critical hazards.			
Reproductive toxicity	: No known significant effects or o	critical hazards.			
ate of issue/Date of revision	: 21/04/2022 Date of previous issue	: 02/04/2019	Version : 5	9/13	

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ethylbenzene	Acute EC50 4900 μg/l Marine water Acute EC50 7700 μg/l Marine water Acute EC50 6.53 mg/l Marine water	Algae - Skeletonema costatum Algae - Skeletonema costatum Crustaceans - Artemia sp Nauplii	72 hours 96 hours 48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 μg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
ethylbenzene	ISO	70 to 80 %	- Readily - 28 days	-		Activated sludge
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
ethylbenzene	-		-		Readily	

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
ethylbenzene	3.6	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

13.1 Waste treatment met	hods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
Date of issue/Date of revision	: 21/04/2022 Date of previous issue : 02/04/2019 Version : 5 10/13

### **SECTION 14: Transport information**

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	UN3175	UN3175	UN3175
14.2 UN proper shipping name	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethylbenzene)	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethylbenzene)	Solids containing flammable liquid, n.o.s. (ethylbenzene)
14.3 Transport hazard class(es)	4.1	4.1	4.1
14.4 Packing group	II	II	II
14.5 Environmental hazards	No.	No.	No.

#### Additional information

Remarks: Excepted Quantit	/
ADR/RID	<ul> <li>Hazard identification number 40 Limited quantity 1 kg</li> <li>Special provisions 216, 274, 601 Tunnel code (E)</li> </ul>
IMDG	: <u>Emergency schedules</u> F-A, S-I <u>Special provisions</u> 216, 274
ΙΑΤΑ	<ul> <li>Quantity limitation Passenger and Cargo Aircraft: 15 kg. Packaging instructions: 445. Cargo Aircraft Only: 50 kg. Packaging instructions: 448. Limited Quantities - Passenger Aircraft: 5 kg. Packaging instructions: Y441.</li> </ul>
14.6 Special precautions for user	: <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to IMO instruments	: Not available.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

# Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

EC number	CAS number	Restriction
202-849-4	100-41-4	3 3

### **SECTION 15: Regulatory information**

Label

: Not applicable.

#### **Other EU regulations**

Ozone depleting substances (1005/2009/EU) Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

Category

P5c

International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

#### Inventory list

Involution y not		
Australia	: All components are listed or exempted.	
Canada : All components are listed or exempted.		
China	: All components are listed or exempted.	
Europe	: All components are listed or exempted.	
Japan	: Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.	
New Zealand	: All components are listed or exempted.	
Philippines	: All components are listed or exempted.	
<b>Republic of Korea</b>	: All components are listed or exempted.	
Taiwan	: All components are listed or exempted.	
Thailand : Not determined.		
Turkey	: All components are listed or exempted.	
United States	: 🕅 components are active or exempted.	
Viet Nam	: All components are listed or exempted.	
15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments might still be required.	

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number</li> </ul>
	vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
<b>F</b> am. Liq. 2, H225	On basis of test data
Acute Tox. 4, H332	Calculation method
STOT RE 2, H373	Calculation method
Asp. Tox. 1, H304	Expert judgment

#### Full text of abbreviated H statements

H225 H304 H332 H373	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure.
------------------------------	--

#### Full text of classifications [CLP/GHS]

Acute Tox. 4 Asp. Tox. 1 Flam. Liq. 2 STOT RE 2		ACUTE TOXICITY - Category 4 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
Date of issue/ Date of	: 21/04/2022	

revision	
Date of previous issue	: 02/04/2019
Version	: 5

#### Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.